

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

50

S. E. Corner to Section 36, only, T31-3W. #198
Found - 40" W. Fir N. 55° W. 60.5 ft. shows good scar.
11" Cedar, now 14" N. 40° E. 68.5 ft., scribe visible "S1BT".
15" W. Fir, now stump, S. 16° W. 28.4 ft. Opened for scribe.
24" D. Fir, now down, S. 14° E. 7.9 ft.
2" Iron Pipe, bent over, under small Log, Ren. #41, T31-3W.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

John M. Powell & Crew
8/30/66
C.S.
File No. 54/28

Reblazed & Rescribed: T 32 S
14" Cedar N. 40° E. 68.5 ft. scribed T32S R3W S1 CS BT.
No other trees available. This corner lies just on S. side of small ridge, running E. - W.

8/30/66

MICROFILM TO HERE 10/67

51

1/4 Corner to Section 25 only, T32-3W.
Found - 50" Fir bears S.77°W. 52 lks. mkd: "1/4 S25 BT" with open face, scribes in good condition.
36" Fir bears N.21°W. 84 lks. mkd: "1/4 S25 BT" with open face, scribes in good condition.
Set - 2"x30" galv.I.P.with Brass Cap, stamped:

T 32 S
R3W 1/4 R2W
S25
1968
OLS 536

From the Pipe Monument, the Orig. BT's are:
42" Fir bears N.21°W. 55.4 ft. mkd: 1/4 S25 BT.
69" Fir bears S.77°W. 34.3 ft. mkd: 1/4 S25 BT.
Placed BT tags on all bearing trees and facing the monument.

52

1/4 Corner Section 24 only, T32-3W.
Found - Orig. Stone 18"x12"x4" marked "1/4" on west face.
Orig.12", now 20" Madrona with open face, scribes in poor condition, bears S. 36° W. 54.9 ft.
Set - 2"x30" I.P.with Brass Cap, stamped:

T 32 S
R3W 1/4 R2W
S 24
1968
OLS 536

From the pipe monument, I marked the trees:
27" Fir bears N.33°W. 25.5 ft. mkd: 1/4 S24 BT.
12" Fir bears S. 6°E. 15.3 ft. mkd: 1/4 S24 BT.
Placed BT tags on all bearing trees & facing the monument.

53

1/4 Corner to Section 18 only, T32-2W.
Found - Orig.24", now 38" Fir, S.20°W. 19.8 ft., opened face and found "1/4 S18 BT" in good condition.
Set - 2"x30" I.P. with Brass Cap stamped:

T 32 S
R3W 1/4 R2W
S 18
1968
OLS 536

From the Pipe Monument, the Orig. BT. is:
38" Fir bears S.20°W. 19.8 ft. mkd: 1/4 S18 BT.
New BT: 40" Fir bears S.27°E. 34.3 ft. mkd: "1/4 S18 BT".
Placed BT tags on all bearing trees and facing the monument.

54

Section Corner to Sections 19 and 30 only, T32-2W.
Found - Stone 24"x12"x5" with 2 notches on S. & 4 notches on N. edges.
Orig. 24", now 34" Fir, bears N.52°E. 4.0 ft., with scribes in poor condition.
Set - 2"x30" I.P.with Brass Cap stamped:

T 32 S
R3W S24 | S 19 R2W
S 30
1968
OLS 536

From the Pipe Monument, the Orig. BT. is:
34" Fir bears N.52°E. 4.0 ft. remkd: T32S R2W S19 BT.
New BT: 22" Fir bears S. 38° E. 22.5 ft. mkd: T32S R2W S30 BT.
Placed BT tags on all bearing trees & facing the monument.