

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

60

1/4 Corner to Section 7 only, T32-2W.
Found - Orig. 12", now 16" Fir marked "1/4 S7" on east face.
Orig. 12", now 16" Fir marked "1/4 S BT", bears N.62°W. 13.7 ft.
Set - 2"x30" I.P. with Brass Cap Mkd:

T 32 S
R3W 1/4 S 7 R2W
1968
OLS 536

Glenn S.
Baughman
Aug. 1968
C.S.
File
No. 55/87

From the Pipe Monument, the Orig. BT is:
16" Fir bears N.62°W. 13.7 ft, mkd: "1/4 SBT".
New BT: 20" Fir bears S.59°E. 26.0 ft. mkd: "1/4 S BT".
Placed BT tags on all bearing trees and facing the monument.

RE-RENEWED, SEE CORNER NO. #201

61

Section Corner to Sections 9 - 10 - 15 - 16.
Found - Granite Stone as recorded in Ren. #2.
22" Fir bears S.0°30'E. 36.1 ft., visible bark scribe.
10" S. Pine bears S.75°E. 4.0 ft., scribe visible.
8" Laurel bears N.77°W. 19.1 ft., closed face.
24" Fir Stump bears S. 1° E. 38.6 ft., scribe visible.
Set - Brass Cap at Cor. Stpd: Sec. Cor. 9, 10, 15 & 16, T32S R3W
OLS 536 1969

RE-RENEWED, SEE CORNER NO. #176

Scribed: 10" Laurel N. 57° 30' E. 18.9 ft.
Added Sept. 10 '69 - 6" D. Fir N. 54° W. 17.9 ft., mkd: T32S R3W S9 CS BT. (See C.S. 54/91)

62

1/4 Corner to Section 10 & 15.
Found - 30" D. Fir BT. bears N.59°E. 24.6 ft., bark scribe visible.
3/4" Iron Rod, See Ren. #14.
Set - Brass Cap at Cor. Stpd: 1/4 Cor. Sec. 10, 15, T 32 S, R 3 W.
OLS 536 1969
Scribed: 10" Incense Cedar bears S. 61° E. 19.1 ft.

RE-RENEWED, SEE CORNER NO. #205

Glenn S. Baughman
For Andrew Koch
March, 1969
Map File M 37 - 45

63

1/4 Corner to Section 3 and 10. Fd. OK L. HERZSTEIN
Found - 1 1/4" Iron Pipe, See Ren. #13. 7-14-81 C.S. 61/27
Bearing Tree Stumps, rotten, no scribes visible.
Set - Brass Cap at Cor. Stpd: 1/4 Cor. 3, 10, T.32 S, R 3 W
OLS 536 1969
Scribed: 10" W. Fir bears N. 16° E. 80.7 ft.
10" Fir Bears S. 9° W. 117.7 ft.

64

Section Corner to Sections 3 - 4 - 9 - 10.
Found - 2" I. Pipe, See Ren. #30.
30" W. Fir bears S.89°W. 140.0 ft., tag & scar.
20" Fir Snag bears N.70°E. 9.8 ft., tag & closed face.
24" Yew Wood bears S. 2° E. 184.4 ft., tag & scribe visible.
Set - Brass Cap at Cor. Stpd: Sec. Cor. Secs. 3, 4, 9 & 10, T32S R3W
OLS 536 1969
Scribed: 20" W. Fir bears N.84°E. 28.9 ft.

RE-RENEWED, SEE CORNER NO. #208

65

Section Corner to Sections 21 - 22 - 27 - 28.
Found - Unrecorded 3/4" Iron Bolt at Corner.
18x8x6 Stone, firmly set mkd; 3 notches on E. & 2 on South Side.
20" Fir, now rotted stump, N.66°E. 17.8 ft., no scribe found.
14", now 40" D. Fir, S.47°E. 38.9 ft., shows good scar.
20", now 42" D. Fir, S.18°W. 29.0 ft., shows good scar.
9", now 16" Alder, N.27°W. 5.3 ft., rotted face, old axework
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office S 21 | S 22
1969 S 28 | S 27
New BT's: 8" W. Fir N.52°E. 6.8 ft. mkd: T32S R3W S22 CS BT.
7" W. Fir N.70°W. 22.6 ft. mkd: T32SR3W S21 CS BT.
This corner lies in old N-S fence line.

Fd. OK
U.S. FS.
CS 61/32
6/7/82

John M. Powell
Frank Jones & W. Penley
July 7, 1969
C.S. File No. 54/91D

7/7/69