

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 3 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21801

John M. Powell
Frank Jones & W. Penley
July, 1969 C.S. File No. 54/91C

1/4 Corner to Sections 21 and 22. 66
Found - 15x8x6 Stone marked with a "4" visible.
36", now 46" D. Fir, N. 55° E. 40.3 ft., shows good scar.
28" D. Fir, now stump, N. 74° W. 48.8 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office, 1969 1/4 S 21 | S 22
New BT: 10" Laurel N. 3° E. 40.5 ft. mkd: "1/4 S22 CS BT".
This corner lies on steep southeast slope. No trees within reason to Sec. 21.

Section Corner to Sections 11 - 12 - 13 - 14. 67
Found - 15x12x10 Stone at Corner, notches visible.
24" Laurel, now dead, N. 35° E. 26.4 ft., shows scar.
12" Laurel, now down, lying on face, S. 33° E. 18.5 ft.
16" Laurel, now down, S. 31° W. 43.6 ft.
10" Laurel, now down, N. 32° W. 34.3 ft., opened for scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office 1969 S 11 | S 12
S 14 | S 13
New BT's: 16" D. Fir N. 12° W. 29.0 ft. mkd: T32S R3W S11 CS BT.
12" D. Fir N. 17° E. 38.5 ft. mkd: T32S R3WS12 CS BT.
18" Laurel S. 74° E. 23.6 ft. mkd; T32S R3W S13 CSBT.
20" Laurel S. 29° W. 43.3 ft. mkd: T32S R3W S14 CS BT.

1/4 Corner to Sections 11 and 12. 68
Found - 30", now 38" D. Fir, East 13.2 ft., shows good axe face.
30", now 37" D. Fir, S. 64° W. (Rec. S27W) 15.2 ft., opened & find scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office, 1969 1/4 S 11 | S 12
No New Bearing Trees needed.
This corner lies on steep north slope and 300 ft. N. of Callahan Pack Trail.

1/4 Corner to Sections 11 and 12. 69
Found - 3/4" Brass Cap at Cor. Mkd. No trace of Brass Cap at Cor. Mkd. 240
Orig. 9" Fir Snag S. 36° W. 6.6 ft., scribe visible
16", now 18" D. Fir, N. 85 1/2° E. 42.2 ft., shows good scar.
17", now 18" D. Fir S. 54° E. 93.5 ft., shows scribing.
Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's T 32 S R 3 W
Office 1969 1/4 S 1 | S 12

1/4 Corner to Sections 1 and 2. 70
Found - 18x12x4 Slate Stone, firmly set, mkd. "1/4" on west face.
Unrecorded 1" I. Pipe bears S. 85° E. 12.6 ft.
18" D. Fir, now S. 34° E. 26.4 ft., shows good scar.
Rotten & Decayed Laurel, possible bearing tree. #172
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office, 1969 1/4 S 2 | S 1
New BT's: 6" D. Fir N. 41° W. 24.6 ft. mkd: "1/4 S1 CS BT".
9" D. Fir N. 74° E. 15.1 ft. mkd: "1/4 S2 CS BT".

Section Corner to Sections 2 - 3 - 10 - 11. 71
Found - Large Stone at Section Corner, See Ren. #16. 7/13/81 CS. 6/27
Orig. 16", now 36" Cedar, S. 25° E. (Rec. S30E) 42.2 ft., faint bark scribe visible.
Orig. 10", now 27" Fir, S. 30° W. 5.9 ft., prev. opened, pitched over scribe visible.
14", now 16" Fir, N. 83° E. 31.0 ft., shows good scar.
60", now 60" D. Fir, N. 23° W. 54.0 ft., bark scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office 1969 S 3 | S 2
S 10 | S 11
New BT: 8" D. Fir N. 66° W. ft. mkd: T32S R3W S3 CS BT.
Reblzd. & Recrbd: 27" D. Fir S. 30° W. 5.9 ft. mkd: T32S R3W S10 CS BT.
36" Cedar S. 25° E. 42.2 ft. mkd: T32S R3W S11 CS BT.

7/10/69