

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

72

Section Corner to Sections 16 and 17 only.
Found - 15x8x6" Stone, firmly set, mkd. with 4 notches on east side.
7", now 8" W. Fir, N. 43° E. 12.5 ft., opened for scribe.
20" W. Fir, now 10", N. 40° W. 4.6 ft. (Rec. 2.07) scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 32 S R 3 W
S 17 | S 16
1969 S 20
New BT: 30" D. Fir S. 71° E. 6.8 ft. mkd: T32S R3 W S20 CS BT.

RE-RENEWED, SET CORNER NO. #179

73

Section Corner to Sections 20 and 21 only. (Closing Corner)
Found - 5", now 6" Yew, S. 73½° E. 68.4 ft., scribe visible. See Ren. #7.
16", now 18" Hemlock S. 80 3/4° W. 1.2 ft. shows good scar.
Set - Brass Cap at C. C. Mkd: County Surveyor's Office T 32 S R 7 W
S 16
1969 CC S 20 | S 21
New BT: 7" D. Fir N. 8° E. 7.3 ft. mkd: T32 S R3W S16 CS BT.
This corner lies on west side of old abandon logging road, Dismal Creek Rd.

RE-RENEWED, SET CORNER NO. #183

74

Section Corner (Closing Corner) to Sections 21 and 22.
Found - 18x8x16" Stone mkd. C C on south face, firmly set.
40", now 48" D. Fir, S. 43° E. 37.0 ft., shows good scar.
18", now 25" D. Fir, S. 50° W. 114.2 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 32 S R 3 W
S 15
1969 CC S 21 | S 22
New BT: 6" Hemlock S. 4° W. 14.0 ft. mkd: T32S R3W S21 CC CS BT.
This corner lies in heavy undergrowth, about 80 ft. S. of E - W ravine.

John M. Powell
Frank Jones & W. Penley
July, 1969 C. S. File No. 54/910

75

Section Corner to Sections 15 and 16 only.
Found - 18x12x5" Stone with 3 notches on E. side, firmly set.
16", now 18" D. Fir, N. 50° E. 9.2 ft. shows good scar.
18", now 20" D. Fir, N. 64° W. 13.2 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 32 S R 3 W
S 16 | S 15
1969 S 21
New BT: 20" D. Fir S. 37° W. 9.2 ft. mkd: T32S R3W S21 CS BT.

RE-RENEWED, SET CORNER NO. #177

76

¼ Corner to Section 15 only.
Found - 15x10x6" Stone mkd: "¼" on North face.
20", now 28" D. Fir, N. 30° W. 24.4 ft., shows good scar.
24", now 32" D. Fir, N. 37° E. 16.5 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 32 S R 3 W
S 15
1969 ¼
Bearing Trees O. K. and Tagged.
7/11/69

77

Section Corner to Sections 14 & 15 only.
Found - 15x8x6" Stone lying on ground near corner mkd. with 2 notches.
Orig. 40", now 50" D. Fir, N. 70° W. 11.9 ft., shows good scar, also faint bark scribe.
Orig. 30", now 38" D. Fir, N. 60° E. 34.3 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 32 S R 3 W
S 15 | S 14
1969 S 22
New BT: 14" D. Fir S. 52° E. 47.1 ft. mkd: T32S R3W S22 CS BT.

78

Section Corner to Sections 22 and 23 only. (Closing Corner)
Found - 14x12x4" Stone, firmly set with CC mkd. on south face.
Orig. 24", now 38" D. Fir, S. 76° E. 17.8 ft., shows good scar.
Orig. 24", now 34" D. Fir, S. 30° W. 13.2 ft., shows good scar.
Set - Brass Cap at C. Cor. Mkd: County Surveyor's Office T 32 S R 3 W
S 14
1969 S 22 | S 23
New BT: 8" Hemlock N. 42° E. 19.2 ft. mkd: T32S R3W S14 CS BT.