

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell  
Frank Jones & W. Penley  
July, 1969 C.S. File No. 54/91

Section Corner to Sections 28 - 29 - 32 - 33.

Found - 18x10x8" Stone mkd: 4 notches on E. & 1 on S., firmly set.

40", now 44" D. Fir, N. 3° E. 48.2 ft., shows good scar.

6", now 16" Hemlock, S. 81° E. 23.1 ft., shows good scar.

40", now 46" D. Fir, S. 76° W. 37.6 ft., shows good scar.

60" D. Fir, now 68" N. 47° W. 8.6 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W

Office S 29 | S 28

1969 S 32 | S 33

Doug. Co.  
Jack. Co.

New BTs: 10" Cedar N. 60° E. 17.0 ft. mkd: "T32S R3W S28 CS BT".

14" Hemlock S. 22° W. 14.0 ft. mkd: T32S R3W S32 CSBT".

FD. OK 7/95 BY LANG - M123-79

Section Corner to Sections 7 - 8 - 17 - 18.

Found - 10", now 18" D. Fir, N. 39° E. 37.6 ft., shows good scar.

15", now 28" D. Fir, S. 35° E. 52.8 ft., shows good scar.

8", now 14" D. Fir, S. 5° W. 31.7 ft., scribe visible, "S18 BT".

10, now 26" Pine, N. 45° W. 13.2 ft., shows good scar.

18x10x8" Stone, firmly set mkd. with 4 notches on S. & 5 on the East.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W

Office S 7 | S 8

1969 S 18 | S 17

All Bearing Trees are Tagged and in good condition.

Section Closing Corner to Sections 19 and 20 only.

Found - 18x10x7" Stone mkd. "C" on S. & 5 notches on E. face.

28", now 32" Hemlock, (Rec. Fir) S. 7° W. 11.9 ft., scribe visible.

30" D. Fir, now stump, S. 61° E. 19.8 ft., shows good scar.

Set - Brass Cap at Cl. Cor. Mkd: County Surveyor's T 32 S R 3 W

Office S 17

1969 CC S 19 | S 20

New BTs: 6" Yew S. 18° E. 24.2 ft. mkd: T32S R3W S20 CC CS BT.

27" D. Fir N14° W. 32.2 ft. mkd: "T32S R3W S17 CS BT".

Section Corner to Sections 17 and 18 only.

Found - 16x8x6" Stone with 5 notches on the East Face.

8", now 11" D. Fir, N. 82° W. 15.2 ft., scribe visible.

10", now 12" D. Fir, N. 18° E. 7.9 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W

Office S 18 | S 17

1969 S 19

New BT: 12" D. Fir 8.1 ft. mkd: "T32S R3W S19 CS BT".

7/29/69

1/4 Corner to Sections 7 and 18.

Found - 18x10x8 Stone out of ground at 1/4 corner.

48" S. Pine, now stump, N. 50° W. 15.8 ft., shows good scar, REN. No. 39

10" Cedar, now stob, S. 30° W. 10.6 ft., scribe visible, "1/18".

16" D. Fir S. 76° W. 10.2 ft., scribe visible (unrecorded Tree)

Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W

Office S 7

1969 S 18

New BT: 10" Cedar N. 70° W. 110.2 ft. mkd: "1/4 S7 CS BT".

This corner lies about 260.0 ft. west of creek in clear-cut unit.

8/4/69

South 1/4 Corner to Section 18 only.

Found - 16", now 18" D. Fir, N. 61° W. 2.0 ft., scribe visible.

5" Pine, now down, N. 35° E. 17.8 ft., scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W

Office 1/4 S 18

1969

New BT: 16" D. Fir N. 84° E. 50.3 ft. mkd: "1/4 S18 CS BT".

8/4/69

91

92

93

94

95

96