

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

97

$\frac{1}{4}$  Corner to Section 19 only, north boundary.  
Found - 12x10x8" Stone, firmly set, mkd: " $\frac{1}{4}$ " on south face.  
5", now 8" Chinquapin, S.26°E. 21.8 ft., opened previously,  
tree rotted out.  
5", now 8" Laurel, S.49°W. 20.5 ft., opened for scribing.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office, 1969  $\frac{1}{4}$  S 19  
New BT's: 6" D.Fir S.24°W. 20.2 ft. mkd: " $\frac{1}{4}$  S19 CSBT".  
12" Laurel S.86°E. 27.7 ft. mkd: " $\frac{1}{4}$  S19 CS BT".

$\frac{1}{4}$  Corner to Sections 14 and 15.  
Found - No trace of truck axle, See Ren. #36.  
16" W.Fir, now stump, S.2°E. 13.1 ft., scribe visible.  
13" W.Fir, now stob, N.23°W. 15.2 ft., scribe visible.  
14" W.Fir, now snag, S.49°E. 17.0 ft., scribe visible.  
10", now 11" Yew S.58°E. 12.5 ft., scribe visible.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office, 1969  $\frac{1}{4}$  S 15 S 14  
New BT's: 3/4" I.Rod bears N.53°W. 50.0 ft.  
This corner lies on west side of old logging road.

Section Corner to Sections 10 - 11 - 14 - 15.  
Found - Orig. 12", now 16" D.Fir, N.40°E. 16.5 ft., shows good scar..  
Orig. 9", now 12" D.Fir, N.14°W. 13.8 ft., shows good scar..  
Orig. 16", now 24" D.Fir, S.70°W. 10.6 ft., prev. opened,  
scribe visible.  
24", now 29" D.Fir, N.50°E. 12.2 ft., bark scribed. Ren. #15.  
14", now 25" D.Fir, S.85°W. 34.9 ft., shows pitched over scribe.  
N.W. Bearing Tree Stump.  
Found Stone, out of place, with "+" near corner.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office, 1969 S 10 | S 11  
S 15 | S 14  
New BT: 14" Laurel S. 4° E. 24.0 ft., mkd: T32S R3W S14 CS BT.

John M. Powell  
Frank Jones & W. Penley  
July, 1969 and August  
C. S. File No. 54/91

7-2-11  
1-2-11  
16-2-11  
Per O&A  
Notes

Section Corner to Sections 22 - 23 - 26 - 27.  
Found - 15x10x8" Stone, firmly set, 2 notches on South & East Sides.  
8", now 18" Cedar, N.70°E. 27.7 ft., shows good scar.  
7", now 13" W.Fir, S.47°E. 28.4 ft., shows good scar.  
15", now 29" Cedar, S.69°W. 25.7 ft., shows good scar.  
24", now 28" D.Fir, N.22°W. 13.9 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office, 1969 S 22 | S 23  
S 27 | S 26  
All Bearing Trees O. K. and Tagged.

$\frac{1}{4}$  Corner to Sections 22 and 27.  
Found - 18x10x8" Stone, mkd: " $\frac{1}{4}$ ", lying downhill from  $\frac{1}{4}$  corner.  
8", now 19" Cedar, S.40°W. 37.0 ft., opened for scribing.  
6", now 19" Cedar, N. 2° W. 25.1 ft., shows very faint scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office, 1969  $\frac{1}{4}$  S 22  
S 27  
Reblzd. & Rescrbd: 19" Cedar N. 2° W. 25.1 ft., mkd: " $\frac{1}{4}$  S22 CSBT.  
New BT: 6" D.Fir S.50°W. 8.9 ft. mkd: " $\frac{1}{4}$  S27 CS BT.  
This corner lies on very steep west slope at head of ravine, running W.  
8/5/69

Section Corner to Sections 5 - 6 - 7 - 8.  
Found - 1 $\frac{1}{2}$ " Pipe, 24" long, set at corner, See Ren. #10.  
24", now 25" D.Fir, S.10°W. 27.7 ft., shows good scar.  
30", now 35" D.Fir, S.22 $\frac{1}{2}$ °E. 27.0 ft., shows good scar.  
10", now 15" Hemlock, N.36 $\frac{1}{2}$ °E. 12.4 ft., scribe visible.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office, 1969 S 6 | S 5  
S 7 | S 8  
All BT's O. K. & Tagged. This cor. lies E. slope about 150' S. & 100' W. of Snow Creek Road.  
Location Tag about 100 ft. north of Sec. Cor. on West Bank of Road.  
8/7/69

RE-RENEWED, SEE CORNER NO #212 102