

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

103

South $\frac{1}{4}$ Corner to Section 13 only.
Found - Corner Stone, 15x8x6 with " $\frac{1}{4}$ " on N. side and in place.
Orig. 12" D. Fir, now 14" Snag, N. 7° W. 31.7 ft., shows good scribing.
Orig. 5" Y. Pine (Record 5" Pinion), now 8", N. 79° E. 24.4 ft., shows scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W.
(alongside Corner Stone) Office $\frac{1}{4}$ S 13
1969

New BT: 8" Y. Pine N. 21° E. 20.2 ft. mkd: " $\frac{1}{4}$ S13 CS BT".
This $\frac{1}{4}$ corner lies approx. 40.0 ft. west of spur and on south slope.

104

$\frac{1}{4}$ Corner to Section 6 and 7.
Found - No trace of I. Pipe due to Cat. trail over corner point, See Ren. #9.
Orig. 36" D. Fir, now Snag, N. 80° W. 9.9 ft., scribe visible.
10", now 18" D. Fir, S. 70° E. 16.5 ft., tree prev. opened, pitched over, scribe visible.
12", now 12" Yew, S. 26 $\frac{1}{2}$ ° E. 31.8 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office $\frac{1}{4}$ S $\frac{6}{7}$
1969

New BT: 8" Hemlock N. 5° W. 10.4 ft. mkd: " $\frac{1}{4}$ S6 CS BT".
Orig. call on creek at 44.40 ch. running east, not good, as main creek has moved southward. Call on Snow Ck. of 49.40 ch. is good.

105

$\frac{1}{4}$ Corner to Sections 29 and 30.
Found - Corner Stone, firmly set, 14x10x8, mkd. " $\frac{1}{4}$ " on west face.
Orig. 24", now 30" D. Fir, S. 58° W. 12.5 ft., shows good scar.
Orig. 6", now down D. Fir, N. 22° E. 8.6 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office, 1969 $\frac{1}{4}$ S 30 | S 29

New BT: 6" D. Fir N. 14° E. 12.3 ft. mkd: " $\frac{1}{4}$ S29 CS BT".

106

Section Corner to Sections 29 - 30 - 31 - 32.
Found - Corner Stone, 18x8x8, firmly set mkd: 1 notch on S. & 5 on the E.
Orig. 15", now 27" D. Fir, N. 51° E. 30.4 ft., shows good scar.
Orig. 36", now 47" D. Fir, S. 41° E. 19.1 ft., shows good scar.
Orig. 30", now 38" Cedar, S. 16° W. 35.6 ft., scribe visible.
Orig. 30", now 34" Y. Pine, N. 30° W. 21.8 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office S 30 | S 29
1969 S 31 | S 32

All Bearing Trees O. K. and Tagged.

107

$\frac{1}{4}$ Corner to Sections 19 and 20.
Found - Corner Stone, 18x10x6, in place & mkd: " $\frac{1}{4}$ " on west face.
Orig. 12" D. Fir, now 14" Snag, S. 29° E. 24.4 ft., opened & found scribing.
Orig. 8", now 12" D. Fir, S. 85° W. 25.1 ft., shows good axe face.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office, 1969 $\frac{1}{4}$ S 19 | S 20

New BT: 6" D. Fir N. 87 $\frac{1}{2}$ ° E. 22.5 ft. mkd: " $\frac{1}{4}$ S 20 CS BT".
This corner lies on gentle grassy north slope.

108

South $\frac{1}{4}$ Corner to Section 17 only.
Found - Corner Stone, 16x16x6 mkd: " $\frac{1}{4}$ " on north face.
Orig. 14", now 27" D. Fir, N. 8° W. 33.4 ft., tree previously opened, pitched over scribe visible.
Orig. 40", now 43" D. Fir, N. 77° E. 54.8 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office $\frac{1}{4}$ S 17
1969

All Bearing Trees O. K. and Tagged.

John M. Powell
Frank Jones & W. Penley
August, 1969 - C.S. File No. 54/91