Douglas County Surveyor's Record of Government Corners Renewed

T. 32 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

109

Section Corner to Sections 19 - 20 - 29 - 30.
Found - Corner Stone, 15x10x6, in place and mkd.
Orig. 6",now 12" Cedar N.66°W. 11.9 ft., opened & shows scribe "B".
6" Fir, now 3" Windfall, S.60°W. 24.4 ft., rotted & no scribing.
N. E. - S. E. Bearing Trees are gone.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1969

T 32 S	R 3 W
S 19	S 20
S 30	S 29

New BT's: 6" Cedar S.10°W. 5.6 ft. mkd: "T32S R3W S30 CS BT".
6" Laurel N.22°E. 7.4 ft. mkd: "T32S R3W S20CS BT
30" D.Fir S.16°E. 78.9 ft. mkd: "T32S R3W S30 CS BT.
This corner lies approx. 85.0 ft. south of ravine.

\- - - - - -

110

¼ Corner to Sections 20 and 21.
Found - No trace of 5/8" Bolt set by Wenderoth, 1946, See Ren. #6.
Orig. 28" D.Fir, now windfall, N.9°W. 21.1 ft., shows brunt scribing.
40" D.Fir, now 42" Stump, N.25°W. 54.4 ft., shows scribing.
N.E. BT. was taken out in skid road.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1969

T 32 S	R 3 W
¼ S 20	S 21

New BT's: 6" D.Fir N.36°W.46.6 ft. mkd: "¼ S20 CSBT".
6" Hemlock S15°E. 40.6 ft.mkd:"¼ S21 CS BT.
This ¼ corner lies in logging unit about 100 ft. S. of small creek.

\- - - - - -

111

¼ Corner to Sections 15 and 16.
Found - Corner Stone, 20x15x12, in place and mkd. Ren. #3.
Orig. 40", now 50" D.Fir Snag, N.25°E. 44.2 ft., shows scribing.
Orig. 48", now 48" D.Fir Stob, N.30°W. 8.6 ft., shows brunt axe face, no scribing.
38",now 40" D.Fir Stump, S.77°W. 60.7 ft., shows good bark scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1969

T 32 S	R 3 W
¼ S 16	S 15

New BT's: 6" D.Fir S.83°E. 46.7 ft. mkd: "¼ S15 CS BT".
5" Hemlock N.50°W. 12.3 ft. mkd: "¼ S16 CS BT.
This ¼ corner lies about 70 ft. south of ravine.

\- - - - - -

112

¼ Corner to Sections 26 and 35.
Found - 15x12x6 Corner Stone mkd. "¼" on north face.
Orig.36",now 38" D.Fir, N.70°E. 10.6 ft., shows good scar.
Orig.36",now 36" D.Fir, S.18°W. 4.0 ft., shows good scar.
Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office 1969 Doug. Co. Jack. Co.

T 32 S	R 3 W
¼ S 26	
S 35	

All Bearing Trees O.K. and Tagged.

\- - - - - -

113

Section Corner to Sections 25 - 26 - 35 - 36.
Found - Corner Stone, 18x12x7, firmly set with unrecorded Brass Cap
Alongside Mkd: State Bd. of Forestry RS 359 1968

T 32 S	R 3 W
S 26	S 25
S 35	S 36

40" D.Fir, now snag, N.55°E. 35.6 ft., scribe visible.
40" D.Fir, now 44" with broken top, S.15°E. 6.6 ft., shows good scar.
48" D.Fir, now snag, S.35°W. 17.8 ft., scribe visible.
54", now 22" D.Fir, N.44°W. 37.6 ft., shows good scar.
New BT's: 17" Y.Pine N.21°E. 31.5 ft. mkd: T32S R3W S25 CS BT".
18" D.Fir S.70°W. 40.2 ft. mkd: T32S R3W S35 CS BT".
7" D.Fir S.41°E. 16.2 ft. mkd: T32S R3W S36 CS BT".
(unrecorded) 36" Cedar S.4°E. 32.0 ft. mkd: "RS 359".

\- - - - - - -

114

Section Corner to Sections 27 - 28 - 33 - 34.
Found - Corner Stone, 15x6x6, firmly set mkd; 1 notch S. & 3 notches E.
Orig.28",now 36" D.Fir, N.83°E. 34.3 ft., shows good scar.
Orig.40",now 48" D.Fir, S.82°E. 31.0 ft., shows good scar.
Orig.40",now 45" D.Fir, N.82°W. 10.6 ft., shows good scar.
Orig.30",now 40" Cedar, S. 7°W. 67.3 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1969

T 32 S	R 3 W
S 28	S 27
S 33	S 34

All BT's O.K. & Tagged. Cor. about on top of rounded Spur, running West.

John M. Powell
Frank Jones & W. Panley
August, 1969
C. S. File No. 54/91

RE-RENEWED, SEE CORNER NO. #228

RE-RENEWED, SEE CORNER NO. #176

RE-RENEWED, SEE CORNER NO. #230