

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 3 W. R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Frank Jones & W. Penley
August, 1969
C.S. File No. 54/91

1/4 Corner to Sections 27 and 28. 115
Found - Corner Stone, 16x12x10, mkd: "1/4" on west face.
Orig. 24", now 29" Y. Pine, S. 1 1/2° E. 46.9 ft., scribe visible.
Orig. 36", now down, S. 3° W. 52.1 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office, 1969 1/4 S 28 | S 27

1/4 Corner to Section 25, T32-4W. (West Bdry. T32-3W.) 116
Found - Corner Stone, 14x8x8, firmly set, mkd: "1/4" on west face.
Orig. 18" D. Fir, now snag, S. 82° W. 4.6 ft., opened for scribe.
Orig. 30" D. Fir, now stob, N. 21° W. 27.1 ft., face burnt.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 32 S R
Office 4 1/4 3
1969 W S 25 | W
New BT's: 6" D. Fir S. 6° W. 10.0 ft. mkd: "1/4 S25 CS BT".
12" D. Fir N. 14° W. 26.7 ft. mkd: "1/4 S25 CS BT".

Section Closing Corner to Sections 19 and 30, T32-3W. 117
Found - No trace of Corner Stone, probably slid down mountain.
(Large stone to south of corner about 10 ft., right size but no marks, not right for bear. dist.)
Orig. 36" Fir, now stob, N. 89° E. 80.5 ft., scribe visible.
Orig. 40", now 40" Fir, S. 82° E. 73.9 ft., has burnt face.
Set - Brass Cap at Cor. Mkd: County Surveyors R T 32 S R
Office CC 4 S 25 | S 19 3
1969 W S 30 | W
New BT's: 12" D. Fir N. 44° E. 7.7 ft. mkd: "T32S R3W S19 CC CS BT".
12" D. Fir S. 59° E. 7.8 ft. mkd: "T32S R3W S30 CC CS BT".

Section Corner to Secs. 25 & 36, T32-4 W. (West Bdry. T32-3) 118
Found - No trace of Corner Stone.
Orig. 24", now 28" D. Fir, S. 75° W. 21.8 ft., shows good scribing.
Orig. 12", now 16" S. Pine, N. 1° W. 68.6 ft., shows good scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 32 S R
Office 4 S 25 | S 30 3
1969 W S 36 | W
No new bearing trees needed. This corner lies about 100' north of creek.

1/4 Corner to Sections 27 and 34. 119
Found - Corner Stone, 12x10x5, firmly set, mkd. "1/4" on north face.
Orig. 30", now 38" D. Fir, N. 14° W. 6.6 ft., shows good scar.
Orig. 8" Hemlock, now stob, S. 20° E. 4.0 ft., opened for scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office Doug. Co. 1/4 S 27
1969 Jack Co. 1/4 S 34
New BT: 8" Hemlock S. 42° E. 22.7 ft. mkd: "1/4 S34 CS BT".

Section Corner to Sections 26 - 27 - 34 - 35. 120
Found - Corner Stone, 15x8x8, firmly set mkd. with notches. #229
Orig. 20" D. Fir, now stob, N. 14° E. 4.6 ft., scribe visible.
Orig. 18" D. Fir, now stob, N. 48° W. 7.3 ft., found reverse scribe.
Orig. 12" D. Fir, now burnt stob, S. 45° W. 16.6 ft., stob flush with ground.
Orig. 16" D. Fir, now stob, S. 60° E. 17.2 ft., scribing rotted out.
Set - Brass Cap at Cor. Mkd: County Surveyor's T. 32 S R 3 W
Office Doug. Co. S 27 | S 26
1969 Jack Co. S 34 | S 35
New BT's: 6" Hemlock S. 18° W. 19.0 ft. mkd: "T32S R3W S34 CS BT".
6" Hemlock S. 66° E. 4.4 ft. mkd: "T32S R3W S35 CS BT".
8" Hemlock N. 69° E. 5.9 ft. mkd: "T32S R3W S26 CS BT".
6" Hemlock N. 15° W. 20.2 ft. mkd: "T32S R3W S27 CS BT".

RENEWED, SET CORNER #229