

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32 S. T. S. R. 3 W. R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

121

$\frac{1}{4}$  Corner to Sections 26 and 27.  
Found - Corner Stone, 15x10x6, in place and mkd.  
Orig. 12", now 24" Y. Pine, S. 27° E. 11.2 ft., shows good axe face.  
Orig. 6", now 12" Cedar, S. 88° W. 15.2 ft., shows good scribing.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office, 1969  $\frac{1}{4}$  S 27 | S 26

No new Bearing Trees needed.  
This corner lies about 40.0 ft. N. of small creek on S.W. slope.

122

$\frac{1}{4}$  Corner to Sections 4 and 9.  
Found - No trace of I. Pipe at corner due to Cab. trail, See Ren. #23.  
30" D. Fir, now snag, N. 47 $\frac{1}{2}$ ° E. 6.3 ft., pitched over scribing visible.  
36", now 38" D. Fir, S. 54° W. 14.4 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office 1969  $\frac{1}{4}$   $\frac{S\ 4}{S\ 9}$

New BT: 7" D. Fir N. 24° E. 32.7 ft. mkd: " $\frac{1}{4}$  S 4 CS BT".  
FO OK 10/94 - M/21-13

123

$\frac{1}{4}$  Corner to Sections 4 and 5.  
Found - 1" Iron Pipe at Corner, See Ren. #25.  
14" Hawthorne, now dead, S. 40° W. 91.3 ft., scribe visible.  
26" Fir Stump N. 52° E. 97.7 ft., scribe visible.  
New BT: 15" D. Fir N. 72° E. 30.0 ft. mkd: " $\frac{1}{4}$  S 5 CS BT".  
18" D. Fir N. 28° E. 21.0 ft. mkd: " $\frac{1}{4}$  S 4 CS BT".  
Fence corner bears N. 19° W. 13.2 ft., fence runs North & East.

**RE-RENEWED, SEE CORNER NO. #213**

124

Section Corner to Sections 23 - 24 - 25 - 26.  
Found - 18x18x15 Stone mkd: "+" & notches, firmly in place.  
20", now 23" Cedar, N. 69° W. 20.5 ft., shows good scar.  
40", now 45" D. Fir, N. 7° E. 38.3 ft., shows good scar.  
40", now 45" D. Fir S. 53° W. 9.2 ft., shows good scar.  
20", now 24" Cedar, S. 44° E. 35.0 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office 1969  $\frac{S\ 23}{S\ 26}$  |  $\frac{S\ 24}{S\ 25}$

All Bearing Trees O. K. and Tagged.

125

$\frac{1}{4}$  Corner to Sections 23 and 24.  
Found - 7", now 17" Yellow Pine, S. 23 $\frac{1}{2}$ ° E. 27.2 ft., opened for scribe "4".  
No trace of S.W. BT. or "marks at  $\frac{1}{4}$  corner on bedrock, due to erosion.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office, 1969  $\frac{1}{4}$  S 23 | S 24

New BT: 14" Cedar S. 32° W. 29.7 ft. mkd: " $\frac{1}{4}$  S 23 CS BT".

126

$\frac{1}{4}$  Corner to Sections 25 and 26.  
Found - 18x12x6 Stone mkd: " $\frac{1}{4}$ " on West face, firmly set at corner.  
10", now 13" Cedar, N. 30° E. 12.5 ft., shows good scar.  
12", now 14" Cedar, N. 82° W. 17.8 ft., scribe marks visible but mostly grown over.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office, 1969  $\frac{1}{4}$  S 26 | S 25

All Bearing Trees O. K. and Tagged.

127

$\frac{1}{4}$  Corner to Sections 28 and 33.  
Found - 16x12x10 Stone, mkd: " $\frac{1}{4}$ " on North face, firmly set at  $\frac{1}{4}$  Corner.  
48", now 82" D. Fir, S. 50° W. 33.0 ft., shows faint scar.  
20", now 39" D. Fir, N. 10° E. 31.7 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
Office 1969  $\frac{1}{4}$   $\frac{S\ 28}{S\ 33}$  Doug. Co.  
Jack. Co.

Rebln & Reestrd: 82" D. Fir S. 50° W. 33.0 ft. mkd: " $\frac{1}{4}$  S 33 CS BT".

**RE-RENEWED, SEE CORNER NO. #226**

John M. Powell  
Frank Jones & W. Penley  
August, 1969 C.S. File No. 54/91  
Sept., 1969

9/5/69