

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

128

$\frac{1}{4}$ Corner to Sections 19 and 30.
Found - 15x12x6 Corner Stone, in place, Mkd: " $\frac{1}{4}$ " on North face.
8" D.Fir, now windfall, S. 3° W. 12.5 ft., shows scribing
No trace of N.W. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office S 19
1969 $\frac{1}{4}$ S 30
New BT's: 6" Hemlock N.72°W. 11.5 ft. mkd: " $\frac{1}{4}$ S19 CS BT".
28" D.Fir S.73°E. 28.2 ft. mkd: " $\frac{1}{4}$ S30 CS BT".
This corner lies on a north slope about 300 ft. East of a ridge.

129

Section Corner to Sections 8 - 9 - 16 - 17.
Found - 15x12x4 Stone, firmly in ground, no good marks visible.
14" Pine, now down & burnt, N.7 $\frac{1}{2}$ °E. 47.5 ft.
6" Pine, now down, S. 1° W. 45.5 ft., shows scar.
14" Pine, now stob, N.3 $\frac{1}{2}$ °W. 42.9 ft., scribe visible.
No trace of S.E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office S 8 | S 9
1969 S 17 | S 16
New BT's: 12" D.Fir N.30°W. 7.9 ft. mkd: T32S R3W S8 CS BT.
14" D.Fir N.11°E. 27.9 ft. mkd: T32S R3W S9 CS BT.
10" D.Fir S.49°E. 16.5 ft. mkd: T32S R3W S16 CS BT.
15" D.Fir S.53°W. 13.9 ft. mkd: T32S R3W S17 CS BT.
(Unrecorded-17" Pine East 46.8 ft., scribe vis. - 12" Fir N.30°W. 7.9 ft., has
scar. Do Not open, but Rescribe for New BT.)

130

$\frac{1}{4}$ Corner to Sections 9 and 16.
Found - 16x8x6" Stone, firmly in ground, " $\frac{1}{4}$ " on north face. Ren. #4.
30", now 39" Cedar, N. 1° E. 14.5 ft. scribe visible
5", now 7" Pine, S.54°E. 13.7 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office S 9
1969 $\frac{1}{4}$ S 16
All Bearing Trees O.K. and Tagged.

131

$\frac{1}{4}$ Corner South Side of Section 16 only.
Found - Stone at Corner, but no marks visible, See Ren. #5.
6", now 8" Yew, N.33 $\frac{1}{2}$ °W. 76.7 ft., scribe visible #244
16", now 24" W.Fir, N.63°E. 58.1 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office, 1969 $\frac{1}{4}$ S 16
Reblzd. & Rescrbd: 24" W.Fir N.63°E. 58.1 ft. mkd: " $\frac{1}{4}$ S16 CS BT".

132

$\frac{1}{4}$ Corner to Sections 16 and 17.
Found - 14", now 26" D.Fir, N.52°E. 23.8 ft., shows good scar.
36", now 39" D.Fir, N.59°W. 22.4 ft., shows good scar.
15x14x6 Stone, firmly in ground, mkd: " $\frac{1}{4}$ " on west face.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office, 1969 $\frac{1}{4}$ S 17 | S 16
All Bearing Trees O. K. & Tagged.

133

Closing Corner for Sections 18 & 19, T32-3W.
Found - Cadastral Brass Cap, properly marked in 1959.
The BT. for Sec. 18 was in good shape & the BT. for Sec. 19 was
fell with stump remaining on a very high cut bank of new road construction.
Because of the very high cut bank & the inaccessability of reasonably
close bearing trees, and the fact that there will be a possibility of a
future timber sale in Sec. 19, I scribing the following BT:
7" Hemlock S. 38° W. 21.1 ft. mkd: "T32S R4W S24".

10/30/69

John M. Powell
Frank Jones & W. Penley
September, 1969
C.S. File No. 54/91

Lorne V. Swearingen
S. Oee. Ply
C.S. File
55/85

RE-RENEWED, CORNER NO. #237