

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 S T. S. R 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Corner No. 2 of H. E. S. #186 134
 Found - Old Corner Stone, in place, mkd. "+" on top & "2HES186" on side.
 Orig. 10", now 18" Fir, S. 58 $\frac{1}{2}$ ° E. 11.9 ft., now burned stump, scribe
 marks visible on burned blaze.
 Orig. 50", now 52" Fir, N. 24 $\frac{1}{2}$ ° W. 27.7 ft., burned, no scribe found.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
 (Reset Stone Alongside) Office, 1969 Cor. #2 HES 186
 New BT's: 6" D. Fir S. 65° E. 12.0 ft. mkd: "2 HES 186 CS BT".
 7" D. Fir N. 28° W. 19.1 ft. mkd: "2 HES 186 CS BT".
12/26/69

FD. OK 6/1/82
2.5. F.S. 05. 6/1/82

Corner No. 3 of H. E. S. #186 135
 Found - Old Corner Stone, in place, mkd: "+" on top & "3HES186" on side.
 Orig. 36", now 40" Fir, N. 44° W. 11.2 ft., now decayed stump, we open &
 find frag. scribe.
 Orig. 24", now 30" Fir, S. 56° W. 19.8 ft., now decaying stump, we open &
 find "3 HES 186 BT" scribe.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
 (Reset Stone Alongside) Office, 1969 Cor. #3 HES 186
 New BT's: 7" W. Fir S. 13° W. 25.7 ft. mkd: "3 HES 186 CS BT"
 7" W. Fir N. 24° W. 24.3 ft. mkd: "3 HES 186 CS BT"
 This corner lies on flat end of old fence, course E.
12/29/69

FD. OK 6/2/82
2.5. F.S. 05. 6/1/82

Corner No. 4 of H. E. S. #186 136
 Found - Old Corner Stone, in place, mkd: "+" on top & "4HES186" on side.
 Orig. 48", now 60", S. 1 $\frac{1}{2}$ ° E. 10.6 ft. alive, shows good axe scar, we tag.
 Other O.B.T. gone.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
 (Reset Stone Alongside) Office, 1969 Cor. #4 HES 186
 New BT's: 11" W. Fir N. 58° E. 27.0 ft. mkd: "4 HES 186 CS BT"
 10" Yew S. 23° E. 33.6 ft. mkd: "4 HES 186 CS BT"
 This corner lies on steep West slope 30 ft. East of toe of hill.
12/29/69

FD. OK 5/25/82
2.5. F.S. 05. 6/1/82

Corner No. 5 of H. E. S. #186 137
 Found - Old Corner Stone, in place, mkd. "5HES186" on side. #222
 Orig. 24" Fir, N. 42° 40' W. 15.8 ft., now stump, broken off almost at
 ground level, no scribe found.
 Orig. 14", now 22" Fir, S. 54° 45' W. 15.2 ft. alive, shows good scar, we tag.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
 (Reset Stone Alongside) Office, 1969 Cor. #5 HES 186
 New BT's: 14" D. Fir S. 15° E. 24.5 ft. mkd: "5 HES 186 CS BT".
 This corner lies on gentle Northerly slope.
12/30/69

RE-RENEWED, SEE CORNER NO. #222

Vernon "Ray" Tracy
Jack Heritage & V. Perron
C. S. File No. 54/91
Dec. 1969

Corner No. 6 of H. E. S. #186 138
 Found - Old Corner Stone, in place & mkd: "+" on top & "6HES186" on side.
 Orig. 40", now 44" Fir, S. 80 3/4° E. 57.4 ft., now stump, scribe "186"
 visible on open blaze.
 Orig. 14", now 26" Fir, S. 3 3/4° W. 75.2 ft. alive, shows good scar, we tag.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
 (Reset Stone Alongside) Office, 1969 Cor. #6 HES 186
 New BT's: 12" D. Fir N. 4° E. 12.3 ft. mkd: "6 HES 186 CS BT"
 12" W. Fir N. 74° E. 8.8 ft. mkd: "6 HES 186 CS BT"
 This corner lies on flat approx. 100 ft. East of Applegate Creek, course
 N. 10° W.
12/30/69

FD. OK 9/21/82
L.H. HERRSTEIN
2.5. F.S. 05. 6/1/82

Corner No. 7 of H. E. S. #186 139
 Found - Corner Stone, in place mkd: "7HES186" on side.
 Orig. 30" now 38" Fir, N. 45° W. 19.1 ft. now stump, record N. 35 $\frac{1}{2}$ ° W. - open
 & shows "x 7 HES 186 BT" scribe.
 Orig. 36" now 40" Fir, N. 62 3/4° E. 16.5 ft., now stump, shows "186 BT"
 scribe.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
 (Reset Stone Alongside) Office, 1969 Cor. #7 HES 186

RE-RENEWED, SEE CORNER NO. #215

Cont. next page