

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 S T.S. R 3 W R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

CONT. - -

New Bl's: 18" D.Fir N.31°E. 43.3 ft. mkd: "7 HES 186 CS BT" #215 139
20" W.Fir S.43°E. 42.3 ft. mkd: "7 HES 186 CS BT" (across road)
This corner lies 20 ft. N.W. of U.S.F.S. Road. Note-see corner #12 for tie
between 12 & 7.
12/29/69

Corner No. 9 of H. E. S. #186 140
Found - O.B.T. as follows
Orig.18", now 28" Fir, S.1 3/4°E. 95.0 ft., now stump, we open & find "86 B"
scribe & reverse, no trace of old corner stone.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
Office, 1969 Cor.#9 HES 186
New BT's: 8" D.Fir N.15°W. 35.6 ft. mkd: "9 HES 186 CS BT"
10" D.Fir S.50°W. 41.5 ft. mkd: "9 HES 186 CS BT"
This corner lies on flat on Eastside of old Roadway.
12/31/69

Corner No. 12 of H. E. S. #186 141
Found - Corner Stone, buried in place with some chisel mks.
Orig.40", now 48" Pine, N.30 1/4°W. 13.9 ft., now stump, (record Fir) we open
& find "x 12 HES 186 BT" scribe.
Orig.16", now 22" Fir, N.17 1/2°E. 42.2 ft., now snag, record (N.22 1/2°E.) we
open & find scribe mks.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
(Deposit Stone Alongside) Office, 1969 Cor.#12 HES 186
New BT's: 9" D.Fir S.71°W. 14.8 ft. mkd: "12 HES 186 CS BT"
9" D.Fir N.77°W. 23.2 ft. mkd: "12 HES 186 CS BT"
This corner lies 30 ft. N.45°W. of existing U.S.F.S. Road. Course N.55°E.-
S.55°W. Note-Corner #7 across exemption, Bears N.44 1/2°E. 78.8 ft. (record
N.41 1/2°E. 90.4 ft.).
#44 1/2°W
5. c.s. 6/1/32
12/29/69

Corner No. 13 of H. E. S. #186 142
Found - Corner Stone in place, mkd. "+" on top & "13HES186" as called for.
Orig.30", now 32" Fir, S.22°W. 50.8 ft., now stump, we open & find "S 186 3"
scribe.
Orig.18", now 26" Fir, N.75°40'E. 39.6 ft., now stump, we open & find
burned blaze, no scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
(Reset Stone Alongside) Office, 1969 Cor.#13 HES 186
New BT's: 6" D.Fir S.87°W. 18.0 ft. mkd: "13 HES 186 CS BT"
6" Laurel N.54°E. 8.8 ft. mkd: "13 HES 186 CS BT"
This corner lies on moderate S.E. slope in very dense Manzanita, Rhododendron,
& Chinquapin brush.
12/30/69

Corner No. 14 of H. E. S. #186 143
Found - Corner Stone, in place, mkd: "+" on top & "14HES186" on side.
Orig.50", now 56" S.31°15'W. 28.4 ft., now stump with "ES 186" scribe
visible O.B.T. to N.E. gone.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
(Reset Stone Alongside) Office, 1969 Cor.#14 HES 186
New BT's: 8" D.Fir S.5°W. 23.5 ft. mkd: "14 HES 186 CS BT"
12" D.Fir N.66°E. 33.5 ft. mkd: "14 HES 186 CS BT"
This corner lies on flat of creek bottom 60 ft. West of creek, course N.
12/30/69

Corner No. 15 of H. E. S. #186 144
Found - Old Corner Stone, in place & mkd: "15 HES 186" on side #217
Orig.8", now 10" Yew, S.42°W. 25.7 ft., alive, "x 15 HES 186 BT" scribe
visible on unhealed blaze-rock outcrop is buried under U.S.F.S. Road
fill across creek.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W
(Reset Stone Alongside) Office, 1969 Cor.#15 HES 186
New BT's: 5" D.Fir S.77°E. 34.6 ft. mkd: "15 HES 186 CS BT"
This corner lies 10 ft. East of creek & 50 ft. East of Road. Corner #16
bears N.77°E. 86.5 ft.
12/31/69

Vernon "Ray" Tracy
Jack Heritage & V. Perron
C. S. File No. 54/91 Dec. 1969

F.S. OK #12/12
H.S.P.S.
C.S. 6/1/32

RE-RENEWED, SEE CORNER NO. #221

RE-RENEWED, SEE CORNER NO. #215
RE-RENEWED, SEE CORNER NO. #216
RE-RENEWED, SEE CORNER NO. #221