

Douglas County Surveyor's Record of  
Government Corners Renewed

T 32 S T. S. R 3 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Corner No. 16 of H. E. S. #186

Found - Old Corner Stone, 12" Below ground mkd: "1" on top & "16 HES 186" on side.

Orig. 40", now 50" Fir, S. 70 3/4° E. 25.7 ft., we open & find scribe mks: O.B.T. to N.E. gone

Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 3 W  
(Reset Stone Alongside) Office, 1969 Cor. #16 HES 186

New BT's: 5" D. Fir S. 33° E. 13.9 ft. mkd: "16 HES 186 CS BT"

This corner lies on flat-corner #15 Bears S. 77° W. 86.5 ft.

12/31/69 New BT: 11" FIR(W) N. 45° E. 17.5' mkd. "16 HES 186 CS BT" (APPROD TO RECORDS 4/1/82 T.R.) 12/31/69

#220 145

Section cor. to sections 5, 4, 8, 9.

Found - 1/2" Iron pipe at sec. cor., See Ren. #26. 32" Douglas Fir, now down, S. 70° E. 41.8 ft. Scribe visible S 9 S.

24" Douglas Fir, now down, N 58° W. 53.8 ft. scribe pitched over.

20" Douglas Fir, now down, S 41° W. 89.2' ft.

Set - Brass cap at sec. cor. mkd: County Surveyor's T32S R3W S5|S4  
Office 1970 S8|S9

New BT's - 24" Douglas Fir N. 54° W. 47 ft. Scribed t32S R3W S5 CS BT.

14" Laurel S. 28° W. 58.2 ft. Scribed T32S R3W S. 8 CS BT.

Note - This cor. lies in partly logged area in old cat road, and now has heavy blow down.

Jan. 26, 1970

#204 146

1/4 Corner to Sec. 35, T31-3 and Sec. 2, T32-3.

Orig. Survey by W. H. Byars, Dep. Co. Surv., 1871.

Resurveyed by Wm. Bushey, 1893. No evidence found.

Set - 2" x 30" Galv. Iron Pipe with Brass Cap, 26" in ground.

Stamped the Disk.

T31S R 3 W

1/4 S 35 OLS 536  
S 2

T32S 1969

Scribed - 18" D. Fir 1/4 S 35 BT" which bears N. 46 1/2° E. 27.7 ft. placed BT tag.

10" D. Fir 1/4 S 2 BT" bears S. 20° E. 45.1 ft., placed BT Tag.

147

1/4 Corner to Sections 2 and 11.

Set by proportionate measurement.

Set - 5/8" Iron Rod, from which bears:

5" Madrone bears N. 48° W. 16 feet

11" Fir bears S. 60° W. 27.7 feet.

#196 148

Aug. 1970

Sec. Cor. to Secs. 32 & 33, T31-3W.

& Secs. 5 & 4, T32-3W.

Found - I. Bolt at Sec. Cor. See Ren. #3, T31-3.

28" Fir, now 42", N. 72° E. 30.5 ft., shows good scar.

16", now 22" Fir, N. 31 1/2° W. 63.2 ft., shows good scar, opened for scribing "S2".

34", now 38" Fir, S. 34° W. 34.0 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S  
Office R3W S 32 | S 33  
1966 S 5 | S 4

#180

New BT: 8" D. Fir N. 64° W. 15.0 ft. scribed T31S R3W S32 CS BT.

149

C. S. File No. 54/91

Glenn S. Baughman  
For: Umpqua Nat'l Forest  
April, 1969  
C.S. 55/114 M 37-60

Bruce R. Rogers  
For: Westland Properties  
M 40 - 24

John M. Powell  
F. Jones & J. Brady  
Jan. 1966  
C. S. File 52/63

MARCH 71