

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T.S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

153

1/4 Corner to Sections 5 and 8.

At the location of the 1/4 corner, I found a 50" diam Sugar Pine Stump & a 38" diam. Fir Snag. The Stump had an old yellow tag nailed to the top which stated, "This is a BT". On examining a slab torn from the face of the stump, I found the remains of the top & bottom of a reverse face with old axe marks at the bottom. The center portion of the reverse face was missing. All evidence of bark scribing on the fir snag has been destroyed by axe work.

On Nov.22,1971, I accompanied James A. Combs, an employee of C.&D. Lbr. Co., to this location. He stated without hesitation that this was the same Sugar Pine Stump that he had seen "BT" scribing in in the period between 1950 & 1955. (See signed statement in file)

At the position determined by measurement of the orig. dist. from the BT's. described above, I set a 2"x36" Iron Pipe, flared at the bottom, with a 3" Brass Cap riveted to the top. The monument projects approx. 10" above the ground.

I stamped this brass cap - - - 1/4 Cor.
T32S, R3W, W.M.
S 5
S 8
R.L.S. 544
1971

From the pipe monument the Orig. BT's. are:

A sugar Pine, 40 ins.,now 50" stump, bears N.60°W. 50 lks.

A fir, 30",now 38" snag) bears S.24°E(Rec.S40E) 13 lks.

I also established New BT's., as follows:

A 32" diam D. Fir bears N. 25° W. 46.0 ft. scribed 1/4 S5 BT

A 13" diam D. Fir bears S. 3/4° W. 27.2 ft. scribed 1/4 S8 BT.

FD OK 7/75 BY LANG - M 123-79

1/4 Corner to Sections 8 and 9.

Set by proportionate measurement.

Set Brass Cap stamped: 1/4 Cor. S 8, S 9, T32S,R3W W.M.
R.L.S. 544, 1971

Established Bearing Trees:

12" Doug. Fir bears East 4.4 ft.(Scribed 1/4 S9 BT)

8" Chinquapin bears N.45°W. 12.1 ft.(Scribed 1/4 S8 BT)

1/4 Corner to Sections 9 and 10.

Set by proportionate measurement.

Set Brass Cap stamped: 1/4 Cor. S9,S10, T32S R3W.
R.L.S. 544, 1971

Established Bearing Trees:

6" Fir bears S.77°45'W. 17.7 feet Scribed 1/4 S 9 BT.

7" Fir bears S.82°E. 32.7 ft. scribed 1/4 S 10 BT.

1/4 Corner to Sections 10 and 11.

Set - Brass Cap (by proportion)

Stamped 1/4 S10, S11, T32S, R3W,W.M.
RLS 544, 1971

Established Bearing Trees:

10" W.Fir bears N.42°W. 15.6 ft. scribed " 1/4 S10 BT".

9" W.Fir bears N.27°E. 4.2 ft. scribed"1/4 S11 BT".

W. 1/16 btwn. Sections 10 and Section 3.

Found - 5/8" I.Rod(See M37-45) found to be in error.

14" Pine bears N.22°E. 145.0 ft.)

26" Pine bears N.63°W. 46.0 ft.)

Set - Brass Cap stamped W 1/16 S10, S3, T32S,R3W
R.L.S. 544, 1971

Used Bearing Trees already established:

14" Pine bears N.33°E. 149.6 ft.

26" Pine bears N.56°W. 25.1 ft.

Dec. 1971

U.S. of AMERICA (Forest Service)
BY DON E. GARRETT
C.S. File No. 55/224 Map M 44 - 8
Nov. 15, 1971

Jan. 1972

154

FD OK 2/1981
L. Herzstein
U.S. Forest Service
C.S. 61/29

1/4 Corner to Sections 8 and 9.

Set by proportionate measurement.

Set Brass Cap stamped: 1/4 Cor. S 8, S 9, T32S,R3W W.M.
R.L.S. 544, 1971

Established Bearing Trees:

12" Doug. Fir bears East 4.4 ft.(Scribed 1/4 S9 BT)

8" Chinquapin bears N.45°W. 12.1 ft.(Scribed 1/4 S8 BT)

1/4 Corner to Sections 9 and 10.

Set by proportionate measurement.

Set Brass Cap stamped: 1/4 Cor. S9,S10, T32S R3W.
R.L.S. 544, 1971

Established Bearing Trees:

6" Fir bears S.77°45'W. 17.7 feet Scribed 1/4 S 9 BT.

7" Fir bears S.82°E. 32.7 ft. scribed 1/4 S 10 BT.

155

FD OK L. HERZSTEIN
7-7-81 C.S. 61/27 U.S. Forest Service

1/4 Corner to Sections 10 and 11.

Set - Brass Cap (by proportion)

Stamped 1/4 S10, S11, T32S, R3W,W.M.
RLS 544, 1971

Established Bearing Trees:

10" W.Fir bears N.42°W. 15.6 ft. scribed " 1/4 S10 BT".

9" W.Fir bears N.27°E. 4.2 ft. scribed"1/4 S11 BT".

156

U.S. of A. U.S. Forest Service
By: Don E. Garrett
Map File 44 - 29

W. 1/16 btwn. Sections 10 and Section 3.

Found - 5/8" I.Rod(See M37-45) found to be in error.

14" Pine bears N.22°E. 145.0 ft.)

26" Pine bears N.63°W. 46.0 ft.)

Set - Brass Cap stamped W 1/16 S10, S3, T32S,R3W
R.L.S. 544, 1971

Used Bearing Trees already established:

14" Pine bears N.33°E. 149.6 ft.

26" Pine bears N.56°W. 25.1 ft.

157

FD OK L. HERZSTEIN
7-14-81 C.S. 61/27