

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T.S. R. 3 W. R.W.W.M.

KGRE-CHAPMAN CO., EUGENE, ORE., 9181

Baughman, G.
For: U.S.
Forest
Service
M 44 - 52

Center 1/4 Corner of Section 3.
Set by subdivision of section.
Set - 2" Iron Pipe with Brass Cap
Marked: 6" Madrone N. 9-1/2 W. 20.6 feet
8" Knob Cone Pine S.60°E. 7.4 feet.

RE-RENEWED CORNER NO. #236

Feb. 1972

158

West

1/4 Corner Section 6, T32-2W.
Found- Iron Stone-W 1/4 clearly marked on west face.
Old BT. N.13°W. 91 lks., fallen down with rotten stump
standing, faint traces of scribing still visible.
Two large D. Firs stand in position of old S.E. BT.,
Did not open: 41"D.Fir S.1°54'E. 191.0 feet.
35" D.Fir S.3°23'E. 195.2 feet.
Set - Brass Cap W/Stone Alongside Stamped: T 32 S
New BT's: 17" Fir S.19°E. 55.9 ft., R3W R2W
scribed "1/4 S6 BT". S 6 1/4
8" Fir N.27-1/2E. 13.0 ft. 1972
scribed "1/4 S6 BT". RPLS 544

159

3/72

East 1/4 Corner Section 12, T32-3W.
Set - Brass Cap by proportionate measurement Stamped:
T32S 1972
1/4 S12
Established BT's: R3W PLS 544
15" D.Fir bears N.61°W. 18.9 feet)
13"D. Fir bears S.55°W. 27.2 feet) both scribed "1/4 S12 BT".

160

3/72

Center 1/4 Corner Section 12.
Set - Brass Cap by prop. measurement, stamped: T32W R3W
C 1/4 S12
1972
Established Bearing Trees: RPLS 544
10" Hemlock bears S.41°E. 49.8 ft.
15" Hemlock bears N.54-1/2° E. 19.1 ft.
(Both Scribed: "C 1/4 S12 BT".

161

3/72

Section Corner of Section 7 & 18 only, T32-2W.
Found - 25"x15"x10-1/2" Iron Stone by Staff Compass & Chain,
Irregular notches on North & South faces
Old Bearing Trees destroyed by Fire.
Set-Brass Cap @ Stone & redeposited Stone alongside Cap, stamped:
1972
T32S R32S
R3W S 7 R2W
S13 S 18
P.L.S. 544

162

Established Bearing Trees:
17" Fir bears N.26°E. 21.8 ft. scribed "S7 BT".
24" Fir bears S.40°E. 20.6 ft. scribed S18 BT".

163

1/4 Corner to Sections 12 and 13.
Set Brass Cap by prop. meas.: Stamped: T 32 S R 3 W
1/4 S 12
S 13
1972

Established Bearing Trees: RPLS 544
26" D.Fir bears N.2°E. 41.9 ft. scribed "1/4 S12 BT".
19" D.Fir bears S.55-1/2°W. 27.8 ft. scribed "1/4 S13 BT".

Jan. 1973

Don E. Garrett
For: U. S. of America - U. S. Forest Service
March 24, 1972
Map File M 44 - 62