

Douglas County Surveyor's Record of
Government Corners Renewed

32 T.S. 3 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21861

A 8" Fir scribed " T32S R3W 11 HES 186 CS BT" in a double blaze bears N 30°W., 45.8 ft.
A Brass cap on 1 1/2" Iron pipe stamped Douglas Co Surveyor #169
1975 T32S R3W Cor 8 HES 186 1975"
bears N88°E., 35.0 ft. Compass Declination 20°

Corner #11, HES 186. 169

Found - Orig. W.N.W. BT, is now 26" stump with scribed "X 11 HES 186 BT" visible, bears N. 83 1/2°W., 20.5 ft.
Orig. N.N.W. BT is blown down, center of hole left by roots, bears N.12°W., 23.8 ft.
No sign of orig. stone.

Set - Brass cap stamped, DOUGLAS COUNTY SURVEYOR T 32 S R 3 W
1975 Cor 11
+
HES 186

At corner from which:

A 8" Pine, scribed "T32S R3W 11 HES 186 CS BT" in a double blaze, bears S.26 1/2°E., 28.8 ft. (Note: scribe is on the west face of the tree.)
A 8" Fir, scribed "T32S R3W 11 HES 186 CS BT" in a double blaze, bears N.64 1/2°W., 41.7 ft. (Note: scribe is on SE face but does not face corner)
A brass cap stamped "Douglas County Surveyor, T32S R3W Cor 8 + HES 186 1975, bears S.43°E., 26.9 ft.
Compass declination 20°.

North 1/4 Corner for Sec. 21 only. 170

Set - 2"x30" I.P. with brass cap stamped T32S R3W 1/4 S21 PLS 536 1975.
BT's - 6" Fir, bears S.20°E., 14.8 ft. scribed N 1/4 S21 BT with brass washer stamped LS 536.
12" Madrone, bears S.89°E., 15.5 ft. scribed N. 1/4 S21 BT, with brass washer stamped LS 536 .
Note: F.B. 5, P.4 - Corner lies approx 100 ft. NORTH of draw, on steep south slope.

Center 1/4 Corner for Sec. 21. 171

Set - 2"x30" I.P. with brass cap stamped T32S R3W C1/4 S21 PLS 536 1975.
BT's - 8" Fir, bears N.46°W., 27.5 ft. scribed C1/4 S21 BT, with brass washer stamped LS 536.
12" Fir, bears N.39°E., 53.3 ft. scribed C1/4S21 BT, with brass washer stamped LS 536. F.B. 5, Pg. 6.

East 1/4 Corner Section 2 only. 172

Found - A 1 in. I.P. with brass cap marked "County Surveyor's Office" T32S R3W 1/4 S2 S1 1969. Pipe extends 1.2 ft. above ground an 18 x 12 x 4 in. slate stone mnrked "1/4" on west side of face firmly set north side of cap. (resurvey)
An unrecorded 1 in. I.P. bears S.85°E., 12.6 ft. extending 2.65 ft. above ground.
An 18" D. Fir (now 29") bears approx. S.34°E., 26.4 ft. This tree is down, shows previous chopping. (resurvey)
The SW BT from resurvey gone.
A 6" D. Fir, now 9", bears N.41°W., 24.6 ft. with well healed double blaze.
A 9" D. Fir now 12", bears approx. N.74°E., 15.1 ft. This tree down with faint scribing visible.
Set - X'd out "S1" on Brass cap. Added "only Restamp 1979".
New BT - A 14" D. Fir bears S.70°W., 49.1 ft. scribed "1/4 S2 CS BT" in double blaze.
Searched for original 1/4 cor. Fd. no trace.

2/28/79

Clell Goodwin, Surveyor's Office
G. Langlitz
Vic Cangie
L. Ladig
C.S. 57/34

Glenn Baughman Surveying Ser
For: U.S. Forest Service
July 1975
M 56 - 20

ren Reed
L. Earle
ug. Co. Surv-
ors Office
Feb. 28, 1979
C.S. 60/24