

Douglas County Surveyor's Record of  
Government Corners Renewed

32 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Center 1/4 Corner Sec. 6

Set - 5/8" Iron Rod, 24 inches long, 20 inches in the ground.

BT's - A fir stump, 20 ins. diam., bears S. 37 1/2° E.,  
178.6 ft. dist., with spike at base  
A fir, 15 ins. diam., bears N. 66 1/4° W., 95.7 ft. dist.,  
with spike at base.

FOOK R. Brown  
2/2009 M157-10

173

Terrence U. Nickerson  
For: U.S. Bureau of Land Management  
October 1979  
M 80 - 71

1/4 Corner Sec. 6 and Sec. 31, T.31S. R3W. Ren. #28

Set - 5/8" Iron Rod, 24 ins. long, 20 ins. in the ground.

BT's - A fir, 10 ins. diam., bears N. 30 1/4° E., 198.0 ft. dist.,  
with spike at base.  
A fir stump, 32 ins. diam., bears S. 12° E., 327.7 ft.  
dist., with spike at base.

Note - This corner set by proportionate distance, there is no  
remaining evidence of the original cor. or the perpetuation  
by Wenderoth and the Douglas County Surveyor's Office.  
This area is now a cultivated field with all trees and  
stump removed.

174

1/4 Corner Sec. 6 and Sec. 1, T.32S. R.4W. Ren. # 20

Fd. - 2 ins. iron pipe, firmly set, protruding 6 ins. above the  
ground.

BT's - Found the remains of the remaining original bearing tree  
A sawed fir stump, 21 ins. diam., bears N.68°E., 5.3 ft  
dist., with no mks. visible on rotted, opened blaze.  
A bearing tree mkd. by Wenderoth, a fir snag, 24 ins. diam.  
bears N.48°W., 12.0 ft. dist., with bark scribe mks. 1/4S  
T32S R4 W visible. (Measured to face)

New BT - A fir, 8 ins. diam., bears S.61 3/4°W., 14.5 ft. dist.,  
mkd. 1/4 S1 BT.

175

Terrence O. Nickerson  
For: U.S. B.L.M.  
October 1979  
M 80 - 71

FOOK, NYGREN, 11/96 M124-34

Section corner for Secs. 9, 10, 16 and 15.

Found - 1" I.P. firmly set, projecting 12" above ground with a  
2 1/2" Brass cap mkd: "T32S R3W WM 9 10 15 16 1969 536" Ren. #61

From which:

Orig. BT, a 32" D. Fir stump, scribe marks "BT" visible, bears  
N.2°E., 26.4 ft.

A 20" D. fir stump scribe marks "R3W S9 BT" visible, bears  
N.43°W., 38.9 ft. to face.

A 24" D. Fir, with healed blaze, bears S.1°E., 37.6 ft.

A 16" Sugar pine, with healed blaze, bears S.75°E., 4.0 ft. Ren. #2

A 10" Madrona, with healed blaze, bears N.77°W., 18.1 ft.

(Record 19.1 ft.) Ren. #2

A 10" Laurel, scribe marks "T32S R3W S10 BT" visible bears  
N.57 1/2°E., 18.9 ft. Ren. #61

A 10" D. Fir with healed blaze, bears N.54°W., 17.9 ft.

New BT - A 24" D. Fir, bears S.41°W., 47.9 ft. marked "T32S R3W S16 BT"  
on a double blaze and nailed a brass washer stamped "LS 536" into  
into lower blaze.

176

Glenn S. Baughman, LS #536  
For: U.S. Forest Service  
November 1979  
C.S. 58/176

Section corner for Secs. 15 and 16 only.

Found - 1" I.P. firmly set, projecting 12" above the ground with a  
2 1/2" Brass cap mkd: "County Surveyors Office T32S R3W  
S15 S16 S21 1969". Ren. #75

From which:

A 20" D. Fir with healed blaze, bears N.64°W., 13.2 ft. to face.

A 18" D. Fir, high cut stump, with healed blaze, bears N.50°E.  
9.2 ft.

A 20" D. Fir, with healed blaze, bears S.37°W., 9.2 ft.

New BT - A 14" D. Fir, bears N. 2 1/2°E., 97.7 ft. marked "T32S R3W  
S15 S16" on a double blaze and nailed a brass washer stamped  
"LS 536" into lower face.

177

FOOK 12/83  
L. HERSTMAN  
USFS  
05.02/15

RE-RENEWED SEE CORNER NO. #223