

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 S T. S. R 3 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 91881

Malcolm Clark - Chickering Green/Empire, Inc.
For: U. S. Forest Service
March 12, 1980
M 82 - 68 and C.S. 58/227 n

Malcolm Clark - Chickering/Green Empire Inc.
For: U. S. Forest Service
April, 1980
M 83 - 53 - C.S. 58/227
M 83 - 54

182
1/4 Corner for Sec. 20 only.
Set - Aluminum cap by proportion marked T.32S R3W 1/4 S20 R.L.S. 601 1980".
Found - 18" Yew bears S.72°00'E., 37.8 ft.
10" D. Fir S.37°45'W., 35.3 ft. Ren. #8
A 1 1/4" G.I.P. is S.07 ft. and E. 8.0 ft. of corner.

183
Closing Corner for Secs. 20 and 21 only.
Found - 1969 County brass cap. Ren. #73 245
10" D. Fir, N.14°E., 7.0 ft.
New BT's - 12" D. Fir, S.51°E., 17.7 ft. scribed "T32S R3W S31 CC BT"
12" D. Fir, S.13°W., 69.0 ft. scribed "T32S R3W S20 CC BT"

184
Center 1/4 Corner for Section 20.
Set - Aluminum cap by proportion marked T32S R3W C 1/4 S20 RLS 601 1980.
New BT's - 8" Hemlock, S.76°10'W., 44.0 ft. #242
14" Hemlock, N.35°10'E., 49.4 ft.
Both scribed "T32S R3W C 1/4 S20 BT"

185
Section Corner for Secs. 20, 21, 29 and 28.
Found - 1969 County Brass cap Ren. #84
44" D. Fir stump, N.52°05'E., 105.4 ft.
Rotten stump, S.54°10'E., 33.4 ft.
14" stump, S.39°05'W., 41.4 ft.
12" D. Fir, N.54°15'W., 22.1 ft.
New BT's - 22" D. Fir, N.78°20'E., 154.2 ft. scribed "T32S R3W S21 BT"
12" D. Fir, S.48°20'E., 259.5 ft. scribed "T32S R3W S28 BT"
16" D. Fir, S.16°55'W., 95.7 ft. scribed "T32S R3W S29 BT".
3/21/80

186
Center 1/4 Corner for Sec. 2
Set - A 2 1/2" x 30" Alum. pipe, flared at bottom with an alum. cap stamped: T32S R3W C 1/4 S2 1980 RLS 601
New BT's 12" D. Fir, N.77°30'W., 13.8 ft.
14" D. Fir bears S.30°00'W., 14.6 ft.
Both trees scribed "T32S R3W C 1/4 S2" on upper blaze and "BT" on lower blaze. A 3/4" brass disc stamped "RLS 601" was nailed flush with lower blaze.

187
Section Corner for Secs. 1 and 6 only. (NE cor. Sec. 1)
Found - 3/4" Iron pipe next to 10" x 10" x 9" stone. See Ren. #1 -T.32-2
Set - Alum. cap at location of pipe stamped: T.31S R2W S31 S1 S6 R3W R2W T32S 1980 RLS 601".
Found BT's -
5" Madrone bears N.38°25'W., 15.8 ft.
6" Madrone bears S.83°55'E., 9.8 ft.
10" Madrone bears S.26°35'E., 34.1 ft.
17" D. Fir bears S.19°35'W., 33.6 ft.

188
1/4 Corner for Sec. 1 only. (north)
Set - Alum. cap by proportion stamped: T31S R3W 1980 RLS 601.
1/4 S1
New BT's: T32S R3W
14" D. Fir bears S.16°15'E., 49.2 ft.
16" D. Fir bears S.38°45'W., 39.0 ft.
Both scribed "T32S R3W 1/4 S1 BT".

189
1/4 Corner for Section 1 only. (West)
Set - Alum. cap by proportion stamped: T32S R3W 1/4 S1 1980 RLS 601.
New BT's - 10" D. Fir bears S.59°25'E., 27.0 ft.
11" D. Fir bears N.29°20'E., 15.6 ft.
Both trees scribed "T32S R3W 1/4 S1 BT".
(1/4 Corner for Sec. 2 only bears north 45.85 ft.)