

Douglas County Surveyor's Record of
Government Corners Renewed

T 32

T. S. R 3

R. W. W. M.

MOSE-CHAPMAN CO., EUGENE, ORE. 21991

190

Center 1/4 Corner for Section 1
Set - Alum. cap by proportion stamped: T32S R3W C 1/4 S1 1980 RLS 601.
New BT's- 13" Ponderosa Pine bears N.34°10'W., 37.2 ft.
12" Madrone bears S.85°50'E., 37.1 ft.
Both trees scribed "T32S R3W C 1/4 S1 BT".

Malcolm Clark
Chickering/
Green Empire
For: U.S. Forest
Service
April, 1980
M 83 - 53 &
M 83 - 54

1/4 Corner for Sec. 1 only. (east)
Set - Alum. cap by proportion stamped: "T32S R3W 1/4 S1 R2W
1980 RLS 601"
New BT's-24" D. Fir bears N.33°30'W., 42.8 ft. scribed "T32S R3W 1/4 S1 BT".
6" D. Fir bears S.09°40'E., 41.4 ft. scribed "T32S R3W 1/4 S1 BT".

191

Section corner for Sections 1, 2, 11 and 12.
Found - Douglas County Surveyors 1959 brass cap.
18" Hemlock bears S.01°20'W., 91.2 ft.
24" D. Fir bears N.86°35'W., 204.3 ft. scribed "T32S R3W S1 BT"
New BT's-12" Knobcone pine bears N.12°40'E., 555.0 ft. scribed
"T32S R3W S1 BT"
18" White fir bears S.03°35'E., 250.7 ft. scribed "T32S R3W
S12 BT".

192

Both new BTs have a 3/4" brass disc stamped "RLS 601" nailed flush with lower blaze.

FO. OK 7/95 BY LANG - M123-79

1/4 Corner for Secs. 7 and 8.
Found - 20" Fir snag bears S.72°W., 10.6 ft. (16 lks.) Shows bark blaze.
30" Fir windfall bears N.52°E., 17.8 ft. (27 lks.) bark scribed
"R", "T", & "B".

193

Set - Alum. cap from orig. BT's stamped: T32S R3W 1/4 S7 S8 1980
RLS 601".
New BT's-18" D. Fir bears N.85°45'E., 72.9 ft. scribed "T32S R3W 1/4 S8 BT".
14" D. Fir bears N.14°40'W., 46.4 ft. scribed "T32S R3W 1/4 S7 BT".

Malcolm Clark
Chickering/Green
Empire
For: U.S. Forest
Service
April 1980
M 83 - 55
and C.S. 58/227 (n)

Center 1/4 Corner for Section 8
Set - Alum. cap by proportion stamped: T32S R3W C 1/4 S8 1980 RLS 601".
BT's - 6" D. Fir bears S.77°10'E., 39.7 ft.
5" D. Fir bears N.16°35'W., 26.6 ft.
Both trees scribed "T32S R3W C 1/4 S8 BT".

194

FO. OK 7/95 BY LANG - M123-79

1/4 Corner for Secs. 8 and 17.
Set - Alum. cap by proportion stamped: T32S R3W 1/4 S8 S17 1980 RLS 601.
BT's - 13" D. Fir bears N.06 1/2°W., 63.5 ft. scribed "T32S R3W 1/4 S8 BT".
16" D. Fir bears S.72°W., 33.6 ft. scribed "T32S R3W 1/4 S17 BT".

195

Malcolm Clark
For: U.S. Forest
Service
April 1980
M 83 - 54 and
C.S. 58/227 (n)

1/4 Corner for Secs. 2 and 11.
Found - 5/8" rebar REN. # 148
12" D. Fir bears S.50°00'W., 25.7 ft. (blazed & Healed)
6" Madrone bears N.57°45'W., 15.6 ft. scribing visible.
Set - Alum. pipe, flared at the bottom with an alum. cap stamped:
"T32S R3W 1/4 S2 S11 1980 RLS 601."

196

William Ruppert
For: U. S. Forest
Service
June 1980
C.S. 58/229

1/4 Corner for Section 36 only of T.31-3.
Found - 4" x 10" x 14" stone with "1/4" plainly visible on north face
a 45" Ponderosa Pine bears S.23°34'E., 83.8 ft. with a good scar.
Set - A 2" x 30" alum. pipe into the ground and constructed a mound of
stones around it. I marked the attached 2 1/2" alum. cap as
"T31S R3W 1/4 S36 PLS 866 1980".
New BT's -26" D. Fir bears N.71°12'E., 29.8 ft. scribed "1/4 S36 BT".
26" D. Fir bears N.21°35'E., 11.5 ft. scribed "1/4 S36 BT".
with a brass washer marked "LS 866 nailed to each lower blaze.

197