

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 T. S. R 3 R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97501

198

William Ruppert
For: U.S. Forest
Service
May 1980
M 84 - 4
C.S. 58/143 (n)

S.E. Corner for Section 36 only of T.31-3
Found - 1" Galv. I.P. with 2 1/2" brass cap, 1966 County. See Ren. #50
15" Incense cedar, N.40°20'E., 68.4 ft. "T32S R3W S1 CS BT" visible
16" Rotten stump, S.15°56'W., 28.5 ft. two faces, one face
chopped scribing visible.
31" Fir uproot, N.59°24'W., 60.6 ft. hollow face.
New BT - 13" Yew N.64°24'W., 67.6 ft. scribed "T31S R3W S36 BT". attached
3/4" brass washer marked "LS 866 to lower blaze.

5/80

199

William Ruppert
For: U.S. Forest
Service
May 1980
M 84 - 6
C.S. 58/143 (n)

1/4 Corner for Section 30 only of T.32-2
Found - Original 12" x 12" x 12" stone, loosley set and broken in
two, no marks.
16" Madrone, N.3°06'E., 27.3 ft. hollow
50" snag, S.15°36'W., 47.9 ft. good snag
Set - 2" x 30" Galv. Iron pipe with 2 1/2" brass cap marked:
T32S R2W 1/4 S30 PLS 866 1980, at location of stone.
New BTs - 6" Chinquapin, S.47°04'E., 31.3 ft. scribed "1/4 S30 BT"
7" D. Fir, N.14°46'E., 70.7 ft. scribed "1/4 S30 BT"
Attached 3/4" brass washer marked "LS 866" to lower blaze of each new BT.

5/80

200

Leonard Herzstein
USFS - Deputy, Doug.
Co. Surveyors Off.
Witness: Rod
Riley; Art Arciniega
August 14, 1980
C.S. 61/11

Section corner for Secs. 2 and 3; and 34 & 35 of T.31-3.
Found - 1966 County brass cap properly marked, firmly set, projecting
12" above ground on a 1 1/4" I.P. Ren. #48
Orig. 28" Hemlock snag, N.38°E., 12.5 ft. with opened face, no
marks visible.
Orig. 28" W. Fir stump, S.31°W., 14.5 ft. with scribe marks
"T32S" visible on decaying blaze.
A 1948 Wenderoth BT, Ren. #12 in T.31-3, A roothole, S.36°E
33.0 ft. with 6" Hemlock alongside with scribe marks "S2 BT"
visible on partly healed blaze.
1966 BT by Powell, Ren. #48, A 20" Hemlock snag, N.86°E., 2.1 ft.
with scribe marks "T31S R3W S35 CS BT" visible on partly healed
double blaze.
A 14" Hemlock, S.9°W., 27.0 ft. with healed double blaze.
A 56" D. Fir, West, 66.3 ft. with healed blaze.
New BT's - A 14" Hemlock, N.70°E., 46.0 ft. scribed "T31S R3W S35 CS BT"
7" Hemlock, S.38 1/2°E., 45.2 ft. scribed "T32S R3W S2 CS BT"

West 1/4 Cor. to Sec. 7 only (T.32-2).

Found - From a 1902 survey, the corner tree marking the West 1/4 of
of Sec. 7 only, originally a 10" Fir, now 16" (dbh) D. Fir.
This tree has an opened blaze on East face, with scribing
"S7" visible. Also on this face is nailed a bronze washer
with markings "2741".

201

Stephen Flause
Deputy, Doug. Co.
Surveyors Office
T.R. Plouff
Feb. 26, 1981
S.C. 61 / 24

From this tree, a 2 1/2" B.C. on a 2 1/2" I.P. (o.d.) protruding
21" from ground & firmly set bears S.83°E., 2.5-ft., per
M 44 - 62. The found B.C. is marked "1/4 S7 1968 OLS 536"
& is recorded in renewal # 60

Orig. BT - 12" Fir (now, 16"), bears N.72°W., 16.2-ft. Partially healed
blaze has fragmentary scribing visible... "45".

20" Fir with healed blaze bears S.59°E., 26.5-ft. REN. # 60
New BT - 11" D. Fir, scribed "WC 1/4 S7 CS BT" bears N.40°E., 22.6-ft

202

Leonard Herzstein
U.S. Forest Service
Deputy, Doug. Co.
Surveyor
Witness: Tom Wolford
June 30, 1981
C.S. 61 / 27
Declination= 19 1/2°

East 1/16 corner between Sec's. 5 and 8.
Found - 2" I.P. set by Don Garrett in 1971, firmly set, projecting
6" above ground, with a Brass Cap properly marked and
with 'RLS 544' stamped on cap. M 44 - 8.
26" D. Fir snag bears S.71 1/2 °E., 23.3-ft., with healed blaze.
14" D. Fir bears N.5°W., 18.9-ft., with healed blaze.
New BT - 12" D. Fir bears S.1°E., 45.1-ft., marked E 1/16 S8 CS BT
on a double blaze.

6/30/81