

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 32 S.    T. S.    R. 3 W.    R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

203

Sec. corner common to Sec's. 5 & 6 and Sec's. 31 & 32 of T.31S.R.3W.  
 Found - 1" I.P. with Brass Cap, Renewal #42.  
 firmly set, projecting 10" above ground, marked:  
 County Surveyors Office T31S S31 S32 R3W S6 S5 T32S 1965 ,  
 and a 1 3/4 " I.P. alongside.

BT's - 36" D. Fir (Orig. BT) bears S.22°E., 59.4-ft. to face with  
 scribe marks BT visible on bark blaze.  
 17" D. Fir bears S.12°E., 31.3-ft., with Ren.# 42.  
 healed double blaze.  
 9" P. Pine bears S.35°W., 24.1-ft. (REC 24.6-ft.), with  
 healed double blaze.  
 13" P. Pine bears N.38°W., 16.7-ft. (REC 17.0-ft.), with  
 healed double blaze.  
 22" D. Fir stump bears N.16°W., 95.0-ft. (REC 94.0-ft.)  
 with healed blaze.

New BT - 10" P. Pine bears N.30°E., 16.6-ft. scribed T31S R3W S32  
 CS BT on a double blaze.

\*NOTE - Corner is 50.0-ft. East of BLM Snow Creek access Road.  
 7/1/81

204

Sec. corner common to Sec's. 4, 5, 8, & 9.  
 Found - 1" I.P. with Brass Cap, firmly set, projecting 14" above  
 ground marked: County Surveyors Office T32S R3W S5 S4  
 S8 S9 1970 . Ren.# 146.

BT's - A roothole (remainder of Orig. BT), bears S.70°E., 23.8-ft.,  
 with a 32" D. Fir tree alongside, rescribed by G.  
 Wenderoth, Deputy County Surveyor in 1955, with scribe  
 marks S9 CS BT visible on partly healed double blaze.  
 20" D. Fir stump bears S.41°W., 69.2-ft., with scribe marks  
 S8 CS BT visible on partly healed double blaze. Ren.# 26.

A roothole bears N58°W., 53.8-ft., with scribe marks  
 S5 CS BT visible on partly healed double blaze.  
 A Madrone root crown (size indeterminate) Ren.# 146.  
 bears S.28°W., 55.9-ft. (REC 58.2-ft.).  
 24" D. Fir stump bears N54°W., 53.8-ft. (REC 47.0-ft.),  
 with no marks visible.

New BT's- 6" Hemlock bears N.13 1/4 °E., 44.5-ft., scribed T32S R3W  
 S4 CS BT on a double blaze. (Base of lower blaze is  
 3.0-ft. above ground.  
 6" Hemlock bears S.74°E., 55.4-ft., scribed T32S R3W S9  
 CS BT on a double blaze.  
 6" D. Fir bears S. 65°W., 58.2-ft., scribed T32S R3W  
 S8 CS BT on a double blaze.  
 6" D. Fir bears N.12°W., 34.0-ft., scribed T32S R3W  
 S5 CS BT on a double blaze. (Base of lower blaze is  
 3.0-ft. above ground. 6/30/81

205

1/4 corner for Sec's. 10 & 15.  
 Found - 1 1/4 " I.P., with Brass Cap, firmly set, projecting 12"  
 above ground, marked:, R32S R3W W.M. 1969 1/4 10 15 OLS 536  
 with 3/4" I.Rod alongside. Renewal # 14.

BT's - 34" D. Fir snag bears N.59°E., 24.6-ft. with scribe marks  
 1/4 S10 CS BT visible on double bark blaze.  
 62" D. Fir stump bears South, 5.2-ft. (2.2-ft. to face)  
 (REC 3.2-ft.) with scribe mark T visible on bark blaze.  
 15" I. Cedar bears S.61°E., 19.9-ft. (REC 19.1-ft.) Ren # 62.  
 with fragmentary scribe marks visible on partly healed blaze.

New BT's- 14" D. Fir bears N.50 1/4 °E., 36.0-ft., marked 1/4 S10  
 CS BT on double blaze.

\*NOTE - Corner is on top of spur ridge running North & is about 300-ft.  
 East of main North-South ridge. Corner is 960-ft. West of  
 Centerline of USFS Rd#3231. 7/8/81

Leonard Herzstein USFS  
 Deputy, Douglas County Surveyor  
 Jim Landrum, witness  
 June & July, 1981  
 C.S. 61 / 27