

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 32S. T. S. R. 3W. R. W. W. M.

See CS 65/57-1 A&B
For USFS Narrative

ROSE-CHAPMAN CO., EUGENE, ORE. 21881

concerning 1/4 Secs 14/14
& Center 1/4 Sec 14

Leonard Herzstein 21545
Deputy Douglas County
Surveyors Office
Jim Landrum, and Jerry
Pierce, witnesses
Oct. 8, 1981
C.S. 61 / 29

206

Center 1/4 corner for Sec. 14.
Found - 2" I.P., firmly set, projecting 6" above ground Ren.#152
w/ B.C. marked: T32S R3W CNTR 1/4 COR S14 ORE LIC 544 1971,
set by Don Garrett. Ren.#152
BT's - 10" Hemlock, S80°E., 19.0-ft. (Rec. W. Fir, S80°W.), w/scrib
marks: C1/4 S14 BT visible on partially healed blaze.
12" Hemlock, S62 1/2 °W., 8.9-ft. (Rec. W. Fir), w/ scribe
marks: C1/4 S14 BT visible on partially healed blaze.
Note - Cor. is on steep No. slope at South edge of clear cut 10/8/81

207

1/4 corner common to Sec's. 15 & 14.
Found - 1 1/2 " I.P., firmly set, projecting 12" above ground. Ren#98
I.P. is in old rd. bed & lies above an old log which is
4-ft. above the natural grade. This corner may collapse
or erode away in the future.
BT's - 16" Fir snag bears S.2°E., 13.1-ft. to face, w/scribe Ren# 32.
marks W3R S23T 41S 4/1 visible on partly decayed dbl. blaze.
11" half-dead Yew bears S.58°E., 142.5-ft. Ren. # 36.
to face, w/scribe marks S23T 41S 4/1 TB visible on
partly healed dble. blaze.
12" W. Fir snag bears S.49°E., 176.0-ft. Ren. # 36.
w/scribe marks 41S 4/1 TB visible on partly healed
dble. blaze.

Note - Marks by Markham are scribed from bottom to top as if left-handed.
BO - 3/4" re-bar bears N.53°W., 50.0-ft., buried 2" under ground,
with top 6" bent over horizontal with ground. Ren# 98.
Set - I set a steel fence post 1.2-ft., N.53°W. of I.R., with U.S.F.S.
signs #54-4, & #54-3 attached. I.R. is on West edge of an
old dirt road.
New BT's- 5" W. Fir bears N.45°E., 44.0-ft., scribed 1/4 S14 CSBT (dbl blaze)
7" D. Fir bears N.88°W., 7.6-ft., scribed 1/4 S15 CSBT (dbl blaze)
Note - Corner lies on West side of old dirt rd., 25-ft. North of creek,
and 125-ft. South of USFS Rd. #3242. 10/29/81

208

Sec. corner common to Sec's. 4, 3, 9, & 10.
Found - 1 1/2" I.P., firmly set, projecting 4" above ground, with B.C.,
marked per Renewal # 64., with 2" I.P. alongside (Ren.# 1).
BT's - Remains of orig. BT's:
30" W. Fir snag bears N.70°E., 9.3-ft. w/fragmentary scribe
marks visible on previously opened blaze & rescribed by
Byron in 1957, w/scribe marks W CS BT visible on bark blaze.
Decayed W. Fir stump, size indeterminate, bears N.65°W., 31.7-ft.
with no marks visible.
B. Irving's BT's marked in 1945. Renewal # 1.:
Decayed W. Fir stump, size indeterminate, bears S.64°W., 50.5-ft.
with no marks visible.
J. Byron's BT's marked in 1957. Renewal # 30.:
23" Yew-wood bears S.2°E., 184.4-ft., with scribe marks
S10 T32S R3W CSBT visible on partly healed double blaze.
35" W. Fir bears S.89 1/2 °W., 140.0-ft. with healed
double blaze.
G. Baughman's BT's in 1969 Renewal # 64.
20" Fir snag bears N.84°E., 29.9-ft. (Rec. 28.9-ft.), with
scribe marks T32S R3W S3 BT visible on partly healed
double blaze.
New BT's- 6" W. Fir bears N.82 1/2 °E., 39.9-ft., scribed T32S R3W
S3 CSBT on double blaze.
No suitable trees in Sec. 4.
Note - Corner is in East-West fence line, approx. 100-ft. S.70°W. of
the confluence of Dismal and Cow Creeks; and is 30-ft. South
of the top of the South bank of Cow Creek. 10/15/81

Leonard Herzstein U.S.F.S.
Deputy Douglas County Surveyors Office
Jim Landrum, witness
October 15, 1981
C.S. 61 / 29