

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 T. S. R 3 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

209

Section corner for Secs. 10, 11, 14 and 15
CORNER REPORT ONLY

Found - 1969 County brass cap properly mkd., firmly set, projecting 18" above ground. Ren. #99
Orig. corner stone is set alongside with "+" on north side and 4 lines mkd. on top.
1912 GLO, 16" D. Fir bears N.40°E., 16.5 ft. with healed double blaze.
1912, A roothole, bears S.65°E., 36.8 ft. with 60" D. Fir log alongside with bark blaze face down.
1912, A 24" D. Fir bears S.70°W., 10.6 ft. with fragmentary scribe marks visible on previously opened double blaze.
1912, A 12" D. Fir bears N.14°W., 13.9 ft. with healed blaze.
A 29" D. Fir bears N.50°E., 18.2 ft. (Rec. 12.2 ft.) with scribe marks "T32S R3W S11 CS BT" visible on bark blaze. Ren. #15
A 14" D. Fir S.85°W., 34.9 ft. with healed double blaze. Ren. #15
A 14" Madrone bears S.4°E., 24.0 ft. with scribe marks "T32S R3W S14 CS" visible on partly healed double blaze. Ren. #99
Note - Corner is at NE corner of USFS clear-cut and about 350 ft. north of end of USFS Rd. #3242-S

11/19/81

CONDITION REPORT ONLY.

1/4 Corner common to Sec. 3 and Sec. 34 of T. 31-3. #235
Found - 1 & 1/4" I.P., firmly set, projecting 8" above ground with properly marked B.C. per Ren. # 47, with a 1 & 1/2" I.P. alongside (outside diameter... per Ren. # 13, in T.31-3.
BT's - 12" Fir, now a root-hole, bears N.39 1/2 °E., 18.9-ft. (Rec. N.39°40'E.), with a 12" D. Fir log alongside with fragmentary scribe marks on partly healed double blaze.
10" Fir, now a root-hole, bears S.71 1/2 °E., 12.3-ft. (Rec. S.71°24'E.), with a rotten log alongside w/no marks visible.
18", still 18" D. Fir bears N.28°W., 23.8-ft. per Ren. # 47, T.32-3, with healed double blaze.
7", now 9" W. Fir bears S.71 1/2 °W., 18.8-ft. with healed double blaze. RE-RENEWED

11/24/81

210

CONDITION REPORT ONLY.

1/4 Corner common to Sec's. 3 & 4.
Found - 1 & 1/4" I.P., firmly set, projecting 14" above ground w/B.C., properly marked, with 1" I.P. alongside. Ren. # 86.
BT's - 6", now 7" Yewwood bears S.44°W., 54.8-ft., w/scribe marks: "1/4 S4 CSBT" visible on partly healed double blaze. Ren. # 12.
46" D. Fir bears S.15°E., 19.6-ft. w/scribe marks: "1/4 S3 CSBT" visible on partially healed blaze. Ren. # 86.
Note: - Fence corner bears N.71°E., 16.0-ft., w/fence running South & West. Corner is about 100-ft. NW of dirt road.

11/25/81

FD OK 10/94 - M121-13

FO. OK 7/95 BY LANG - M123-79

211

Sec. Corner common to Sec's. 5, 6, 7, & 8.

Found - 1" I.P., firmly set, projecting 12" above ground, w/B.C., properly marked, with a 1 & 1/4" Iron Pipe alongside per Renewal # 10. Ren. # 102.
BT's - 30" D. Fir, now a root-hole, bears S.22 1/2 °E., 27.0-ft., with 35" D. Fir log alongside, w/scribe marks visible on double bark blaze. Orig. BT
24" D. Fir, now a root-hole, bears S.10°W., 27.7-ft., with 25" D. Fir log alongside, w/healed dbl. blaze. Orig. BT
18" Fir, now 20" D. Fir bears N.54°45'W., 9.2-ft., with healed double blaze. Orig. BT
10" Hemlock, now 17" bears N.36 1/2 °E., 12.4-ft. Ren. # 10 with healed double blaze.
New BT's- 15" W. Fir bears S.39 1/2 °E., 52.0-ft. scribed "T32S R3W S8 CSBT" on a double blaze.
Note: - Corner lies on E. slope, about 100-ft. West and 150-ft. South of Snow Ck. Rd.

11/23/81

212

Leonard Herzstein
U.S.FS Deputy,
Doug. Co. Surveyor
Office.
Witness: Jim
Landrum
Nov. 19, 1981
C.S. 61/29

Leonard Herzstein, USFS
Deputy Douglas County
Surveyors Office
Jim Hamilton, witness
Nov. 14, 1981
C.S. 61 / 29

Leonard Herzstein, U.S.F.S.
Deputy, Douglas County
Surveyors Office
Randy Lopez & Jim Hamilton, witnesses
Nov. 23 & 25, 1981
C.S. 61 / 29