

Douglas County Surveyor's Record of  
Government Corners Renewed

T 32 T. S. R 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Leonard Herzstein,  
U.S. Forest Service  
Jim Landrum; Jim  
Hamilton  
Nov. 30, 1981  
C.S. 61/29

1/4 Corner for Sections 4 and 5

213

CONDITION REPORT ONLY

Found - 3" dia. I.P. firmly set, projecting 8" above ground with brass cap marked T32S R3W WM. 1/4 S5 S4 1971 RLS 544, set in 1971 by Don Garrett, L.S. #544. (M 44 - 8) 1" dia. I.P. along e. A decayed Pine stump, size indeterminate, S.50°E., 25.7 ft. with no marks visible.  
A 26" D. fir stump, N.52°E., 97.7 ft. with scribe marks "S 5 BT" visible on open blaze. Ren. #25  
A 12" Hawthorn, 1/2 dead, S.40°W., 91.3 ft. with scribe marks "C BT" visible on blaze laying alongside BT. Ren. #25  
A 10" D. fir, N.28°E., 21.0 ft. with healed double blaze. Ren. #123  
A 20" D. fir, N.72°W., 30.0 ft. with healed double blaze. Ren. #123

FOOK 10/94 - M121-13

1/4 Corner for Secs. 21 and 22.

214

Found - 1" I.P. with 1969 County brass cap properly marked, firmly set projecting 16" above ground, leaning slightly SE, set by John Powell. Ren. #66  
Orig. 46" D. fir, N.55°E., 39.4 ft. (Rec. 40.3 ft.) with healed blaze.  
Orig. 28" D. fir stump, N.14°W., 48.8 ft. toface with old axe marks visible on decayed blaze.  
A 10" madrone, N.3°E., 40.1 ft. (Rec. 40.5 ft.) with scribe marks "1/4 S22 CS BT" visible on partly healed blaze. Ren. #66  
New BT - A 7" P. Pine, N.77°W., 23.8 ft. scribed "1/4 S21 CS BT" on double blaze.

Note: Corner lies on steep SE slope about 150 ft. west of USFS Rd. #3231 5/3/82

Corner #7, H.E.S. #186

215

Found - 1" I.P. with 1969 County Brass cap properly mkd., firmly set projecting 12" above ground. Ren. #139  
Orig. BT, a 36" D. fir stump, N.62 3/4°E., 16.5 ft. with scribe marks "186 BT" visible on partly healed blaze.  
Orig. BT, A 30" D. fir stump, N.45°W., 19.1 ft. with scribe marks "X7 HES 186 BT" visible on previously opened blaze. (blaze faces S.10°E.)  
19" D. fir, N.31°E., 42.8 ft. (Rec. 43.3 ft.) with healed blaze.  
20" W. fir snag, S.43°E., 42.3 ft. with scribe marks "HES 186 CS BT" visible on partly healed blaze. Ren. #139

New BT - 5" D. fir, S.31°W., 14.2 ft. marked "7 HES 186 CS BT" on double blaze.

Corner #12 bears N.44 1/2E., 78.06 ft. Corner #7 lies 20 ft. NW of USFS Rd. #3231.

4/26/82

Corner #9, H.E.S. #186

216

CONDITION REPORT

Found - 1" I.P. with 1969 County brass cap properly mkd. projecting 14" firmly set. Ren. #140  
10" D. fir, S.50°W., 41.5 ft. with healed blaze. Ren. #140  
9" D. fir, N.15°W., 35.6 ft. with healed blaze. Ren. #140  
Orig BT a 28" D. fir stump, S.1 3/4°E., 95.0 ft. with scribe marks "86 B" visible on previously opened blaze.

Add 3 ft. diam. mound of stone. I.P. and brass cap now project 6 inches. Set 6 ft. steel fence post S.35°W., 2 ft. with USFS sign #54-4.

4/22/82

Corner #15, H.E.S. #186

217

Found - 1" I.P. with 1969 County brass cap properly mkd. loosely set, projecting 16" above ground. Ren. #144  
Orig. corner stone alongside with marks "15 HES 186" on bottom side.  
10" D. fir, S.77°E., 34.0 ft. (Rec. 34.6 ft.) with healed blaze. Ren. #144  
Original SW BT falls in creek. No evidence found.  
Corner #16, HES 186 bears N.77°E., 85.7 ft. (rec. 86.5 ft.)  
Set - Reset I.P. & brass cap which now projects 12" above 2 ft. diam. mound of stone. Buried orig. corner stone alongside.

Leonard Herzstein, U.S. Forest Service  
Jim Landrum  
Jim Hamilton  
April 22 - May 3, 1982  
C.S. 61/32