

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 32

T. S.

R 3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

**217**

C O N T. - -  
Jim Landrum, USFS  
Leonard Herzstein  
April 28, 1982  
C.S. 61/32

(Corner #15, HES #186)  
New Accessories:  
A 10" D. fir, N.0 1/2°E., 54.2 ft. scribed "15 HES 186 CS BT"  
on double blaze. (this BT is on west side of Applegate Creek.)  
6 ft. steel fence post, N.77°E., 1.6 ft. with USFS sign  
#54-4 attached.  
Corner is 10 ft. east of Applegate Creek and about 40 ft. east of USFS  
Road #3231 at rock quarry.

4/28/82

**218**

S 1/16 for Secs. 21 and 22  
Found - 2 1/2" I.P. with 1974 brass cap properly mkd. firmly set  
flush with 1 ft diam. mound of stone. (M49-69;M56-20)  
12" half dead alder, N.68°E., 25.4 ft. with scribe marks  
"S 1/16 S22 BT" and brass washer stamped "RLS 536" visible  
on partly healed double blaze.  
8" hemlock stump, N.03 1/2°W., 26.9 ft. (rec. N.06°W., 26.6 ft.)  
with scribe marks "S 1/16 S21 BT" and brass washer stamped  
"RLS 536" visible on partly healed blaze.  
1" iron rod, bears N.82°E., 4.3 ft. projecting 8" above ground.  
New BT's- 10" yew, S.23°E., 8.7 ft. scribed "S 1/16 S22 CS BT" on double  
blaze.  
8" W. fir, N.79 1/4°W., 88.1 ft. scribed "S 1/16 S21 CS BT" on  
double blaze.  
6 ft. steel fence post, North 2.0 ft. with USFS signs #54-2 and  
#54-9 attached.

Corner is about 25 ft. west of Applegate Creek.

5/4/82

**219**

1/16 80 for Secs. 21 and 22  
Found - 2 1/2" I.P. with 1974 brass cap properly mkd. firmly set, projectin  
2" above ground, leaning slightly east. (M 49 - 69)  
20" D. fir stump, N.13°E., 42.9 ft. (Rec. 43.8 ft.) with scribe  
marks "1/16 80 S22 BT" and brass washer stamped "RLS 536" visible  
on partly healed double blaze.  
A roothole, N.25°W., 60.7 ft. (Rec. 65.5 ft.) with 18" D. fir  
stump alongside with scribe marks "1/16 80 S21" and brass  
washer visible on partly healed double blaze.  
New BT's- 5" chinquapin, N.26 3/4°E., 38.7 ft. marked "1/16 80 S22 CS BT" on  
double blaze.  
9" chinquapin, S.13 3/4°W., 45.8 ft. mkd. "1/16 80 S21 CS BT" on  
double blaze.  
Reset ft. steel fence post 3 ft. south with USFS signs #54-2  
and #54-9 attached.

Corner is in USFS clearcut about 80 ft. east of USFS Rd. #3240.

4/26/82

**220**

Corner #16 for H.E.S. #186  
Found - 1 1/2" I.P. with 1969 county brass cap properly mkd., firmly set,  
projecting 4" above 2 ft. diam. mound of stone. Ren. #145  
50" D. fir stump, S.70 3/4°E., 25.7 ft. with fragmentary scribe  
marks visible on previously opened blaze. (Original)  
18" W. fir, N.43°E., 17.5 ft. with healed blaze. Ren. #145  
12" D. fir, S.33°E., 13.9 ft. with healed blaze. Ren. #145  
Corner #15, H.E.S. #186, bears S.77°W., 85.7 ft. (Rec. 86.5 ft.)  
Set - 6 ft. steel fence post, S.77°W., 1.4 ft. with U.S.F.S. sign  
#54-4 attached.

Corner is about 120 ft. east of USFS Rd. #3231 at Rock Quarry.

4/28/82

**221**

Corner #14 for H.E.S. #186  
Found - 1 1/2" I.P. with 1969 county brass cap, firmly set, projecting  
8" above ground. Ren. #143  
56" D. fir stump, S.31°15'W., 28.4 ft. with scribe marks "ES 186"  
visible on previously opened blaze. (original)  
16" D. fir N.66°E., 33.5 ft. with healed blaze. Ren. #143  
13" D. fir, S.5°W., 23.5 ft. with healed blaze. Ren. #143

New Accessory

E 1/16 for Secs. 21 and 28, bears N.88°W., 32.64 ft. which is a  
brass cap set by Baughman, RLS #536 in 1975.

Corner lies about 40 ft. east of USFS Rd. #3231 and 80 ft. west of  
Applegate Creek.

4/20/82

Leonard Herzstein, U. S. Forest Service  
Jim Landrum - Jim Hamilton  
April - May 1982  
C.S. 61/32