

Douglas County Surveyor's Record of  
Government Corners Renewed

T 32 T. S. R 3 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

222

Leonard Herzstein  
U.S.F.S.  
Jim Landrum  
June 10, 1982  
C.S. 61/32

Corner #5, H.E.S. #186  
Found - 1969 County brass cap properly mkd., firmly set, projecting 12" above ground. Ren. #137  
Orig. 22" D. fir, S.54°45'W., 15.2 ft. with healed blaze.  
Orig. D. Fir, root crown, size indeterminate, N.42°40'W., 1 ft. with no marks visible.  
1969, 14" D. fir, S.15°E., 24.5 ft. with healed blaze.  
Set - Add 2 ft. diam. mound of stone, I.P. now projects 6" above mound of stone.

6/10/82

223

Gerald V. Nygren  
L.S. #1035  
1988  
C.S. 63/69

April 11

Section Corner for Secs. 15 and 16 only.  
Found - 1" iron pipe with 2½" 1969 County brass cap extended 10" above ground. Ren. #75  
20" snag bears N.64°W., 13.2 ft. (blaze healed) Orig.  
18" D. fir stump bears N.50°E., 9.2 ft. (blaze healed) Orig.  
20" D. fir stump bears S.37°W., 9.2 ft. (visible scribe) Ren. #75  
14" snag bears N.02°30'E., 97.7 ft. (visible scribe) Ren. #177  
New BTs - 6" D. fir bears N.53°W., 52.7 ft. scribed "X" in small upper blaze and "BT" in small lower blaze. A ½" brass washer is nailed flush to lower blaze.  
27" D. fir bears N.01°E., 107.2 ft. scribed "T32S R3W S15 BT" with brass washer nailed flush to lower end of blaze.

4/11/88

224

(TYR in New System) FD OK By L. Herzstein 11/2007 CS 65/60 - SJ N 112° 27.9ft April 15

Center 1/4 Corner for Section 8  
Found - 2" alum. pipe with 2½" alum. cap extended 6" above ground and mkd. by RLS 601. Ren. #194  
6" D. fir stob bears S.77°10' E., 39.7 ft. (visible scribe)  
7" D. fir bears N.16°35'W., 26.6 ft. (blaze healed.)  
New BT - 8" madrone bears N.72°W., 14.9 ft. bark scribed "C 1/4 S8 BT".  
A ½" brass washer is nailed flush to lower end of scribing.

225

Jackson County Surveyors Office  
Edward McGinty, County Surveyor  
C.S. 63/82  
Oct. 4, 1988

1/4 Corner for Sections 30 and 31  
Found - 1969 Doug. Co. Surveyors brass cap on 1" galv. I.P. projecting 8" above ground. Ren. #82  
The original 18x10x8 in. stone mkd. with "X" on top and "¼" on the side is found alongside corner.  
Orig. 1913 BT, sawed Fir stump, 24 ins. dia. with healed blazes, bears S.87°E., 32.44 ft. (Rec. 34.32 ft)  
Orig. 1913 BT, Sawed fir stump, 42" dia. containing scribe marks including "¼" in partially exposed face bears N.34°45'W., 12.82' (Rec. N.33°W., 12.54 ft.)  
32" D. fir containing scribe marks in axed into upper face bears N.7°E., 57.26 ft. to center of tree at upper face. (Rec. 58.9')  
Ren. No. 82  
38" D. fir with healed blazes bears N.78°E., 37.71 ft. to center of tree at lower blaze. (Rec. N.81°E., 38.6 ft.) Ren. #82  
New BT - 11" D. fir bears S.6°15'W., 5.0 ft. to center of tree at lower blaze.  
Corner lies in re-prod. area, 15 ft. north of draw, c. S.28°W., and approx. 60 ft. S.60°W. of location marker on fir snag, alongside road.

226

Sept. 26, 1988

1/4 Corner for Sections 28 and 33.  
Found - 1969 Doug. Co. 2½" brass cap on 1" galv. I.P. projecting 12" above ground. Ren. #127  
Original 1913 16X9X8 in. stone mkd. "¼" found alongside.  
Orig. BT, a 40" D. fir with healed blazes bears record, N.10°E., 31.7 ft. to center of tree at base.  
Orig. BT, 82" D. fir with scribe marks visible in partly exposed lower face bears record S.50°W., 33.0 ft. to center of tree at lower blaze.  
New BT - 6" Hemlock bears S.29°E., 9.7 ft. to center of tree at lower blaze.  
Corner lies an estimated 120 ft. east of the East Fork of Applegate Creek and about 350 ft. west of location marker on 36" dia. fir alongside road c. N.5°E., and southeast.