

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 T. S. R 3 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97101

227

Section Corner for Secs. 28, 29, 32 and 33
Found - 1969 Doug. Co. Surveyors 2½" brass cap on 1" galv. I.P. projecting 12". Ren. #91
Orig. 18x8x6 in. (serpentine) stone mkd. with "X" on top and 1 and 4 grooves on adjacent sides, is found alongside corner.
Orig. 1913 BT, the center of partial stump remains of a tipped over (large) fir bears N.6°E., 48.18 ft. (Rec. N.3°E)
Orig. 1913 BT, Hemlock, 16" with healed blazes bears S.80°E., 21.87 ft. to center of tree, at lower blaze. (Rec. S.81°E., 23.10 ft.)
Orig. BT, Sawed fir stump, 48" with healed blazes bears S.76°W., 38.07 ft. to center. (Rec. 37.62 ft.)
Orig. BT, Sawed fir stump, 60" with healed upper blaze, bears N.47°W., 8.65 ft. to center. (Rec. 8.58 ft.)
1969 BT, 13" cedar with scribe marks visible in partly exposed face bears N.60°E., 17.0 ft. to center.
1969 BT, Hemlock, 15" diam. with scribe marks visible in partly healed blaze bears S.22°W., 14.0 ft. to center.
New BT - 11" D. fir bears N.20°W., 20.6 ft. to center of tree at lower blaze, scribed "CS" "BT".
Corner lies on east slope, about 800 ft. south of location marker on 12" dia. fir, located alongside road, c. N.75°E.

10/6/88

1/4 Corner for Sections 26 and 35
Found - Doug. Co. Surveyors brass cap on 1" galv. I.P. projecting 15". Ren. #112
The orig. 14x11x5 ins. stone, mkd. "¼" as recorded by Mensch in 1913 is fd. deposited alongside above described monument.
(Corner lies in area of recent forest fire and no trees are available, within a reasonable distance, for references. The original bearing trees, were felled (high stumped), prior to fire.
Set - Mound stones around corner and in the top center of found charred stumps set PK nail through bearing tree tag:
32" diam. fir stump, bears N.70°E., 11.25 ft. to center (Rec. 10.56)
34" diam. fir stump, bears S.20°W., 3.92 ft. to center. (Rec. S.18°W., 3.96 ft.)
Corner lies on (40%) northwest slope, 64 ft. south of creek, c. N.80°W and an estimated 500 ft. N.10°W., of small landing alongside road (curve around ridge) c. southeast and southwest.

228

229

Section corner for Sections 27, 26, 34 and 35
Found - 1969 Doug. Co. brass cap on 1" galv. I.P. projecting 12". Ren. #120
Original Stone, mkd. with cross on top, recorded by F. Mensch, in 1913, is found deposited (buried) alongside corner.
Orig. BT. sawed fir stump, 25" diam., containing scribe mks. bears N.18°E., 5.45 ft. to center. (Rec. N.14°E., 4.62 ft.)
Orig. BT, The center of rotted fir stump, 20" diam., bears record S.60°E., 17.16 ft.
Orig. BT, the middle of rotted fir stump remains, bears record S.45°W., 10.56 ft.
Orig. BT, rotted fir stump, 24 ins. diam., containing reverse impression of scribe mks. including "BT" bears N.40°30'W., 8.2 ft to center. (Rec. N.48°W., 7.26 ft.)
1969 BT, Hemlock, 12" diam., with scribe mks. visible in partially healed blaze bears N.69°E., 6.4 ft. (Rec. 5.9 ft.) Ren. No. 120
1969 BT, Hemlock, 10" diam., containing scribe mks. in partly exposed face bears S.66°E., 4.60 ft. (Rec. 4.40 ft.) Ren. No. 120
1969 BT, Hemlock, 11 ins. diam., with healed blaze, bears S.18°W., 18.3 ft. (Rec. 19.0 ft.) Ren. No. 120

The Northwest bearing tree is now gone. As there is no suitable tree in Section 27:

Set - A 5/8" x 24" rebar, 23" in the ground with yellow plastic cap mkd. "Jackson C.S.", located 6 ft. south of a 28" diam., Fir stump, bears N.1°18'W., 48.59 ft.

Corner lies at top of cut-bank, 8 ft. above and 30 ft. south of middle of road, C. S.50°W., and about 6 ft. south of location marker on original northeast BT (stump) alongside road.

Jackson County Surveyors Office
Edward McGinty
County Surveyor
Oct. 6, 1988
C.S. 63/82

Jackson County Surveyors Office
Edward McGinty County Surveyor
R. Frost, Tech. S. Beecher, Tech.
C.S. 63/82

October 24, 1988

October 20, 1988