

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 T. S. R 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

230

Section Corner for Sections 27, 28, 33 and 34

Found - Corner monument is fd. disturbed, apparently struck by logging equipment or log in tow. Fd. the 1x36 ins. flanged bottom pipe with attached brass cap set by Doug. Co. Surveyor, Ren. #114 dated 1969. Said monument has been nearly removed from the ground and bent. It lies horizontal and partially buried alongside the (buried) orig. 13x7x4 ins. granite stone, mkd. with cross on top and 1 & 3 grooves on adjacent sides.

From the following evidence:

Set - A 1x36 ins. galv. I.P. with 2 1/2 ins. diam. brass cap mkd:
T32S R3W 28|27 C.S. 1988.
33|34

From which orig. BTs mkd. by F. Mensch in 1913 found:

- Sawed fir stump, 36" diam. with healed lower blaze bears N.83°E., 32.0 ft. to center of stump, (Rec. 34.32 ft.)
- Sawed fir stump, 48" diam., bears S.82°E., 29.60 ft. to center. (Rec. 31.02 ft.)
- Cedar, 42" diam., with healed blazes, bears S.6 1/2°W., 67.1 ft. to center of tree at upper blaze. (Rec. S.7°W., 67.32 ft.)
- Sawed fir stump, 50" diam., bears record N.82°W., 10.56 ft. to center.

New BTs - 7" chinquapin bears N.17°E., 22.40 ft.

7" chinquapin bears S.52°E., 11.90 ft.

30" D. fir bears N.47°W., 27.90 ft.

New BTs mkd. "CS" "BT" and take measurements to center of trees at lower blaze.

Corner lies near top of west sloping ridge, an estimated 225 ft. west of location marker on large fir stump, alongside road curving southwest and northeast. (See also Jackson County project file 88-62)

231

Section corner for Sections 25, 26, 35, and 36

Found - OSBF 1968 brass cap on I.P. projecting 12" (leaning 25° southeast of vertical). Said brass cap is centered over a chiseled cross atop the (firmly set) 10x7x? ins. orig. stone fd. projecting 6". Orig. bearing trees recorded by F. Mensch in 1913 as follows:

- Burnt fir stump, 48" diam., bears N.55°46'E., 35.46 ft. to center. (Rec. N.55°E.)
- Burnt fir stump 45" diam., bears S.16°41'E., 7.50 ft. to center. (Rec. S.15°E., 6.60 ft.)
- Burnt fir stump 51" diam., bears S.35°05'W., 18.80 ft. to center. (Rec. S.35°W., 17.82 ft.)
- Burnt fir stump 66" diam., bears N.44°57'W., 39.45 ft. to center. (Rec. N.44°W., 37.62 ft.)

A BT mkd. on the above noted survey (OSBF), a cedar, now a burnt snag, 32" diam., bears S.5°49'E., 31.5 ft. (Rec. S.8 1/2°E., 31.6')

The above BTs were also reported by the Doug. Co. Surveyors Office on 1969 re-establishment, Ren. #113. BTs mkd. by the county surveyor fd:

- Burnt pine stump, 16" diam., bears N.21°E., 31.3 ft. to center (Rec. 31.5 ft.)
- Burnt fir snag, 7" diam., with healed blazes bears S.41°E., 15.90 ft. to center. (Rec. 16.2 ft.)
- Burnt fir stump 21" diam. bears S.69°39'W., 39.75 ft. to center (Rec. S.70°W., 40.2 ft.)

A bearing tree not of record (in Jackson County) a burnt fir snag, 7" diam., with nail through washer, stamped "CS 536" in lower burned face bears N.28°43'E., 10.45 ft. Ren. #178

As all trees within a reasonable distance of the corner have been destroyed by recent (1987) forest fire:

Set - 5/8" x 24" ins. rebars with yellow plastic caps mkd. "Jackson C.S.", 23 ins. in the ground except as noted:

- N.41°59'E., 12.15 ft.
- S.38°00'E., 9.05 ft.
- S.73°24'W., 122.45 ft. set 3" deep, 3 ft. south of metal fence post, with attached attention sign, located alongside road c. N.45°E.-S.45°W.
- N.37°23'W., 9.57 ft.

Corner lies on southeast slope, an estimated 160 ft. west of draw c. southeast and 3 ft. west of steel fence post with attention sign.

October 5, 1988

November 1, 1988

Jackson County Surveyor Office
Edward McGinty, County Surveyor
R. Frost, Tech. H. Durkee, Tech.
C.S. 63/82