

Douglas County Surveyor's Record of  
Government Corners Renewed

T 32

T. S.

R 3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

James Artman  
For: USFS  
Dec. 1990  
C.S. 63/124

Center 1/4 Corner for Section 3 236  
Found - 2" iron pipe with 3" brass cap 3" above ground. Ren. No. 158  
8" madrone N.9½°W., 20.6 ft. healed blazes  
10" knobcone pine S.60°E., 7.4 ft. (dead) scribes  
partially visible.  
New BT - 12" knobcone pine S.18°W., 12.4 ft. scribed "C 1/4 S 3  
BT" nailed alum. washer marked "Artman RLS 2268" flush  
to BT face.

12/90

Jim Artman LS #2268  
For: U.S.F.S.  
Jan. 1991  
C.S. 63/124

1/4 Corner for Sections 9 and 16 237  
Found - 1" iron pipe with a 2½" brass cap 12" above ground, granite  
stone alongside. Ren #'s 4 and 130  
40" cedar bears N.1°E., 14.5 ft. scribes partially visible  
7" pine (dead) bears S.54°E., 18.7ft. healed blazes.  
New BT - 12" D. fir bears S.77°W., 11.8 ft. scribed "1/4 S16 BT" with  
alum. washer marked "ARTMAN RLS 2268" nailed blush to BT  
face.

1/91

Richard Templin  
for: Williams &  
Jackson  
Oct. 1994  
M 121 - 13

Center 1/4 Cor. Sec. 4 238  
Set - 5/8" rebar mkd. "Templin LS 2359" in sandstone. on the edge  
of cow creek protruding 12"  
New Accessories -  
Alder, 12" dia., bears N.24 3/4°E., 30.6' scribed "C1S4"  
"BT"  
Alder, 8" dia., bears N.34½°W., 19.4' scribed "C1S4" "BT"  
5/8" rebar, mkd "Templin LS 2359", bears S.89°55'E., 116.47'

Stephen Barott  
3/2007  
M152-65  
C.S. File  
65/61-5 C & D

Cor. Secs. 1, 2, 11, & 12 239  
Found - 1½" dia. iron pipe with a 3" dia. brass cap  
monument mkd as shown on plat, protruding  
14" above ground. (Ren. 192)  
From which the following accessories:  
25" dia. Hemlock bears S.01°31'19"E., 91.3  
ft. with a healed double blaze.  
18" dia. Knobcone Pine fir bears N.12°45'43"E.  
549.7 ft, w/fragmentary scribing visible  
on partially healed blaze [rec 555.0 ft]  
42" dia. fir bears N.86°35'19"W., 204.5 ft  
with a healed double blaze.  
27" dia. fir bears S.03°25'26"E., 250.5 ft  
with a partially healed blaze.  
GPS Point DF-1 bears N.32°44'06"E., 508.40 ft.  
Corner lies on a gentle south slope and in a fence line,  
500 feet south of Cow Creek Road No. 36. National Forest  
property boundary marked West and South from corner.  
Sec. Cor 1, 2, 11, 12 GPS info: Used Trimble R8 GPS Receivers  
Latitude: 42°48'46.869"N  
Longitude: 123°00'47.383"W  
Elevation: 2237.1 ft.

1/4 Cor. Secs. 1 & 12 240  
Found - 1½" dia. iron pipe with a 3" dia. brass cap  
monument mkd as shown on plat, protruding  
12" above ground, in a mound of stone. (Ren #69)  
From which the following accessories:  
26" dia. fir bears N.84°58'04"E., 42.8 ft. with  
healed double blaze.  
19" dia. fir bears S.54°28'05"E., 93.6 ft. with  
healed double blaze.  
GPS Point DF-2 bears N.64°57'55"W., 412.33 ft. Corner lies  
41 feet south of Cow Creek Road No. 36.  
DF-2 Lat: 42°48'48.476"N Long: 123°00'17.014"W  
Elevation 2319.8 ft.