

**Douglas County Surveyor's Record of
Government Corners Renewed**

32

T. S.

3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91801

Kris DeGroot
For: USFS

Aug. 2007
C.S. 65/60-49

241

1/4 Cor. Secs. 20 & 29

Found - A 1½" dia. Galvanized iron post, firmly set, projected 16" above the ground with a 2½" dia. brass cap (properly) stamped. Ren 85
From which an original bearing tree:
A 31" D.Fir snag bears S.57°W., 19.1 ft. with a healed blaze.
And bearing trees by Powell in 1969:
A 11" Yew bears N.3°W., 39.7 ft. with scribe marks "0 CS BT" visible on a partially healed blaze. (Rec. N.3°W.)

New - A 9" D.Fir bears S.54°E. 12.3 ft scribed "¼ S29 BT"
Note - All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown and distances are measured to an aluminum nail in the root crown at the side and center of the tree. All bearing trees have a 6" red band painted around the tree and the blazed face painted red and Bearing Tree and USFS Land Survey Monument sign nailed to the tree.

Kris DeGroot
8/2007
For: USFS
C. 65/60-50

242

Center 1/4 Cor. Sec. 20

Found - A 2½" dia. aluminum post, firmly set, projecting 8" above the ground with a 2½" dia. aluminum cap (properly) stamped. (ren. #184)
From which bearing trees by Clark in 1980:
A 13" Hemlock bears S.76°10'W., 44.0 ft. with a healed double blaze. (Rec. S.76°10'W.)
A 14" Hemlock snag with broken top bears N.35°10'W., 49.4 ft. with scribe marks "T32S R3W C ¼ S20 BT" visible on a partially healed double blaze. (Rec. N.35°10'W.)

New - A 9" D.Fir bears S.66°E. 9.9 ft scribed "C ¼ S20BT"
Note - All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown and distances are measured to an aluminum nail in the root crown at the side and center of the tree. All bearing trees have a 6" red band painted around the tree and the blazed face painted red and Bearing Tree and USFS Land Survey Monument sign nailed to the tree.

Leonard Herzstein
USFS Aug/Sept 2007
M154-54
C.S. 65/61-12A-E

Ren #179
243

Section corner of sections 16 and 17

Found - A 1½" outside dia iron pipe, firmly set, projecting 14" above ground, with a 2½" dia. brass cap (properly) marked as shown. The cap is twisted 45° clockwise.
From which the remains of the orig bearing trees:
32" D.Fir, bears S.70°E., 6.6 ft, with healed double blaze. Marks on tree were destroyed by Mensch in 1913 & the tree was rescribed by Powell in 1969 (rec. 1969, S.71°E, 6.8 ft).
8" decayed W.Fir snag, bears N.40°W., 4.6 ft, with partially healed decayed double blaze (rec. 20", 4 links = 2.64 ft)
And bearing tree marked by Mensch in 1913:
10" W.Fir, bears N.43°E., 12.5 ft, with healed double blaze (rec. 19 links = 12.54 ft).
And bearing tree marked by Baughman in 1969:
18" D.Fir, bears N.68°W., 42.1 ft. with healed double blaze.