County Surveyor's Record, Douglas County, Oregon

T 32 S, R 4 W, WM.

CHAINS

¼ COR. BETWEEN SECS. 29-32 — 20

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX.

Found the stumps of the old B. T's.
40" Fir bearing N 9° E 95.7 ft. dist.
30" Fir bearing S 13½° E 87.1 ft. dist.
Set 1" I. Pipe for the corner and marked followin g B. T.
30" Fir bearing S 22° 20' E 129.9 ft. dist. — Fo. O.K. 5/5/70
24" Fir bearing N 19° 48' E 89.7 ft. dist. — C.S. 54/114 J.M.P.

¼ COR. ON THE EAST SIDE OF SEC. 18 — 21

RE-ESTABLISHED. SEE CORNER NO. 76

Set 1" I. Pipe halfway bet. Sec. cors.
~~20" Fir bearing S 15° 19' W 41.5 ft. dist.~~
30" Fir bearing N 51° 50' W 32.5 ft. dist.

¼ COR. BETWE. SECS. 20-29 — 22

Set 1" I. Pipe for the corner between(halfway) Sec. Cors.
12" Fir bearing N 50° E 32.4 ft. dist.
10" Alder bearing S 7° 23' E 31.6 ft. dist.

SEC. COR. 19-20-29-30 — 23

Found 3 old B. T's.
36" Fir bearing S 6° E 79.2 ft. dist.
20" Fir bearing S 14° W 93.0 ft. dist.
30" Cedar bearing N 58° W 69.3 ft. dist. - down.
Set 1¼" I. Pipe fob the corner and marked B. T.
4" Fir bearing N 11° 55' E 28.1 ft. dist.
4" Pine bearing N 83° 02' W 34.1 ft. dist.

SEC. COR. 20-21-28-29 — 24

O. B. T. 48" Fir bearing N 23° E 110.8 ft. dist.
Stump bearing S 33° E 58.7 ft. dist.
Stump bearing N 23° W 108.9 ft. dist.
Set 1¼" I. Pipe for the cor. marked following B. T.
5" Chinquapin bearing N 34° 33' W 22.3 ft. dist.
8" Fir bearing S 80° W 5.6 ft. dist.
4" Madrone bearinig N 9° 09' E 35.9 ft. dist.
5" Madrone bearing S 48° 04' E 21.5 ft. dist.

S EC. COR. 28-29-32 -33 — 25

Found O. B. T. 40" Fir bearing N 58° W 60.7 ft. dist.
Stump 36" Fir bearing S 13° W 13.8 ft. dist.
Stump 36" Fir bearing S 34° E 41.8 ft. dist.
Set 1" I. Pipe for the corner marked following B. T.
6" Fir bearing N 54° 33' W 25.5 ft. dist.
8" Madrona bearing N 9° 30' E 42.5 ft. dist.
10" Madrona bearing S 47° 40' E 29.0 ft. dist.
No tree available in Sec. 32.

SEC. COR. 16-17-20-21 — 26

Found 18" Madrona bearing N 26° E 26.0 ft. dist.
Set 1¼" I. Pipe for cor. marked following B. T.
8" Fir bearinng N 82° 45' E 51.2 ft. dist.
14" Fir bearing S 78° 34' E 38.7 ft. dist.
30" B. Oak bearing N 60° 45' W 91.1 ft. dist.
16" Fir bearing S 12° 20' W 44.9 ft. dist.

¼ COR. BET. SEC. 19-20 — 27

Found both B. T's. in good shape
Drove 1½" I. Pipe and marked the following B. T.
30" Fir bearing S 50° E 2.2 ft. dist.
30" Fir bearing S 23° W 6.1 ft. dist.

¼ COR. EAST SIDE SEC. 8 — 28

Set a 4" Fir post 4' long, firmly in the ground, scribed ¼ S 8 also crayoned mared 1543, from which
12" Fir bears N 33° W 32.4 ft., scribed ¼ S 8 B T.
~~42" Fir bears S 55° W 41.6 ft., scribed ¼ S 8 B T.~~

RE-ESTABLISHED. SEE CORNER NO. # 161

George J. Wenderoth - - Deputy County Surveyor

C.S. FILE No. 38/246

H. W. Laurence
Reg. Engineer
March 1949

File 40/174