

County Surveyor's Record, Douglas County, Oregon

T 32 S, R 4 W.

George J. Wenderoth - Deputy County Surveyor
Frank Loso - Wenderoth

Geo. J. Wenderoth - Deputy Co. Surveyor
F. Loso - Witness
April, 1950

Eng.-John H. Markham, Jr. - Wit.-Martin Perry
May 14, 1951

CHAINS

October 1948

July 1948

C.S. 40/246

CS 40/32

see also
rens #
83 & 35
T32-5

$\frac{1}{4}$ COR. BET. 18-19 29
Place by proportionate measurement, 1" I. P. #15A
Marked 12" Madrona S 33° W 15.8 ft.
28" Fir N 15° 30' E 28.0 ft.

$\frac{1}{4}$ COR. BET. SECS 32-33 30
Found both B. T's. in good shape. Rock for corner gone.
Bearings of B. T's. do not check so use measurements. REN #5
Drive 1" Iron Pipe for corner.
Mark 30" Fir, N 43° 05' E 16.5 ft.
30" Fir, S 89° 45' W 31.7 ft.

CLOSING CORNER. N. SIDE OF SECS. 19-20 31
Found one B. T. badly rotted.
Set 1" Iron Pipe for corner. 114
Mark 18" Fir N 86° 10' W 76.4 ft.
8" Hemlock S 28° E 45.0 ft.

SECTION CORNER 4-5 (T 32S) & 32-33 (T 31 S) 32
Found 48" Fir S 51° 15' E 84.5
30" B. Oak S 75° W 32.3
Drive 1" I. Pipe for Corner.
Scribe 14" Fir N 45° 15' W 33.1
10" Maple N 39° 25' E 50.3

SOUTH SECTION CORNER 4 & 5 33
Find 20" Cedar N 40° E 37.0
48" Fir N 45° W 28.4
Drive 1" Iron Pipe for Corner.

$\frac{1}{4}$ COR. BET. 4-5 34
Halfway between Sec. Cor. - 2677.4 ft.
Drive 1" I. Pipe for Corner.
Scribe 30" Pine N 2° 50' W 90.9
24" Pine N 33° 13' E 69.1

COR. to TWP. 31 and 32 S, RGE 4 and 5 W 35
Determined by O. B. T. 68
A Fir 54 in. diam. bears S 73° E, 26.0 ft. dist. O.B.T.
A Fir Stump (logged) 24 in. diam. bears N 67° E 21.0 ft. dist. O.B.T.
I marked on top of stump S 31, B.T.
A Fir 20 in. diam. bears S 63° W 38.0 ft. dist. O.B.T.
At corner point set $\frac{3}{4}$ " x 24" iron pipe and found original stone,
from which
A Fir 7 in. diam. bears N 82° E, 10.0 ft. dist. marked S 31, B.T.

S.W. COR. SEC. 6 36
Determined by O.B.T. 99
A B. O. 14 in. diam. bears S 31° E, 50.0 ft. dist. O.B.T.
At corner point found 12x12x14 stone and $\frac{3}{4}$ in. iron pipe from which
A Pine 5 in. diam. bears S 85° W 8.0 ft. dist. marked XXX B.T.
A Pine 12 in. diam. bears N 21° W 12.0 ft. dist. marked XXX B.T.
A B. O. 15 in. diam. bears N 83° E, 62.4 ft. dist. marked S 6, 2880
B.T.