

Douglas County Surveyor's Record of
Government Corners Renewed

32 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Geo. J. Wenderoth - Dep. County Sur
Witness - Frank Loso.
April, 1948.

$\frac{1}{4}$ corner between 16 and 17
Found 24 inch Fir S. $73^{\circ}45'$ E 19.1 feet
Oak stump S 83° W. 3.9 feet
Drive $1\frac{1}{2}$ inch iron pipe and mark a new B.T.
14 inch Pine S. $64^{\circ}35'$ W. 17.4 feet

37

Section corner 8, 9, 16 and 17
Find old B.T.
30 inch Fir N 87° E. 86.4 feet
30 inch Fir S 68° E 46.8 feet
30 inch Fir S 56° W 99.0 feet
Drive a 1 inch iron pipe and mark new B.T.
8 inch Madrona N $66^{\circ}45'$ W. 21.4 feet

38

FNO OK 11/90 M111-12

~~Section corner 23, 24, 25, and 26 - SHOULD BE IN T. 32S. R. 6W. 39
Set at intersection of corner lines.
Drove a $\frac{3}{4}$ inch iron pipe 30 inches long, 24 inches into the
ground, from which:
A Y. pine 32 inches in diameter bears N. 56° E., 14.2 feet mkd. S 24 BT.
A Y. pine 12 inches in diameter bears S. 48° E., 3.6 feet mkd. S 25 BT.
A B. oak 13 inches in diameter bears S. 46° W., 15.0 feet mkd. S 26 BT.~~

~~$\frac{1}{4}$ section corner between 24 and 25
Drove a $\frac{3}{4}$ inch pipe 30 inches long, 24 inches into the ground,
From which:
A B. oak 26 inches in diameter bears N. 50° E., 108.9 feet mkd.
 $\frac{1}{4}$ S 24 BT.
A B. oak 32 inches diameter bears S. 71° W., 230.8 feet mkd.
 $\frac{1}{4}$ S 25 BT.
A mound of stone bears South at 11' from this set $\frac{1}{4}$ corner.~~

40

Set $\frac{1}{16}$ corner West of $\frac{1}{4}$ corner section 7 and 18
Set 1 inch I. Bar.
5 inch chinipin S. $86^{\circ}14'$ East, 34.5 feet.
8 inch Madrona N. $13^{\circ}42'$ East, 20.2 feet.

41

Corner of sections 21, 22, 27, and 28
Determined at the record bearing and distance from the original
NE., SW., and NW. bearing trees and record bearing from the
Original SE. bearing tree.
Set and iron pipe, 3 feet long, 2 inches diameter, 28 inches in the ground
mkd. RS33;
From which the original bearing trees:
A sugar pine, 48 inches diameter, bears N. 64° E., 25 lks. dist.,
mkd. T32S R4W S22 CS BT.
A fir stump, 26 inches diameter, bears S. 10° E., 61 lks. dist.,
with no marks remaining.
A fir stump, 34 inches diameter, bears S. 9° W., 26 lks. dist., with
no marks remaining.
A fir stump, 52 inches diameter, bears N. 60° W., 58 lks. dist.,
with no marks remaining.
And a bearing tree marked by the county surveyor:
A Douglas fir, 36 inches diameter, bears S. $30\frac{1}{2}^{\circ}$ E., 99 lks. dist.,
mkd. T32S R4 W S27 CS BT.

42

H. W. Lawrence - Dep. County Sur
Witness - Fred H. Daugherty.
Dec. 21, 1951

Geo. J. Wenderoth
Dep County Surveyor.
Sur. for Fred H. Daugherty.
Drawer 45. Env. 136.

Norman D. Price
Survey executed May 26 - August 18, 1954
Done for the Dollar and Patterson
Lumber Co. Inc.
County Surveyor's File 41/302.