

Douglas County Surveyor's Record of  
Government Corners Renewed

32 T. S. 4 R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 97106

43

$\frac{1}{4}$  section corner of sections 15 and 22  
Monumented with the almost disintegrated remains of a wooden stake  
mkd.  $\frac{1}{4}$  S15 on N. and  $\frac{1}{4}$  S22 on S. face;  
From which the only extant original bearing tree:  
A sugar pine, 28 inches diameter, bears N.  $46\frac{1}{2}^{\circ}$ E., 108 lks. dist.  
with the scribe marks BT uncoverd.  
Set an iron pipe, 3 feet long,  $1\frac{1}{2}$  inches diameter, 28 inches in the  
ground, mkd. RS33 and deposit the remains of wooden stake at base of pipe.

44

Corner of sections 15, 16, 21, and 22.  
Determined at the record bearing and distance from each of the  
original bearing trees:  
Set an iron pipe 3 feet long, 2 inches diameter, 28 inches in the  
ground, mkd. RS33;  
From which the original bearing trees:  
A madrona, 18 inches diameter, bears N.  $70^{\circ}$ E., 46 lks. dist. mkd.  
T32S R4W S15 with other blaze healed.  
A Douglas fir, 30 inches diameter, bears S.  $60^{\circ}$ E., 67 lks. dist., with  
blaze healed.  
A Douglas fir, 27 inches diameter, bears S.  $34^{\circ}$ W., 30 lks. dist., with  
blaze healed.  
A Douglas Fir stump, 16 inches diameter, bears N.  $63^{\circ}$ W., 33 lks.  
dist., on which no marks remain.

Section corner to sections 1 & 2, T 32 S, R 4 W., and Secs. 35 & 36,  
T 31 S, R 4 W.  
Found 4 old B. Ts.  
24" Fir bearing N.  $32^{\circ}10'E.$ , 30.3 ft. dist.  
16" Madrona bearing N.  $24^{\circ}54'W.$ , 20.9 ft. dist.  
14" Fir bearing S.  $30^{\circ}50'W.$ , 13.2 feet dist.  
10" Madrona bearing S.  $5^{\circ}45'E.$ , 8.6 feet dist.  
Drove a 1" I. Pipe for the corner.  
Marked a 14" Fir bearing S.  $14^{\circ}30'W.$ , 20.5 ft. dist.

45

$\frac{1}{4}$  sec. corner to sec. 1, T 32 S, R 4 W., and Sec. 36, T 31 S, R 4 W.  
I. Bar.  
48" Cedar, S.  $57^{\circ}09'W.$ , 170.0  
18" Fir, N.  $48^{\circ}E.$ , 130.4

46

Township corner to sec. 1, T 32 S, R 4 W., Sec. 6, T 32 S, R 3 W.,  
Sec. 31, T 31 S, R 3 W., and Sec. 36, T 31 S, R 4 W.  
 $1\frac{1}{4}$  inch iron pipe.  
8" Thorn, S.  $77^{\circ}E.$ , 48.8 feet.  
10" Hemlock, S.  $33^{\circ}40'W.$ , 185.5 feet.  
24" Fir, N.  $12^{\circ}20'W.$ , 142.0 feet.

47

$\frac{1}{4}$  sec. corner to sec. 1, T 32 S, R 4 W., and sec. 6, T 32 S, R 3 W.  
1 inch iron pipe.  
20 inch Fir, N.  $68^{\circ}E.$ , 5.3 ft.  
20 inch Fir, N.  $48^{\circ}W.$ , 12.0 ft.

48

Section corner to secs. 1 & 12, T 32 S, R 4 W., and Secs. 6 & 7, T 32 S,  
R 3 W.  
1 inch iron pipe.  
38" Fir, N.  $22^{\circ}E.$ , 13.2 ft.  
30" Fir, S.  $8^{\circ}E.$ , 141.2 ft.  
42" Fir, S.  $8^{\circ}30'W.$ , 109.5 ft.  
36" Fir, N.  $18^{\circ}W.$ , 71.3 ft.

49

Norman D. Price  
Survey executed May 26 - August 18, 1954.  
Done for Dollar and Patterson Lumber Co. Inc.  
County Surveyor's File 41/302.

George Wenderoth,  
Dep. Co. Surveyor  
Dec., 1947  
C S 42/134

George J. Wenderoth, Deputy County Surveyor  
Work done for H. D. Hauck  
May, 1955.  
See C. S. File No. 46/134.

RE-NEWED, SEE CORNER NO. #94

RE-NEWED, SEE CORNER NO. #91

RE-NEWED, SEE CORNER NO. #95

RE-NEWED, SEE CORNER NO. 144