

Douglas County Surveyor's Record of
Government Corners Renewed

32 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Geo. J. Wenderoth
August 31, 1955.
C. S. File No. 47/8.

North Closing corner to sections 11 and 12.
Found Stump - 24" Fir, S. 58°W., 49.5 feet, scribe showing.
Set 1" Iron Pipe for corner.
No trees available in Sec. 12 and Deadfall hides trees in Sec. 11 - So
mark trees in Sec. 2.
A 26" Fir, N. 40° 49' W., 49.0 feet.
A 26" Fir, N. 41° 55' E., 58.8 feet.
Corner is in bottom of Gulch.

50

Richard L. Templin Jr., partial sub.
of Sec. 24, T 32 S., R 5 W., for
Sierra Land Co.
April 30, 1956.
C. S. File No. 42/133.

Section corner to secs. 18 & 19, T 32 S., R 4 W., and secs. 13 & 24,
T 32 S., R 5 W.
Found 1 inch iron rod. REN. #14
Found stump of 20 inch Fir, S. 45°W., 34 lks. FDOIC PER ARTMAN
3/16/90 m 109-66
Found County Survey B.T.s:
8 inch Chinquapin, N. 55°W., 8.2 feet.
12 inch Fir, S. 22°E., 13.5 feet. (Blaze healed).
Scribed new B. T.:
8 inch Fir, N. 09°W., 8.6 feet, marked S 13, RE 3024 B. T.

51

Section corner to secs. ~~17 & 20, T 32 S., R 4 W.~~, and secs. 24 and 25,
T 32 S., R 5 W.
Found two orig. B.T.s:
10 inch Madrone, S. 11°W., 98 lks. - no scribing.
10 inch Madrone, N. 07°W., 58 lks. - no scribing.
Found 54 inch Fir line tree with notches, S. 257 feet.
Scribed new B.T.:
34 inch Fir, South 40.1 feet, mkd. S 25 RE 3024 BT.

52

George Wenderoth
1953
C. S. File No. 45/136.

Section corner to secs. 7 & 18, T32S, R4W., and secs. 12 & 13, T32S, R5W.
1/2 inch iron pipe. REN. #2
From which:
10 Fir, S. 60° 35' E., 60.3 feet.
9 inch Live Oak, N. 4° 06' E., 105.8 feet.

53

G. G. Stewart, Deputy County Surveyor
May, 1922.
C. S. File No. - Vol. 3, P. 121
M 3 - 32.

1/4 corner to secs. 7 and 18.
Set stake with Brick for corner. Found two O. B. Ts.
Marked:
An 18 inch Pine, S. 27°W., 20.0 feet. (O. B. T.)
An 18 inch Pine, N. 43°E., 45.6 feet.

54

1/4 corner to secs. 6 and 7.
Set an Iron Pipe at location of original stake as pointed
out and agreed upon in writing by Robert Payne, B. Neff,
H. J. Wilson, K. H. Cooper and G. A. Pickett. REN. #7
Marked:
A 12 inch Cedar, S. 51 1/2°W., 9.0 feet.
A 10 inch Cedar, N. 7 1/2°W., 178.7 feet.
No O. B. T.s to be found.

55

Center 1/4 corner to section 7.
Set an iron pipe at intersection of centerlines of section.
Marked:
A 36 inch Fir, S. 7°E., 64.0 feet.
A 6 inch Fir, S. 40°W., 62.0 feet.

56

Section corner to secs. 7 & 18, T 32 S, R 4 W., and secs. 12 & 13, T32S, R5W.
Set an iron bar from 2 O. B. T. stumps. Others gone. REN. #2
Marked:
24 inch Fir, N. 16°E., 163.2 feet.
30 inch Fir, N. 71°E., 216.0 feet.
No other trees available.

57

RENEWED, SEE CORNER NO. 66

RENEWED, SEE CORNER NO. 123

RENEWED, SEE CORNER NO. 97

RENEWED, SEE CORNER NO. 3

RENEWED, SEE CORNER NO. 65

RENEWED, SEE CORNER NO. 53 + 97