

Douglas County Surveyor's Record of
Government Corners Renewed

32

T. S.

4

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21811

Section corner to secs. 6 & 7, T32S, R4W., and secs. 1 & 12, T32S, R5W.
Set an iron pipe from 2 O. B. T.s. Others gone.

58

Marked:

- A 30 inch Pine, N. 51°E., 26.8 feet. (O. B. T.)
- A 10 inch B. O., S. 30°E., 47.4 feet.
- A 20 inch B. O., N. 5°W., 95.2 feet.
- An 18 inch B. O., S. 44°W., 121.0 feet.

RENEWED, SEE CORNER NO. 36

G. G. Stewart, Dep. Co. Surveyor
May, 1922
See Vol. 3, P. 121.

1/4 corner to sec. 7, T32S, R4W., and sec. 12, T32S, R5W.

59

Set an iron bar from stump of O. B. T.

Marked:

- A 12" Fir, N. 89°W., 218.0 feet.
- A 10" Fir, N. 56°E., 143.0 feet.

RENEWED, SEE CORNER NO. 67

Section corner to secs. 3 & 4, T 32 S, R 4 W., and secs. 33 & 34, T31S, R4W.
At corner point set 1" x 24" iron pipe.

60

All of the following are O. B. T.s which I remarked:

- A Fir 20 in. diam., bears N. 44°W., 27.0 feet dist.
- An Ash, 9 in. diam., bears S. 80°W., 29.3 feet dist.
- A Fir, 10 in. diam., bears S. 48°E., 4.6 feet dist.
- A Fir, 40 in. diam., bears East 21.5 ft. dist. This O. B. T. was already bark scribed S 34, R 4 W, W 31 S, B. T. The notes call for this tree to bear N. 80°E., -the distance was correct.

RENEWED, SEE CORNER NO. 77

Eng. - John Markham
Apr. 1, 1951.
C.S. 40/232

1/4 Corner of Sections 14 and 15.

61

Found: Stone marker and scribed the following new W.T.: 28 inch D. Fir
S 78°E 21.0 feet dist mared 1/2 S 14 BT RE3024.

Section Corner common to Sections 10, 11, 14 and 15. - See Ren. # 70

Set a mound of stone at corner from which: 5 inch D. Fir bears S 24°W 10.9 Ft dist. mkd. S15BT RE3024: 7 inch D. Fir bears N 24°W 32.0 ft. dist. marked # 70 S10BT RE3024: 6 inch D. Fir bears N 26°E 44.0 ft. dist. mkd. S11BT RE3024: 10 inch D. Fir bears S 3°E 54.4 ft. dist. mkd. S14BT RE3024.

Corner of Sections 14, 15, 23 and 24:

62

Set a Quartz Stone 18"x10"x7" - 10" in the ground and mounded around with smaller quartz stones from which:

- 26 inch D. Fir snag bears N 32°E 17.8 ft. dist., blaze healed.
- 30 inch D. Fir bears S 30°E 37.6 ft. dist., blaze healed.
- 30 inch D. Fir snag bears S 51°W 11.2 ft. dist., blaze healed.
- 30 inch D. Fir snag bears N 45°W 45.6 ft. dist., scribe visible.

This corner located in a recent burn & no green trees available to scribe

1/4 Corner of Sections 14 and 23.

63

Monument with a slate stone 12x10x5 inches marked 1/4 on the north face from which: 40 inch D. Fir bears N 16°W 14.5 ft. distant, blaze healed.
16 inch D. Fir bears S 52°W 22.4 ft distant, blaze healed.

Corner Common to Sections 11, 12, 13, and 14:

64

Monument with a basalt stone 10x7x7 inches 5 inches in ground from which:
32 inch D. Fir sang bears N 7°E 43.6 ft. dist. blaze evident.
24 inch D. Fir bears S 46°E 42.3 ft. distant, scribing visible.
40 inch D. Fir snag bears S 40°W 95.1 ft. distant blaze evident.
28 inch B. Fir bears N 70°W 67.6 ft. distant blaze healed.

Scribe the following new witness trees:

- 6 inch D. Fir bears N 40°30'E 20.3 ft. dist. marked S 12 BT RE3024.
- 12 inch D. Fir bears S 25°55'W 62.0 ft. dist. marked S 14 BT RE3024.

1/4 Section Corner to Sections 6 & 7.

65

Found - 1 1/2" I.P. in N. S. Fence Line. sec # 7+55

The S. W. BT. gone. The N. 7 1/2°W. BT. now 36" Cedar, checks for bearing & distance, shows old blaze. I do not open, N. 25°E.

- Blaze & Scribe: 10" Pine 1/4 S6 CS BT 21.7 ft. N. 25°E.
- 20" Cedar 1/4 S7 CS BT S. 51°W. 9.7 ft. Dec. 18, 1956

Renew Closing Corner to Sections 2, 1, & 12.

Found - Orig. BT. 6" Fir now 12" N. 27°E. I do not open shows old blaze.

Orig. 14" Fir BT. now, face open scribing visible. BTs. check.

Set Brass Cap at corner marked Closing Corner S2/S1 T32S R4W County Surveyor's Office, 1957

From Which: S12

I Scribe 12" Fir N. 70°E. 24.5 ft. S1 T32S R4W CS BT.

SEE GOV'T. NOTES

James W. Byron
For Douglas County Road Dept.
Dec. 1956-Feb. 1957
Road Drawer 48 / Rd. #36

65A