

Douglas County Surveyor's Record of
Government Corners Renewed

32 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Eyrone
Douglas County Road Dept.
Dec. 1956 - Feb. 1957
Road Drawer 48/Rd. #36

Closing Corner to Section 2, 11, & 12. 66
Found - 1" I.P. at corner. N.W. BT. as scribed by G. Wenderoth checks
for bearing & distance - good condition. REN.#50 *SEE GOV'T. NOTES*
N.E. BT. down.
Set Brass Cap at corner alongisde I.P. marked S2 T32S R4W County Surv.
(See sketch in file) Clos. Cor. S11|S12 Office, 1957
From Which: 6" Hemlock bears S.19°W. 29.1 ft. scribed S11 T32S R4W CS BT.
Feb. 5, 1957

#149
67
 $\frac{1}{4}$ Section Corner to Sections 7 & 12.
Found - 2" X $\frac{3}{4}$ " X 12" I. Bar at base of Ewewood Post, check bearing &
distance to 18" Fir as renewed by Stewart, 1922. BT. has been
opened several years ago. No scribing visible at this time.
The N.W. BT. is gone. REN.#59
Set Brass Cap alongside I. Bar marked 12/7 T32S County Surveyor's
R5W R4W. Office, 1956
From Which: 12" Live Oak bears N.85°E. scribed $\frac{1}{4}$ S7 CS BT. *13, 1956*
I rescribed Stewart's N.56°E. 143.0 ft. BT. $\frac{1}{4}$ S7 CS BT.
Dec. 13, 1956

Richard L. Templin, Jr.
Sept. 1958
C.S. File No. 42/389

Township Corner Common to Twps. T32/R4; T32/R5; T31/R4; T31/R5 68
Found - $\frac{3}{4}$ " Iron Pipe (unmarked). REN.#35
24" Fir S.62 $\frac{3}{4}$ °W. 39.5 ft., blaze healed.
50" Fir Stump S.74 $\frac{1}{2}$ °E. 25.5 ft. scribing visible.
40" Fir Stump N.65°E. 20.0 ft. blaze healed.
16" Fir Stump N.16°W. 54.0 ft., blaze healed.
10" Fir N.79 $\frac{1}{2}$ °E. 9.8 ft. scribing visible.
Scribed $\frac{1}{4}$ 6" Cedar N.27°W. 16.6 ft. mkd. S36 RE3024 BT.

#147 69
 $\frac{1}{4}$ Sec. Cor. common to Sec. 6 T32S, R4W, & Sec. 10, T32S, R5W.
Found - 12" Fir N.54°W. 52 lks., scribing visible.
Set: $\frac{3}{4}$ " IRON PIPE mkd. RE3024 scribed: 22" Fir S.15 $\frac{1}{2}$ °W 44.0 ft., mkd.
 $\frac{1}{4}$ S1 RE3024 BT.

Richard L. Templin, Jr.
For Southern Ore. Plywood
May 10, 1956
C.S. File No. 42/159

Section Corner Common to Sections 10, 11, 14, and 15. 70
The locus of this corner was determined from the intersection
of original blazed section lines ascertained by ring count and
from the rotted stumps of the four original bearing trees with
no marks discernable:
Rotted Stump, 24" D. Fir bears N.31°E. 50.5 ft.
Rotted Stump, 24" D. Fir bears S.72°E. 32.0 ft.
Rotted Stump, 20" D. Fir bears S.56°W. 45.1 ft.
Rotted Stump, 20" D. Fir bears N. 5°W. 72.4 ft.
I was unable to find the rock after a diligent search.
I placed a mound of stone to monument the corner from which bears
the following new witness trees:
5" D. Fir bears S.24°W. 10.9 ft. mkd. S15BTRE3024
7" D. Fir bears N.24°W. 32.0 ft. mkd. S 10BTRE3024
6" D. Fir bears N.26°E. 44.0 ft. mkd. S11BTRE3024
10" D. Fir bears S. 3°E. 54.4 ft. mkd. S14 BTRE3024 *See Also #61A*

$\frac{1}{4}$ Corner of Sections 11 & 14. 71
Which is a Rock 12 x 8 x 8 inches Mkd: $\frac{1}{4}$ on north face from
which the following original witness trees bear:
38" D. Fir bears N.7 $\frac{1}{2}$ °E. 32.4 ft.
56" D. Fir bears S.57°E. 13.9 ft.

G. Robert Lecklider
July 30, 1959
Map. File No.
M 15 - 31

#134 72
 $\frac{1}{4}$ Section Corner to Sections 2 & 11.
Found - 56" I. Cedar - N.20°W. - 31 lks.
Set - 16" Fir - N.75°E. - 16.1 ft.
13" Fir - N.46°W. - 11.0 ft.

$\frac{1}{4}$ Section Corner to Sections 1 & 2. 73
Found - 6" Yew - S.50°E. - 37 lks.
Set - $\frac{1}{2}$ " Rod and 24" Fir - S.42°W. - 57.1 ft.
6" Yew - S.70°E. - 34.3 ft.