

Douglas County Surveyor's Record of
Government Corners Renewed

32

T. S.

4

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

Center $\frac{1}{4}$ Corner of Section 2.

Set - $\frac{1}{2}$ " Rod
10" Fir - S.86°E. - 37.7 ft.
30" Fir - N.38°E. - 38.3 ft.

74

G. Robert Lecklider
Done for Pacific Plywood
July 30, 1959
Map File No. M 15 - 31

$\frac{1}{4}$ Section Corner to Sections 2 & 3.

Original Corner Not Found.

Set - $\frac{1}{2}$ " Rod
24" Fir - S.30°E. - 37.2 ft.
32" Fir - N.46°W. - 39.0 ft.

75

$\frac{1}{4}$ Corner East Side Section 18.

Found Stumps of both Witness Trees as renewed before and

1" Iron Pipe. REN. #21

Put in new Trees as follows:

10" Fir N.12°49'W. 69.1 ft.
24" Cedar S.48°16'W. 155.1 ft.

FDOK PER ARTMAN
M109-66 3/16/90

76

George J.
Wenderoth, Dep.
June 18, 1960
C.S. File No.
52/29

Sec. Cor. to Secs. 3 & 4, 32-4W. & Secs. 33 & 34, T31-4W.

Found - 1" Iron Pipe with Brass Cap. REN. #60

20" Fir S.46°30'E. good, 4.6 ft.
14" Ash S.81°20'W. good, 29.3 ft.
24" Fir N.39°45'W. 27.0 ft. Blown down, no tree available.
Scribed New BT: 12" Cedar N.48°50'E. 15.9 ft.
Found Stump of Orig, now 40" Fir N.89°15'E. 21.5 ft.

77

Geo. J.
Wenderoth
Dec. 5, 1962
C.S. File
No. 52/29

Section Corner to Sections 5 - 6 - 7 - 8.

Set - 1" I. Pipe.

Found - 20" Fir N.40°E. 5.9 ft.
20" Fir S.30°W. 7.2 ft.

78

George J.
Wenderoth
M 24 - 70

Section Corner to Sections 5 - 6 - 7 - 8.

Found - 1" Iron Pipe from which: 24" D.Fir, Orig. BT. with scribes
visible bears S.30°W. 7.2 ft.

22" D.Fir, Orig. BT. with old face, bears N.40°E. 5.9 ft.

New BT's: 20" D.Fir, bears N.24°W. 20.6 ft. scribed T32S R4W S6 BT.

24" D.Fir bears S.60°E. 33.0 ft. scribed T32S R4W BT.

79

Bruce A. Shaner
For Aggson & Harrison
June 1963
Map File RM 1 - 37.

$\frac{1}{4}$ Corner to Sections 5 and 8.

Set - $\frac{5}{8}$ " x 36" Rod by proportional measurement, from which:
40" D.Fir bears S.69°W. 50.4 ft. scribed $\frac{1}{4}$ S S8 T32S R4W.
38" D.Fir bears N.8°W. 59.0 ft. scribed $\frac{1}{4}$ S S5 T32S R4W BT.

80

Center $\frac{1}{4}$ Corner to Section 5.

Set - $\frac{5}{8}$ " x 36" Iron Rod from which a:
14" D.Fir bears S.7°W. 27.7 ft. scribed "C $\frac{1}{2}$ S5 BT".
18" D.Fir bears N.47°W. 68.5 ft. scribed "C $\frac{1}{4}$ S5 BT".

81

88

$\frac{1}{4}$ Cor. Common to Sec. 13, T32-4W. & Sec. 18, T32-3W.

Area of this corner was logged and original
stone lost. I found both Fir Bearing Trees, which
are now stumps, with faces grown over. I chopped
out both faces and exposed original scribing.
Replaced - Original Stone with Iron Pipe.

82

John Madding
By Bate Plywood
C. S. File
No. 51/270

November 22, 1963