Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

93

¼ Corner to Sec. 5, T32-4 and Sec. 32, T31-4.
Found - I. Pipe at ¼ Corner, See Information on Map RM 1 - 37.
5" Oak, now 8", S. 53° E. (not S.30°E.) 7.9 ft., scribing visible.
10" Pine, now 12", N.66°W. (not N.54½°W.) 19.4 ft. Tree had been opened & pitched over.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 (alongside I.P.) — ¼ S 32 / S 5 — T31S / T32W R4W
Set this corner by I.Pipe & 2 correct distances.
New BT's: 14" D. Fir N. 25° W. 26.8 ft. scribed ¼ S32 CS BT.
15" Pine S. 41° W. 46.6 ft. scribed ¼ S 5 CS BT.

94

Sec. Cor. to Secs. 2 & 1, T32-4 and Sec. 35 & 36, T31-4.
Found - Iron Pipe at corner, See Ren. #. 45
Orig. 24" Fir N. 32° 10' E. 30.3 ft., shows good scar.
" 16", now 19", Laurel N.24°54'W. 20.9 ft., scribe visible.
" 14", now 17" Fir S.30°50'W. 13.2 ft. Open, no scribing.
" 10" Laurel S.5°45'E. 8.6 ft., very rotten.
14" Fir, down, S. 25° E. 22.7 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 (Alongside I.P.) — T31S / T32S — S 35 | S 36 / S 2 | S 1 — R4W
Rescribed: 19" Laurel N.24°54'W. 20.9 ft. scribed T31S R4W S35 CS BT.
New BT's: 8" Fir S. 46° W. 18.7 ft. scribed T32S R4W S 2 CS BT.
8" Laurel S. 27° E. 29.9 ft. scribed T32S R4W S 1 CS BT.

John M. Powell
Frank Jones and Joe Brady
February 1966
C. S. File No. 54/20

95

Township Corner, T. 31 & 32 S., Ranges 3 and 4 West.
Found - Iron Pipe at Corner which was out of ground, See Ren. #. 47
8" Thorn, now 18", S. 77° E. 48.8 ft. scribe visible "S6CS BT".
10" Hemlock, now 12", S. 33½°W. 185.5 ft., scribe visible "BT".
24" Fir Stump N. 12° W. 142.0 ft.
Set - Brass Cap at Twp. Cor. Mkd: County Surveyor's Office, 1966 — T 31 S — R 4 W — S 36 | S 31 / S 1 | S 6 — R 3 W — T 32 S
New BT's: 6" D. Fir N. 2° E. 120.3 ft. scribed S31 CS BT.
11" Hemlock S. 75° E. 62.9 ft. scribed T32S R3W S6 CS BT.
Note - Best way to reach corner is to wade Cow Creek in the summer.

FD OK BY R. BROWN 4-93 M112-72

John Powell & Crew
Jan. 13, 1966
C.S. File No. 52/63

96

Wit. Cor. ¼ Corner to Sec. 4, T32-4W. & Sec. 33, T31-4W.
Found - No trace of Brass Cap set by Gov't.
22" Fir, now 19", N. 9° E. 85.1 ft., shows good scar.
(Find bearing to be N. 4° E.)
18" Cedar, now 22", S. 42½° W. 34.3 ft., scribe visible ¼ S4 BT.
Set - ¾" Iron Rod at ¼ Corner in Creek Bed.
Brass Cap for Wit. Cor. Mkd: County Surveyor's Office, 1966 — T31S Wit. Cor. 25' N. To ¼ — S 33 / S 4 — R 4W — T32S
New BT's: 9" D. Fir N. 29° W. 30.2 ft. scribed W.C. ¼ S33 CS BT.
23" D.Fir S. 45½° E. 6.0 ft. scribed W.C. ¼ S 4 CS BT.

John M. Powell
Frank Jones & Joe Brady
March 1966
C. S. File No. 54/20

MICROFILM TO HERE 10/67

FD 2" I.R. BY R. BROWN 7/93 M117-58

97

Section Corner to Secs. 7 & 18, R4W and Secs. 12 & 13, R5W.
Found - ½" I.Pipe at Corner, See Renewals No. 2 and No. 53. + 57
9", now 13" Live Oak, N. 4° E. 105.8 ft., shows good scar.
10", now 22" Fir, S.60½°E. 60.3 ft., shows good scar.
Note - 13" Live Oak to be cut down.
New BT: 6" D.Fir N. 2° E. 87.5 ft. mkd: "T32S R4W S7 CS BT".
Power Pole N. 21½°W. 24.0 ft., Pole No. E3457 (ABA10)

C.S. File No. 54/114 7/18/69

SEE C.S. 62/16 FOR MARCH 1984 CORNER REPORT. L.B. MONREAN, DOUG. CO. J.R.

(FD 2" BAR 1½" BLM REC. DID NOT FIND B.I.R.)