

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 32 S. T. S. R. 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

North 1/16 section corner btwn. Sections 7 and 12. (Rgs. 5+4) **98**  
 Set at 1320 feet which is the proportionate distance.  
 There is no iron pipe and the 20" Fir which bears N.80°W., 6.2 ft.  
 is now a sawed stump and scribe marks destroyed. - See M 3 - 32.  
 Set - 1" iron pipe 3' long 28 ins. in the ground, mkd. RS404,  
 from which: 10" D.Fir bears N.10½°E. 14.6 ft. mkd:N 1/16S 7 RS #04 BT.  
 20" D.Fir bears S.80°W. 20.2 ft.mkd: N1/16 S12 RS #04 BT.

Section Corner to Secs. 6 & 7, T32-4W. & Secs. 1 & 12, T32-5W. **99**  
 Found - L" Iron Pipe 4" above the ground, firmly set, See Ren. #36,  
 remains of a pipe burned out bears N. 54° E. 26.8 ft.  
 24" B.Oak bears S. 80° E. 47.4 ft. healed.  
 24" B.Oak bears S. 44° W. 121 ft. with mks. burned out.  
 30" B.Oak bears N. 5° W., 95.2 ft., healed.  
 New BT's: Yellow Pine, 10 ins., bears N. 44° E. 17.7 ft. mkd.  
 "T32S R4W S 6 RS 404 BT."  
 Yellow Pine, 12 ins., bears S. 37° W. 57.3 ft. mkd.  
 "T32S R5W S12 RS404 BT."

N.W. 1/16 section corner of Section 7. **100**  
 Do not find an iron pipe at this corner so determine the corner  
 point from a BT, See C.S. File M 3 - 32:  
 18" Ash bears S. 55° W. 37.5 ft. with scribe marks 1/16 BT  
 exposed.  
 Set - 1" Iron Pipe 3 ft. long, 28 ins. in the ground mkd. RS 404,  
 from which new bearing tree:  
 14" Cedar bears S. 11° W. 30.3 ft. mkd. NW 1/16 S 7 RS404 BT.

Closing Corner to Sections 34 and 35. **101**  
 The S.E. Section Corner of Section 34, T32S, R4W WAS a stone  
 which has been destroyed by a cat fire trail on a BLM timber Sale.  
 I replaced the corner as follows:  
 Set - 1" x 30" Iron Pipe, 10" above ground level.  
 Used compass and steel tape.  
 Two original bearing trees remain:  
 24" D. Fir Bears 96 lks. distance.  
 30" D. Fir bears 50 lks. distance.  
 July 31, 1968

¼ Corner to Sections 25 only, T32-4W. **102**  
 Found - Corner Stone, 14x8x8, firmly set mkd: "¼" on west face.  
 Orig. 18" D.Fir, now snag, S.82°W. 4.6 ft., opened for scribe.  
 Orig. 30" D.Fir, now stob, N.21°W. 27.1 ft., face burnt.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's R T 32 S R  
 Office 4 ½ 3  
 1969 W S 25 W  
 New BT's: 6" D.Fir S.6°W. 10.0 ft. mkd: "¼ S25 CSBT".  
 12" D.Fir N.14°W. 26.7 ft.mkd: "¼ S25 CS BT."

C.C. Section Corner to Sections 19 & 30 only, T32-3W. **103**  
 Found - No trace of Corner Stone, probably slid down mountain.  
 Orig. 36" Fir, now stob, N.89°E. 80.5 ft., scribe visible.  
 Orig. 40" Fir, now 40" S.82°E. 73.9 ft., burnt face.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S  
 Office R S 19 R  
 1969 4W CC S25 S 30 3W  
 New BT's: 12" D.Fir N.44°E. 7.7 ft. mkd: "T32S R3W S19 CC CS BT.  
 12" D.Fir S.59°E. 7.8 ft. mkd: "T32S R3W S30 CC CS BT."

Section Corner to Sections 25 and 36 only, T32-4W. **104**  
 Found - No trace of Corner Stone. Orig. 24", now 28" D.Fir, S.75°W.  
 21.8 ft., shows good scribing and good BT. face.  
 12", now 16" S.Pine, N.1°W. 68.6 ft., shows good scribing.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R  
 Office R S 25 S 30 3  
 1969 4W S 36 W  
 No new BT's. needed. Corner lies about 100 ft. N. of a creek.

Marvin C. Ramsey  
 R. Darrig for A. Cripps  
 June 8, 1967  
 C.S. File No. 55/37 M 34 - 26

By Lorne Swearingen  
 For: S.Ore. Plywood  
 7/31/68  
 C. S. File No. 55/85

John M. Powell  
 Frank Jones & V. Tracy - W. Penley  
 August, 1969  
 C.S. File No. 54/91