

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

1/4 Corner to Sections 9 and 16. 112
Found - 24", now 21" D. Fir, N. 51° E. 12.5 ft., opened for scribe "BT".
66", now 60" D. Fir, S. 15° E. 7.9 ft., shows faint face.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 4 W
Office 1/4 S 9
1970 S 16

Rblzd. & Rscbd: 60" D. Fir S. 15° E. 7.9 ft. mkd: "1/4 S16 CS BT".
New BT: 9" D. Fir N. 45° W. 14.3 ft. mkd: "1/4 S9 CS BT".

- - - - - FD. OK PER ARTMAN 5/6/70
3/16/90 M 109-66 113
Closing Corner to Sections 17 and 20.
Found - Orig. 24" D. Fir Stump N. 38° E. 30.4 ft., has burnt face.
Orig. 26" D. Fir Stump S. 27° E. 56.1 ft., opened for scribe "B".
Ren. #11-1" Iron Pipe set by Wenderoth which bears S. 4° W. 10.7 ft.
5" Chinquapin, dead, N. 77 1/2° E. 53.5 ft. (Rec. N87 1/2 E) rotted scribe vis.
8" Chinquapin, dead, S. 11° E. 13.8 (Rec. S22E 78.8) rotted scribe vis.
Set - Brass Cap at Cl. Cor. Mkd: County Surveyor's T 32 S R 4 W
Office CC S 18 S 17
1970 S 20

New BT's: 11" Cedar N. 71° E. 11.9 ft. mkd: "T32S R4W S12 CC CS BT".
9" D. Fir S. 50° E. 16.7 ft. mkd: "T32S R4W S20 CC CS BT".
6" D. Fir S. 44° W. 13.9 ft. mkd: "S18 CS BT".

- - - - - 5/8/70
Closing Corner to Sections 19 and 20. 114
Found - 1" Iron Pipe at Sec. Cor. (Cl. Cor.), See Ren. #31.
18" D. Fir, now stump, S. 86° W. (Rec. N86W) 76.4 ft.,
scribe visible "S19 CS BT".
8", now 14" Hemlock S. 28° E. 45.0 ft., shows good scar.
New BT: 8" D. Fir S. 86° W. 48.6 ft. mkd: T32S R4W S19 CC CS BT.
This corner lies in logged area in bottom of ravine, running north.

- - - - - FD. OK PER ARTMAN
M 109-66 3/16/90 115
S. E. Corner Section 18.
Found - 1 1/2" Iron Pipe at Sec. Cor., See C.S. File 38/246 (Wenderoth)
20" D. Fir, now stump, S. 59° W. 8.6 ft., opened for scribe.
No trace of S. E. Bearing Tree. - No trace of Orig. Tree.
New BT's: 20" D. Fir N. 70° W. 10.6 ft. mkd: T32S R4W S18 CS BT.
6" D. Fir N. 1 1/2° E. 26.2 ft. scribes "CS BT".
This corner lies in old cut unit, no other trees available.

- - - - - 5/12/70
1/4 Corner to Sections 19 and 30. 116
Found - 36", now 52" D. Fir, N. 11° E. 87.1 ft., opened for scribe "S".
No trace of other BT. (S52W)
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 4 W
Office 1/4 S 19
1970 S 30

New BT's: 10" D. Fir N. 6° W. 11.5 ft. mkd: "1/4 S19 CS BT".
8" D. Fir S. 71° W. 6.2 ft. mkd: "1/4 S30 CS BT".

- - - - - 5/11/70
1/4 Corner to Sections 8 and 17. 117
Found - 10" Laurel, now down, S. 8° E. 4.6 ft., faint rotten scribe vis.
12" Laurel, now down, N. 15° W. 7.3 ft., rotten scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 4 W #158
Office 1/4 S 8
1970 S 17

New BT's: 38" D. Fir N. 40° E. 26.3 ft. mkd: "1/4 S 8 CS BT".
38" D. Fir S. 59° E. 31.3 ft. mkd: "1/4 S17 CS BT".

- - - - - 5/12/70
1/4 Corner to Sections 34 and 35. 118
Found - 12x10x8 Stone at 1/4 Cor. mkd: "1/4" on west face.
8" D. Fir, rotted stump, N. 20° E. 31.0 ft., found scribe "S B".
14", now 23" D. Fir, N. 21° W. 19.8 ft., shows scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 4 W
Office 1/4 S 34 S 35
1970
D O C O. J A C K C O.

New BT: 16" D. Fir S. 87° E. 33.0 ft.
Good Call on ridge top, approx. 90. ft. S. of said high ridge.
- - - - - 5/18/70

John M. Powell
W. Penley & J. Heritage
C. S. File No. 54/114