

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

119

$\frac{1}{4}$ Corner to Sections 31 and 32.
Found - Unrecorded 1" Iron Pipe near Corner, S.62°W. 2.0 ft.
12", now 28" D. Fir, N.62°E. 40.9 ft., tree opened earlier for
scribe " $\frac{1}{4}$ " & other pitched over scribe marks.
24" Dead Fir, now down & burnt, N.31 $\frac{1}{2}$ °W. 10.6 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 4 W
Office, 1970 $\frac{1}{4}$ S 32 | S 31
New BT's: 22" D. Fir S.30°E. 24.1 ft. mkd: " $\frac{1}{4}$ S 32 CS BT".
6" Laurel N.32° W. 20.3 ft. mkd: " $\frac{1}{4}$ S31 CS BT".

5/22/70

120

$\frac{1}{4}$ Corner to Section 25 and 36.
Found - 12X8X7 Stone, firmly in place, mkd: " $\frac{1}{4}$ " on N. face.
42" D. Fir, now snag, N.9°W. 35.0 ft., burnt face, faint scribe
marks visible.
No trace of S.E. BT. due to old logging.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 4 W
Office 1970 $\frac{1}{4}$ S 25 | S 36
New BT's: 12" W. Fir N.75°W. 6.3 ft. mkd: " $\frac{1}{4}$ S25 CS BT".
6" D. Fir S.56°E. 19.8 ft. mkd: " $\frac{1}{4}$ S36 CS BT".

Doug. Co.
Jack. Co.

5/28/70

121

$\frac{1}{4}$ Corner to Section 30 and 31.
Found - 6", now 12" D. Fir, S.72°W. 40.9 ft., opened for scribe " $\frac{1}{4}$ ".
20" D. Fir, now snag, N.18 $\frac{1}{2}$ °E. 29.0 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 4 W
Office 1970 $\frac{1}{4}$ S 30 | S 31
New BT's: 6" D. Fir N.51°W. 10.1 ft. mkd: " $\frac{1}{4}$ S30 CS BT".
6" D. Fir S.28°W. 24.9 ft. mkd: " $\frac{1}{4}$ S31 CSBT".

5/20/70

122

Section Corner to Sections 29 - 30 - 31 - 32.
Found - 40", now 48" D. Fir, N.15°E. 32.3 ft., shows good scar.
10", now 22" D. Fir, S.26 $\frac{1}{2}$ °W. 75.9 ft., shows good scar.
24" D. Fir, now stump, N.68 $\frac{1}{2}$ °W. 50.2 ft., opened for scribe.
No trace of S.E. Laurel BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 4 W
Office 1970 S 30 | S 29
S 31 | S 32
New BT's: 13" Y. Pine N.74°W. 24.1 ft. mkd: "T32S R4W S30 CS BT".
6" D. Fir S.40°E. 24.4 ft. mkd: "T32S R4W S32 CS BT".

This cor. lies on S. slope about 450.0 ft. S. of ridge top, good N-S
blazed line.

5/20/70

123

Section Corner to Secs. 24 & 25 only, T32-5W.
Found - 1" Iron Pipe at Section Corner, See Ren. #52.
40" D. Fir South 40.1 ft., opened for scribe "3".
Hit 2 Laurels (Orig. BT's.) for Bear. & Dist., rotted, possible shoots
from old trees found, no scribing.
New BT: 18" D. Fir N.11°W. 58.9 ft. mkd: "T32S R4W S24 CS BT".

5/13/70

124

$\frac{1}{4}$ Corner to Sec. 18, T32-4W. and Sec. 13, T32-5W.
Found - 1" Iron Rod at $\frac{1}{4}$ Corner, See Ren. #15, T32-4W.
Scribed Post " $\frac{1}{4}$ S 18 - 13".
16" Fir, now stump, N.76°W. 29.7 ft., scribe visible.
No trace of S.E. BT, skid road.
New BT: 13" D. Fir S.48°W. 48.3 ft. mkd: " $\frac{1}{4}$ S13 CS BT".
No other trees available.

Location Tag on Fir Stump near old logging road bears west 80.0 ft.

5/13/70

John M. Powell
W. Penley & J. Heritage
C.S. File No. 54/114

#153