

Douglas County Surveyor's Record of
Government Corners Renewed

32 T. S. 4 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

136

Cont.

11" Fir, bears N.44°E., 15.2 ft. to face; scribed T32S R4W S31 AP BT.
10" Fir, bears N.80°W., 20.1 ft. to face; scribed T32S R5W S36 AP BT
RS 359.
Set - 4" x 4" x 72" white painted Cedar post 2.5 ft. S.44°E. of corner
pipe. Oregon State Forestry Department metal location poste on 11" Fir
N.44°E., 15.2 ft. Also poster on 10" Fir N.80°W., 20.1 ft.
5/30/72

Oregon State Bd.
of Forestry
Arnold Gibson
Lloyd D. Smith
May 30, 1972
C.S. File 55/ 3

137

1/4 Corner East Boundary Sec. 36, T32-5W.
Set-Ore.St.Bd.of Forestry 1 1/2"x36"Galv.I.P. with
3" B. Cap 34" in ground.
7" Fir S.22°W. 22.3 ft.
20" Fir N.65°W. 67.9 ft., Yellow Metal Loc. Poster(RS359)
12" Cedar S.38°E. 14.8 ft., YMLP
4"x4"x72"White Painted Cedar Post N.56°E. 6.4 feet.

Ore.St.Bd.of
Forestry
Gibson, A.
Filed 11/72
Map File
M 47

8/15/72

JAN. 1973 2

138

1/4 Corner for Sections 27 and 34.
Diligent search was made for original 1/4 corner with negative results.
Set - By proportionate measurement, a 3/4" x 36" Gal. I.P. with 2:
brass cap stamped: T32SR4W 1/4 27 cor 1976,
exposed 6" from which: 34

New BT's -

Scribed an 8" D. Fir, "1/4S - BT" which bears North 80° East,
3.8 ft. to the face of the lower blaze.
Scribed an 8" D. Fir, "1/4S - BT" which bears South 45 1/2° East.
5.6 ft. to the face of the lower blaze.

*Fd. B.C. 7/90
M 110-28*

Mark E. Boyden R.I.
For: Boise Cascade Corporation
July 26, 1976
M 61 - 7 C.S. 58/112

139

Center 1/4 Corner for Sec. 34
Set - 3/4" x 36" Gal. I.P. with a 2" brass cap stamped: T32SR4W
Ctr 1/4 cor. S34 1976, exposed 3" from which:

New BT's -

Scribed a 3" D. Fir "C 1/4 - BT" which bears South 72° East,
46.1 ft. to the face of the lower blaze.

7/26/76

140

1/4 Corner for Secs. 6 and 5.
Found - A 30" Fir stump bears S.15°E., 46.8 ft. with visible scribing
"1/4" on open face. Ren. #13

A 60" Fir stump bears S.47°W., 114.0 ft., 36" diam. at time of
Ren. #13. No visible scribing or blaze

A 6" now 14" Madrone, bears N.22°E., 66.7 ft. healed single
blaze on most southerly trunk on triple trunk tree. 1959 Resurvey

A 10" now 22" Madrone bears S:25°W., 54.1 ft. no blaze or scribing
visible.

Set - 5/8" I. R. with Alum. cap marked "T32S R4W S6 S5 1/4 1979" at
record distance and bearings of BTs.

Corner falls in ditch alongside Cow Creek Rd. County maint. crew destroyed
former monument.

New Accessories:

A 5/8" I. Rod bears N.45°W., 30.0 ft. for B0 in NW quadrant. Iron
Rod flush with ground.

1/17/79

141

Corner #3 of Mineral Survey #148, (in Sec. 33)

Found - A sawed fir stump 24" bears S.67 3/4°E., 20.5 ft. with scribe marks
BT visible on opened face. (Rec. N.64°E. 31 lks.) The face of
blaze fits the S. 67 3/4°E. bearing, it is my assumption that
Briggs erred when he recorded the bearing to this tree.

A sawed fir stump, 36" bears S.20 1/4°W., 18.5 ft. no blaze
visible, the stump has been cut too low to leave the blaze.
(Rec. S.22°W., 28 lks.)

Set - An iron rod, 5/8" 20 ins. in the ground

New BT - 25" Fir bears N.89°E., 19.1 ft. mkd. X BT.

8/17/79

Terrence Nickerson
For: Bureau of
the Land Management
Prelim. Administra
tive survey.
Medford District
Aug. 17, 1979
M 78 - 42
C.S. 58/206

Karen Reed
Terrie Plouff
Doug. Co. Sur
veyors Office
Jan. 17, 1979
C.S. 60/24

RE-RENEWED CORNER NO. #146

*B.S.
12/30/98*

1-29