

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 32 T. S. R 4 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21991

Terrence O. Nickerson
LS #649
For: Bureau of Land
Management
Preliminary Admini-
strative survey.
Medford District
Aug. 17, 1979
M 78 - 42
C.S. 58/206

142

Corner #5, Mineral Survey #148 (Sec. 33)
Found - No wood post found.
Found 10" Madrone, bears N.20°E., 11.9 ft. with no visible
mks. (Rec. N.20°E., 8.6 ft.)
Fd. 18" Madrone bears S.28°W., 20.0 ft. with no visible mks.
(Rec. S.28°W., 21.1 ft.)
Set - 5/8" iron rod, 24" lon, 20" in the ground.
New BT's- 25" Fir, bears N. 56 3/4°E., 28.6 ft. mkd. X BT.
15" Fir, bears S. 8 1/2°E., 8.6 ft. mkd. X BT.
8/17/79

143

Corner #6, Mineral Survey #153.
Found - A 42" Fir, bears N.22°E., 15.8 ft. with mks. No. 6 MS 153 BT
on bark.
Set - An 5/8" Iron rod, 24" long, 20 ins. in the ground.
New BT - A 8" Fir, bears N.82 1/2°W., 27.0 ft. dist., with blaze and
spike at base.
8/17/79

Terrence O. Nickerson
LS #1649
For: B.L.M.
October 1979
M 80 - 71

144

1/4 Cor. Sec. 1 and Sec. 6, T. 32 S. R. 3 W. Ren. #48
Found - 2 ins. diam., iron pipe firmly set and protruding 6 ins.
above ground.
Remains of the remaining original bearing tree, a sawed
fir stump, 21 ins. diam., bears N. 68°E., 5.3 ft. dist.,
with no mks. visible on rotted opened blaze.
Bearing tree marked by Wenderoth, a fir snag, 24 ins.
diam., bears N. 48° W., 12.0 ft. dist., with bark scribe
mks. 1/4S T32S R4W visible. (Measured to face.)
New BT - A fir, 8 ins. diam., bears S. 61 3/4° W., 14.5 ft. dist.,
mkd. 1/4 S1 BT.

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
John Powell - Randy
Smith
Dec. 20, 1982
C.S. 62/1

145

1/4 Corner for Sections 17 and 20
Found - 2 1/2" I.P. with 1971 BLM brass cap attached, firmly set 0.4 ft.
North of fence corner.
Orig. 8" now 28" madrone, bark gone blaze not visible, bears
N.78°W., 13.8 ft. Tree is dead and soon to be cut down. I
move BT tags to base of tree.
10" now 19" fir, Ren. #16, with good double blaze bears S.46°W.,
47.8 ft.
8" now 13" fir per resurvey, with good single blaze bears
N.28 3/4°E., 47.5 ft.
New BT - 11" cedar scribed "1/4 S17 CS BT" in double blaze bears
N.76°E., 64.6 ft.
Douglas Co Surveyor Office BT tags on all trees.
12/20/82

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
John Powell - Randy
Smith
Jan. 12, 1983
C.S. 62/7

146

1/4 Corner for Secs. 5 and 6
Found - 5/8" iron rod with alum. cap. Ren. #140 Monument is located
in ditch on North side of Cow Creek Road.
30" fir stump, Ren. #13, with scribed "1/4 visible bears
S.15°E., 46.8 ft.
36" fir, Ren. #13, now 60" stump with no face visible bears
S.47°W., 114.0 ft.
6" madrone, per resurvey, now 14" with good scar on most southerly
trunk of a triple trunk tree bears N.18°E., 66.7 ft. (Rec.N22°E)
10" madrone, per resurvey, now 22". No good blaze visible bears
S.25°W., 54.1 ft.
5/8" iron rod set flush with the ground, Ren. #140, bears
N.45°W., 30.0 ft.
Since found monument is in a location where it is continually being disturbed
by road maintenance crews, I SET a 1" x 30" I.P. with brass cap attached
for WITNESS CORNER. Cap mkd. "Douglas County Surveyors Office T32S R4W
Wit. Cor. S22 W 41' to 1/4 S6 S5 1983".
Witness corner bears N.22°E., 41.0 ft. from 1/4 corner. Witn. cor. is set
along the westerly side of a North-South fenceline.