

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 32

T. S.

R 4

R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

146

CONT - - -

New BTs - 14" madrone per resurvey bears N.13°E., 26.6 ft. from wit. cor.
22" madrone per resurvey bears S.24 1/2°W., 99.1 ft. from wit. corner.
30" fir stump per Ren. #13 bears S.2°W., 83.3 ft. from wit. cor.
5/8" iron rod per Ren. #140 bears S.66 1/2°W., 40.7 ft. from witness corner.

Gregory Quibell, Deputy
Douglas Co. Surveyors Off.
John Powell - Randy Smith
Jan. 12, 1983
C.S. 62/7

1/1/83

1/4 Corner for Section 6; and Section 1 of T.32-5.

147

Found - 3/4" iron pipe with metal tag stamped "RE 3024". Ren. #69
12" fir, now 19" diam. fir snag, 4 ft. tall, bears N.52 1/2°W.
34.1 ft. scribing is visible, "1/4 2". (Rec. N.54°W. 34.3')
22" fir now 24" diam. stump (tree down with scribing "RE 3024") bears S.15 1/2°W., 44.0 ft. (Rec.)

Set - We reference iron pipe and replace with 2 1/4" brass cap on 1" x 30" pipe and mound rocks around monument. 3/4" iron pipe is buried alongside. Brass cap mkd. "Douglas County Surveyor T32S R5W 1/4 S1 S6 R4W 1984".

New BTs - 11" incense cedar, center of base bears N.23 1/2°W., 57.6 ft. and scribed "1/4 S1 CS BT" on a double blaze.
12" maple, center of base bears S.58°W., 35.9 ft. and scribed "1/4 S1 CS BT" on a double blaze.
12" maple, center of base bears S.34 1/2°E., 13.2 ft. and scribed "1/4 S6 CSBT" on a double blaze.
10" fir, center of base bears S.83°E., 25.0 ft. and scribed "1/4 S6 CS BT" on a double blaze.

Larry E. Monrean
Deputy, Douglas Co.
Surveyors Office
J. Lundeen
R. Smith
Nov. 7, 1984
C.S. 62/11

11/7/84

148

1/4 Corner for Sections 5 and 4

Found - 1959 BLM disk on an I.P. protruding 11 in. above ground, properly marked.

1 inch I.P., Ren. #34 reset along side BLM I.P. not found protruding above ground. We did not disturb ground around BLM I.P. to look for 1 inch iron pipe.

30" now a 41" dia. 1 1/2 ft. high Ponderosa pine stump with partial scribe visible "BT" bears N. 1 1/2° W., 91.9 ft. (Rec. N.2°50'W, 90.9 ft.) dist. is to face of blaze per Ren. #34 (Rec. N.3°W., 99.7 ft. dist. is in error per 1959 remon. of proportioned cor.)

24" now a 27" dia. Ponderosa Pine with a well healed double blaze, bears N.31 1/2°E., 70.0 ft. (Rec. N.33°13'E., 69.1 ft. dist. is to face of blaze per Ren. #34) (Rec. N.34 1/4°E., 68.6 ft. dist. is to edge of bark per 1959 remon. of proportioned corner.)

New BTs - 11" dia. I. cedar double blazed and scribed "1/4 S5 CS BT" bears S.52°W., 6.8 ft.

7" dia. D. fir double blazed and scribed "1/4 S5 CS BT" bears N.60°W., 65.2 ft.

9" dia. P. Pine double blazed and scribed "1/4 S4 CS BT" bears S.62 1/2°E., 47.7 ft.

Corner lies in a N-S fence line.

8/21/85

149

1/4 Corner for Section 7; and Section 12 of T.32-5

Found - 1956 County brass cap properly mkd. on an I.P. firmly set and protruding approx. 4 ins. above ground. Ren. 67

Monument was not disturbed to check for Iron bar in Ren. #5

10" fir now a 34" DBH D. fir with a fully healed double blaze bears N.56°E., 143.9 ft. dist. (Rec. N.56°E., 143.0 ft., a possible face meas.) Ren. #59

12" live oak now an 18" DBH live oak with a fully healed double blaze bears N.84°E., 163.8 ft. (Rec. N.85°E., 163.0 to center of trunk blaze height.) Ren. #67

No evidence of NW BT found from Ren. #59. No evidence of original bearing trees found.

New BT - An apple tree, 7" in dia., 1 1/2 ft. above ground (stunted, no DBH poss.) bark scribed "X BT: bears N.87 1/2°W., 31.0 ft.

New BO - A power pole marked COPCO E 698 AB39 bears S.0 1/2°W., 40.9 ft. Corner is approx. 900 ft. north of Yeust Rd. #287 and approx 500 ft. east of Cow Creek, near west end of driveway to B.B. Lawrence residence.

Doug. Co. Surveyors
Office
Stephen J. Flause,
Party Chief
Randall Smith,
Notekeeper
Aug. 21, 1985
C.S. 62/29