

Douglas County Surveyor's Record of
Government Corners Renewed

32 T. S. 5 R. W. W. M.

COKE-CHAPMAN CO., EUGENE, ORE. 97198

G. Wenderoth
Wit: Chas. Leiser
June 1951

SECTION CORNER BETWEEN SECTION 26 - 27
Place $\frac{1}{2}$ way bet. Sec. corners $\frac{3}{4}$ " I. Pipe
20" Madrone, N. 50° 43' W. 42.5 feet
12" Fir, N. 6° 16' E. 30.0 feet

TRANS. TO
T. 30 S. R. 5 W.

36

Geo. Wenderoth
Wit: F. Dean
August 1951

CORNER SECTIONS 1 - 2 - 11 - 12

Found Yew stake and 16" Fir, N 61° W. 4.6 feet
Drive $\frac{3}{4}$ " I. Pipe

SAME AS
46

Scribe 12" Fir, N 34° 15' W. 90.6 feet
20" Fir, S 60° 15' W. 48.9 feet
18" Fir, N 86° 07' E, 49.2 feet
16" Fir, S 75° 22' E. 44.5 feet

37

Surveyor:
Wenderoth
Feb. 1952

SECTION 20 CENTER SECTION:

$1\frac{1}{2}$ " Iron Pipe
36" Fir S. 21 degrees 56' East, 123.5 Ft.
12" Fir S. 79 degrees 22" East, 146.9 Ft.

SAME AS # 104
SEE OVER

38

SECTION 30 N. E. CORNER of N. W. $\frac{1}{4}$ of S. E. $\frac{1}{4}$:

~~1 $\frac{1}{4}$ " Iron Pipe
12" Madrone S. 67 degrees 48' East, 47.8 Ft.
16" Fir N. 5 degrees, 05' East, 30.3 Ft.~~

NOT
RECORDED
(CHECKED 7-66)
LL

~~1/16 SOUTHEAST CORNER OF S. W. $\frac{1}{4}$ of S. E. $\frac{1}{4}$:~~

~~3/4" Iron Pipe
32" Maple S. 87 degrees 54' West, 8 Ft.
16" Maple N. 22 degrees 35' West, 39.6 Ft.~~

39

SECTION 19: West $\frac{1}{4}$ cor

~~1" Iron Pipe - 8-17-1967 - CORNER O.K. # 20
12" Oak which bears S. 78 degrees 20' West, 59.2 Ft.
14" Oak which bears N. 12 degrees 45' East, 194.0 Ft.~~

LOCATED IN FENCE CORNER
C.B. 53/52

M27-12

40

SECTION CORNER 19 and ~~20~~³⁰: S. W. Cor SEC. 19

1 $\frac{1}{4}$ " Iron Pipe
16" White Oak which bears S. 43 degrees East, 37.6 Ft.
16" Pine which bears N. 78 degrees 25' East, 29.2 Ft.
22" Pine which bears N. 75 degrees 19' West, 39.5 Ft.
15" Fir which bears S. 25 degrees 42' West, 44.9 Ft.

SAME AS # 16

SEE CORNER NO. 162

41

QUARTER CORNER SECTIONS 19 and 30:

3/4" Iron Pipe
20" Ash S. 75 degrees 20' East, 24.3 Ft.
14" Ash N. 42 degrees 20' West, 43.2 Ft.

SAME AS

28
CORNER O.K. AUG. 1967
J.M.P.

42

SECTION CORNER OF SECTIONS 19, 30, 20, 29:

1/2" Iron Pipe
20" Alder N. 57 degrees 02' West, 28.5 Ft.
14" Ash N. 73 degrees 20' East, 57.3 Ft.
14" Alder S. 52 degrees 15' West, 59.5 Ft.
8" Alder S. 71 degrees 10' East, 19.2 Ft.

SAME AS

31

43

QUARTER CORNER SECTIONS 19 and 20:

5/8" 1 Rod
32" B. Oak S. 29 degrees West, 31.7 Ft.
10" Fir N. 62 degrees 30' East, 26.0 Ft.

SAME AS # 29

102
SEE OVER

See # 11 & 8

44

NORTHEAST CORNER DONLATION LAND CLAIM NO. 39:

3/4" Iron Pipe
24" White Oak bears S. 35 degrees West, 34.3 Ft.
24" Fir bears N. 41 degrees 30' West, 9.2 Ft.
8" Black Oak bears S. 78 degrees 15' East, 14.1 Ft.

SAME AS

18 & 61

G. J. Wenderoth
January 1951