

Douglas County Surveyor's Record of
Government Corners Renewed

32 T. S. 5 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97196

Southeast corner of the D. A. Levens Donation Land Claim No. 38.
Fir stump.

24" Cedar, N.40°55'W., 51.8 feet.
10" Maple, S.45°10'W., 22.6 feet.

71

George Wenderoth
1955

C. S. File No.
46/148

C.S.M 7-53

1/4 corner to secs. 11 and 14.

Found BTs as renewed by Wenderoth in 1952. The NE BT is a stump only (Pine)
scribed 1/4 S BT. BTs check for bearing and distance.

Also found 3/4 inch iron pipe at corner under N - S fence.
I blaze and scribe:

36 inch Pine, S.83°E., 108.7 feet, mkd 1/4 S CS BT.

8/31/71 Remove I.P. & Set Brass Cap. L.S.#5, at 1/4 Corner-Pine BT. in good shape.)

RE-RENEWED, SEE CORNER NO. #211

FD OK 7/17
RE-RENEWED M78-29
(Wenderoth)

James W. Byron,
Dep. County
Surveyor
Mar. 28, 1956.
C.S. File 47/75.

1/4 corner to secs. 13 and 24.

Corner not found; set by single proportion.

Set 1 inch Channel Bar, and scribed:

A 1 1/4 inch Fir, S.43°30'E., 39.2 feet, mkd. 1/4 S 24 RE 3024 BT.
A 48 inch Fir, N.24°05'E., 65.4 feet, mkd. 1/4 S 13 RE 3024 BT.

SEE ALSO
REN. #262

73

Richard L. Templin Jr., - Partial Sub. of sec. 24, for Sierra
Land Co.
April 30, 1956.
C. S. File No. 42/133.

Section corner to secs. 13 & 24, T 32 S., R 5 W., and secs. 18 & 19, T 32 S.,
R 4 W.

Found 1 inch iron rod.

Found Stump of 20 inch Fir, S.45°W., 34 lks.

Found County Surveyors B. T.s:

8" Chinquapin, N.55°W., 8.2 feet.
12" Fir, S.22°E., 13.5 feet. (Blaze healed)

Scribed new B. T.:

An 8 inch Fir, N.09°W., 8.6 feet, mkd. S 13 RE 3024 BT.

FD OK PER ARTMAN
3/16/90 M 109-66

74

Section corner to secs. 24 & 25, T 32 S., R 5 W., and ~~secs. 19 & 20,~~
~~T 32 S., R 4 W.~~

Found two orig. B.T.s:

10 inch Madrone, S.11°W., 98 lks. - no scribing.
10 inch Madrone, N.07°W., 58 lks. - no scribing.

Found 5 1/4 inch line tree with notches, S. 257 feet.

Scribed New B.T.:

34 inch Fir, South, 40.1 feet, marked S 25 RE 3024 BT.

NOT COMMON CORNER
FROM B.T.s (?)
THIS MUST BE COR.
SECS. 24 & 25 ONLY

75

1/4 corner to secs. 24 & 25.

Found 50 inch Fir with bark scribe, N.85°W., 75 lks. (slope).

Found rotted stump 30 inch Fir, South 20 lks.

Set rock, 3 inches x 8 inches x 14 inches mkd. 1/4 N face.

Scribed:

12 inch Fir, S.15°10'W., 44.7 feet mkd. 1/4 S 25 RE 3024 B. T.

76

Center 1/4 sec. corner to section 12.

1 inch pipe.

From which:

8 inch Maple, S.62°50'W., 23.6 feet.
12 inch Fir, S.21°30'E., 73.9 feet.

FD OK PER HULL
1-89 M107-39

77

George J.
Wenderoth
1956.
C. S. Map File
No. M 3 - 9.

Section corner to secs. 20, 21, 28 and 29.

Found angle iron at corner point.

Marked two trees:

10 inch Fir, N.74°45'W., 45.3 feet.
34 inch Pine, S.55°30'E., 72.1 feet.

RE-RENEWED, SEE CORNER NO. #219

78

George J.
Wenderoth
July, 1956.
C. S. File No.
47/94.