

Douglas County Surveyor's Record of  
Government Corners Renewed

32 S T. S. 5 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Geo. Wenderoth  
1955.  
C. S. File No. 46/148.

$\frac{1}{4}$  sec. corner to secs. 21 and 22.  
 $\frac{1}{2}$  inch Iron Pipe.  
From which:  
48 inch W. Oak, S.50°E., 25.7 feet.  
16 inch Pine, N.71°16'E., 68.6 feet.

RENEWED, SEE CORNER NO. 170

79

George Wenderoth  
July, 1952.  
C. S. File No. 45/99M 7-53

$\frac{1}{4}$  sec. corner to secs. to 15 and 16.  
 $\frac{5}{8}$  inch iron Bolt.  
From which:  
18 inch B. Oak, N.19°30'W., 96.7 feet.  
8 inch Madrona, S.64°30'E., 26.2 feet.

RENEWED, SEE CORNER NO. 146

80

$\frac{1}{4}$  sec. corner to secs. 16 & 17.  
1 inch Iron Pipe.  
11 inch Madrona, S.51°25'E., 17.6 feet.  
8 inch Madrona, N.38°30'W., 11.0 feet.

FD. OK 3/92 BY A. RAMBO  
M114-7B

80-A

Section corner to secs. 9, 10, 15 and 16.  
 $\frac{3}{4}$  inch Iron Pipe.  
50 inch B. Oak, S.52°E., 171.6 feet.  
7 inch W. Oak, S.22°W., 42.1 feet.  
12 inch W. Oak, N.69°05'E., 47.0 feet.

RENEWED, SEE CORNER NO. 144

80-B

George Wenderoth  
1953  
C. S. File No. 45/136.

Section corner to secs. 12 & 13, T 32 S, R 5 W., and secs. 7 & 18, T32S, R4W.  
 $\frac{1}{2}$  inch iron pipe.  
From which:  
10 inch Fir, S.60°35'E., 60.3 feet.  
9 inch Live Oak, N.4°06'E., 105.8 feet.

RENEWED, SEE CORNER NO. 178

81

CORNER O.K. - J.M.P.  
AUG. 1967

Section corner to secs. 12 & 13, T32S, R5W., and secs. 7 & 18, T32S, R4W.  
Set an iron bar from 2 O. B. T. stumps. Others gone.  
Marked:  
24 inch Fir, N.16°E., 183.2 feet.  
30 inch Fir, N.71°E., 216.0 feet.  
No other trees available.

RENEWED, SEE CORNER NO. 81

82

G. G. Stewart, Deputy County Surveyor  
May, 1922  
See Vol. 3, P.121.

Section corner to secs. 1 & 12, T32S, R5W., and secs. 6 & 7, T32S, R4W.  
Set an iron pipe from 2 O. B. T.s. Others gone.  
Marked:  
A 30 inch Pine, N.54 $\frac{1}{2}$ °E., 26.8 feet. (O. B. T.)  
A 10 inch B. O., S.30°E., 47.4 feet.  
A 20 inch B. O., N.5°W., 95.2 feet.  
An 18 inch B. O., S.44°W., 121.0 feet.

RENEWED, SEE CORNER NO. 35

83

$\frac{1}{4}$  corner to sec. 12, T32S, R5W.; and sec. 7, T32S, R4W.  
Set an iron bar from stump of O. B. T.  
Marked:  
A 12 inch Fir, N.89°W., 218.0 feet.  
A 10 inch Fir, N.56°E., 143.0 feet.

RENEWED, SEE CORNER NO. 109

84

George J. Wenderoth  
Nov. 7, 1956  
C. S. File No. 47/139.

Closing corner to secs. 25 and 36.  
Found old original stake still in ground. Renewed stake.  
Found stump of 40 inch Fir, S.10°W., 46.2 feet, no marks.  
Found burnt yew stump N.24°W., 36.3 feet, no marks.  
Scribed:  
8 inch Fir, S.10°25'W., 15.0 feet.  
12 inch Fir, N.37°57'W., 39.7 feet.

RENEWED, SEE CORNER NO. 129

85