

Douglas County Surveyor's Record of  
Government Corners Renewed

32 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 corner to secs. 10 and 15.

Found: 26 inch B. O., N.8°E., 106.9 feet partly dead.  
12 inch B. O., S.7°E., 17.2 feet dead.

Drove a 3/4 inch iron pipe at corner point.

Marked:

16 inch B. Oak, S.32°W., 11.3 feet.  
18 inch B. Oak, N.57°40'E., 70.2 feet.

Distance between the corner above and the corner to secs. 9, 10, 15 & 16,  
is 2692.6 ft. course S.89°34'E.

86

Geo. J. Wenderoth  
July, 1956.  
C. S. File No.  
47/98.  
Map File No. M5-27.

North 1/4 corner to section 27.

1 1/2 inch iron pipe.

From which:

8 inch Fir, S.50°55'W., 18.7 feet.  
10 inch Madrona, N.52°25'E., 29.0 feet.

COR. O.K. AUG. 1967 J.M.P.

RE-RENEWED SEE CORNER NO. #207

87

George J. Wenderoth  
January, 1956  
C. S. File No. 42/88.

1/4 corner to secs. 27 and 28.

1 1/2 inch iron pipe.

From which:

32 inch Fir, S.84°50'E., 25.7 feet.  
16 inch Fir, N.68°10'W., 9.8 feet.

88

1/4 corner to secs. 27 and 34.

1 1/2 inch iron pipe.

From which:

28 inch Fir, S.87°E., 33.6 feet.  
30 inch Cedar, N.62°45'W., 79.4 feet.

FOUND O.K. 7-6-67 V.R.T.

89

North 1/4 corner to sec. 19.

Corner located by proportional measurement.

Drove a 1 1/2 inch iron pipe for 1/4 corner,  
from which:

An 8 inch fir bears N.34°W., 2.3 feet dist., scribed 1/4 S 18 BT, 1543.

A 10 inch Madrone bears S.23°E., 5.4 feet dist. scribed 1/4 S 19 BT, 1543.

90

H. W. Lawrence  
December 23, 1955  
C. S. File No.  
42/78.

North 1/4 corner to Section 23.

One inch Harrow Tooth: 20 inch Cedar S 61°E 81.3

14 inch Cedar S 10°30'E 115.1 - COR. O.K. AUG. 1967 J.M.P.

SEE ALSO #203

RE-RENEWED SEE CORNER NO. #203

91

N.E. Corner Section 23. Corner Common to Sections 14, 13, 23, & 24.

1/2 inch Iron Pipe: 16 inch Cedar S 69°39'W 26.0  
12 inch Fir S 58°30'E 57.4  
12 inch Cedar N 35°W 31.1  
7 inch Cedar N 22°30'E 28.8

92

1/4 Corner to Sections <sup>23</sup> and 24.

One inch Iron Pipe: 18 inch Fir N 60°W 9.9.  
8 inch Cedar S 30°40'W 26.2.

93

S.E. Corner Sections 23, 24, 25, & 26.

3/4 inch Iron Pipe: 30 inch Fir N 16°E 19.8.  
14 inch Fir S 69°34'E 9.0.  
14 inch Fir S 18°20'W 42.5.  
12 inch Fir N 74°W 55.3.

SAME AS

#54

94

George J. Wenderoth, Deputy  
June, 1957  
C.S. File No. 45/154  
M 5 - 28

South 1/4 Corner to Section 23.

3/4 inch Iron Pipe: 26 inch Fir N 78°10'E 67.0.  
26 inch Fir S 8° 30'E 27.0.

SAME AS

#53

95

Corner to Sections 22, 23, 26, & 27.

1/2 inch Iron Pipe in Road: 18 inch Fir N 30°E 18.5. - 11" Cedar S43°45'E 126.0.  
20 inch Cedar N 81°15'E 93.8

SAME AS #52

96

#159